



特性: Specifications;  
 电器: Electrical;  
 接触阻抗: Contact Resistance  
 30 millionms MAX

耐压: Dielectric Withstanding Voltage:  
 500v AC AT Sea Level  
 绝缘阻抗: Insulation Resistance:  
 1000 MEGA ohms MLN

机构: Mechanical;  
 接合为: Mating Force;  
 4.0 KG MAX 最大4Kg

拔出力: Unmating Force;  
 0.7KG MIN.最少0.7KG

PART NO	H
U-A-24DD-W-2	13.00
U-A-24DD-W-3	13.70
U-A-24DD-W-4	15.00

Recommended PCB Layout

③	②	①	ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING
③	Base	—	1	NYLON				White
②	Terminal	—	4	Phosphor Bronze				Ag Plated
①	Housing	—	1	SPCC/Phosphor Bronze				Ni Plated

APPROVALS	DATE	TITLE:
DRAWN	JIANKUN.LU	2015.03.18
		ELECTRONICS CO.,LTD
		USB CONNECTOR

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.	TOLERANCES ARE	ANGLE	UNIT:	SCALE:	PROJ:	SHEET
	A		NEW				30~0.15	±0.30	mm	1:1	PROJ:	1 OF 1
							10~0.25	±0.25				
							5~0.10	±0.20				
							~5	±0.15				

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [USB Connectors](#) category:*

*Click to view products by [HRO parts manufacturer](#):*

Other Similar products are found below :

[950](#) [A-USB B-TOP-C](#) [MUSBA511N5](#) [MUSBC111M5](#) [MUSBD11135](#) [17-200721](#) [217450-1](#) [KMBVX-TH-5S-B30](#) [896-30-004-00-000000](#)  
[KUSBX-AS2N-W](#) [KUSBX-SMT2AP1S-W30](#) [935](#) [957](#) [30-498-6](#) [SK-60A-2](#) [1734082-1](#) [30-1574](#) [30-470](#) [30-489](#) [30-541](#) [30-572-3](#) [A-USB](#)  
[A-2P-C](#) [MIKROE-1451](#) [USBFTV2PEM2G](#) [USBFTVSCCG](#) [4689-1](#) [1-1734084-2](#) [MUSBC11135](#) [USBF21ZNSCC](#) [USBBFTV6ZC](#)  
[MUSBB151341](#) [10135326-001LF](#) [M9177/3-1](#) [TJ-105](#) [USB-A-S-F-B-VT](#) [4198](#) [690-024-633-031](#) [UB-20PMFP-LC7001](#) [USBFTVC6MRG](#)  
[UA-20BMFA-SL8001](#) [17-200011](#) [USBFTVC7ZC](#) [UB-20AFMM-LL7A01](#) [USBFTVC2MN](#) [CAP-WCCMLPB1](#) [1310-1031-01](#) [2041386-1](#)  
[2274475-3](#) [UB-20BMFA-SL8001](#) [UB-20PMFP-SC8003](#)