



- NOTES:
1. MATERIALS AND FINISHES:  
HOUSING MATERIAL:  
PIN MATERIAL:  
CONTACT AREA:  
SOLDER TAIL:  
SHELL MATERIAL: PLATED Ni 500 $\mu$  MIN  $T=0.30$ mm
  2. ELECTRICAL CHARACTERISTICS:  
CONTACT RESISTANCE: 30m $\Omega$  Max.  
DIELECTRIC WITHSTANDING VOLTAGE : AC 500V R.M.S.  
INSULATION RESISTANCE: 1000M $\Omega$  MIN.
  3. MECHANICAL CHARACTERISTICS:  
CONTACT INSERTION FORCE: 35 N MAX.  
CONTACT SEPARATION FORCE: 10 N MIN(AFTER CYCLE 1500).
  4. MATERIAL MUST FULFILL 6174-11 SALICORP HAZARDOUS SUBSTANCES MANAGEMENT STANDARD LATEST VERSION.

APPROVALS		DATE		TITLE		
DRAWN	D.JLV	2017/12/26		ELECTRONICS CO.,LTD		
CHECKED				HDD®		
APPROVALS				PART NO.	U-A-25DD-W-1	
TOLERANCES ARE	30~0.1mm ±0.30	ANGLE		SCALE:	1:1	
	10~30 ±0.20			PROJ:		
	5~10 ±0.15					
	~5 ±0.10	±2'	DRAWING NO.			
ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [USB Connectors](#) category:*

*Click to view products by [HRO parts manufacturer](#):*

Other Similar products are found below :

[950](#) [A-USB A-LP-SMT-C](#) [A-USB B-TOP-C](#) [MUSBA511N5](#) [MUSBC111M5](#) [MUSBD11135](#) [17-200721](#) [217450-1](#) [KMBVX-TH-5S-B30](#)  
[896-30-004-00-000000](#) [KUSBX-AS2N-W](#) [KUSBX-SMT2AP1S-W30](#) [935](#) [957](#) [30-498-6](#) [SK-60A-2](#) [1734082-1](#) [30-1574](#) [30-470](#) [30-489](#) [30-](#)  
[541](#) [30-572-3](#) [A-USB A-2P-C](#) [MIKROE-1451](#) [USBFTV2PEM2G](#) [USBFTVSCCG](#) [4689-1](#) [1-1734084-2](#) [MUSBC11135](#) [USBF21ZNSCC](#)  
[USBBFTV6ZC](#) [MUSBB151341](#) [10135326-001LF](#) [M9177/3-1](#) [TJ-105](#) [USB-A-S-F-B-VT](#) [4198](#) [690-024-633-031](#) [UB-20PMFP-LC7001](#)  
[USBFTVC6MRG](#) [UA-20BMFA-SL8001](#) [17-200011](#) [USBFTVC7ZC](#) [UB-20AFMM-LL7A01](#) [USBFTVC2MN](#) [CAP-WCCMLPB1](#) [1310-](#)  
[1031-01](#) [2041386-1](#) [2274475-3](#) [UB-20BMFA-SL8001](#)