



NOTES:

1. Specifications
- 1-1. INSERT FORCE: 35N MAX.
- 1-2. WITHDRAW FORCE: 10N MIN. INITIAL 8-20N AFTER
- 1-3. Current rating: 1.0A
- 1-4. Voltage Rating: 30V
- 1-5. Life Test: 10000 CYCLES MIN.
- 1-6.: Dielectric withstanding: voltage 100V AC MIN.
- 1-7. Contact resistance: 30mΩ
- MAX. INITIAL: 40mΩ MAX AFTER
- 1-8. Insulation resistance: 100MΩ MIN
- 1-9. Temperature range: -30 TO +80°

APPROVALS		DATE	ELECTRONICS CO., LTD						
DRAWN	D.J.LV	2017/12/26							
CHECKED									
APPROVALS									
TOLERANCES ARE		30~1.1 ±0.30	10~30 ±0.20	ANGLE	PART NO.	TITLE:			
		5~10 ±0.15		±2°	U-A-39DD-W-1	USB CONNECTOR			
ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.	SCALE: 1:1	PROJ. 	SHEET 1 OF 1
	A		NEW						

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [USB Connectors](#) category:

Click to view products by [HRO parts manufacturer](#):

Other Similar products are found below :

[950](#) [A-USB A-LP-SMT-C](#) [A-USB B-TOP-C](#) [MUSBA511N5](#) [MUSBC111M5](#) [MUSBD11135](#) [17-200721](#) [217450-1](#) [KMBVX-TH-5S-B30](#)
[896-30-004-00-000000](#) [KUSBX-AS2N-W](#) [KUSBX-SMT2AP1S-W30](#) [935](#) [957](#) [30-498-6](#) [SK-60A-2](#) [1734082-1](#) [30-1574](#) [30-470](#) [30-489](#) [30-](#)
[541](#) [30-572-3](#) [A-USB A-2P-C](#) [MIKROE-1451](#) [USBFTV2PEM2G](#) [USBFTVC6ZN](#) [USBFTVSCCG](#) [4689-1](#) [1-1734084-2](#) [MUSBC11135](#)
[USBF21ZNSCC](#) [USBBFTV6ZC](#) [MUSBB151341](#) [10135326-001LF](#) [M9177/3-1](#) [TJ-105](#) [USB-A-S-F-B-VT](#) [4198](#) [690-024-633-031](#) [UB-](#)
[20PMFP-LC7001](#) [USBFTVC6MRG](#) [UA-20BMFA-SL8001](#) [17-200011](#) [USBFTVC7ZC](#) [UB-20AFMM-LL7A01](#) [USBFTVC2MN](#) [CAP-](#)
[WCCMLPB1](#) [1310-1031-01](#) [2041386-1](#) [2274475-3](#)