


SPECIFICATIONS

1. Rating : DC 30V 1.5A
2. Contact Resistance: $\leq 50m\Omega$
3. Insulation Resistance: $\geq 1000m\Omega$ Min DC250V
4. Operating Temperature Range: $-40^{\circ}C + 85^{\circ}C$

③	Shell	—	1	SPCC			
②	Contact	—	4	BRASS			
①	Housing	—	1	PBT	Blue		
ITEM	PART NAME	TER.NO.	QTY.	MATERIAL	FINISHING	REMARK	
APPROVALS		DATE					
DRAWN	QFENG.XU	2020/7/1					
CHECKED							
TITLE:		USB CONNECTOR					
PART NO.		U-G-09WS-W-1					
UNIT: mm		SCALE: 1:1					
DRAWING NO.		PROJ.					
		SHEET 1 OF 1					

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			
TOLERANCES ARE 30~φ以上 ±0.30 ANGLE 10~30 ±0.25 5~10 ±0.20 ±2° ~3 ±0.15						



HONGSHAN ELECTRONICS CO., LTD

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [USB Connectors](#) category:

Click to view products by [HRO parts manufacturer](#):

Other Similar products are found below :

[950](#) [A-USB B-TOP-C](#) [MUSBA511N5](#) [MUSBC111M5](#) [MUSBD11135](#) [17-200721](#) [217450-1](#) [KMBVX-TH-5S-B30](#) [896-30-004-00-000000](#)
[KUSBX-AS2N-W](#) [KUSBX-SMT2AP1S-W30](#) [935](#) [957](#) [30-498-6](#) [SK-60A-2](#) [1734082-1](#) [30-1574](#) [30-470](#) [30-489](#) [30-541](#) [30-572-3](#) [A-USB](#)
[A-2P-C](#) [MIKROE-1451](#) [USBFTV2PEM2G](#) [USBFTVSCCG](#) [4689-1](#) [1-1734084-2](#) [MUSBC11135](#) [USBF21ZNSCC](#) [USBBFTV6ZC](#)
[MUSBB151341](#) [10135326-001LF](#) [M9177/3-1](#) [TJ-105](#) [USB-A-S-F-B-VT](#) [4198](#) [690-024-633-031](#) [UB-20PMFP-LC7001](#) [USBFTVC6MRG](#)
[UA-20BMFA-SL8001](#) [17-200011](#) [USBFTVC7ZC](#) [UB-20AFMM-LL7A01](#) [USBFTVC2MN](#) [CAP-WCCMLPB1](#) [1310-1031-01](#) [2041386-1](#)
[2274475-3](#) [UB-20BMFA-SL8001](#) [UB-20PMFP-SC8003](#)