




|   |  |
|---|--|
| <b>7 SOCKET OUTLETS<br/>5 WITH EARTHING PIN</b> | <b>AUTOMATIC FUSE</b>                            |
| <b>SOCKET OUTLETS<br/>SAFE FOR CHILDREN</b>     | <b>SURGE PROTECTION</b>                          |
| <b>ILLUMINATED DOUBLE<br/>POLE MAINS SWITCH</b> | <b>CABLE<br/>MANAGEMENT SYSTEM</b>               |
| <b>2 AVAILABLE<br/>COLOUR VARIANTS</b>          | <b>AVAILABLE CABLE<br/>LENGTHS: 1.5m, 3m, 5m</b> |

**acar P7** is a device with seven protected sockets outlets, 5 of which are round with earthing pin and 2 are unearthed Euro-sockets. Additionally, it is equipped with a system to organize cables allowing for convenient and aesthetic management of power cables extending from the **acar P7** to the appliances. Thus it allows to avoid messy cables under the desk, while protecting sensitive electrical equipment against surges and spikes. **acar P7** is equipped with an automatic fuse, which guarantees simplicity and effectiveness.

#### Technical data: **acar P7**


|                                     |  |
|-------------------------------------|--|
| Maximum load                        | $P_{MAX}$ 2300W  |
| Nominal voltage $U_N$               | 230V   |
| Nominal frequency                   | 50Hz   |
| Nominal load current                | $\Sigma I_N = 10A$ MAX   |
| Surge protection response time      | <25ns  |
| Maximum voltage $U_C$               | 250V 50Hz  |
| Protection level $U_P$              | $\leq 1.3kV$   |
| Nominal discharge current $i_N$     | 2kA (L/N) – 8/20 $\mu$ s   |
| Maximum discharge current $i_{MAX}$ | 6.5kA (L/N) – 8/20 $\mu$ s   |
| Fuses                               | 1 automatic fuse, slow blow 10A/250V   |
| Anti-shock protection system        | earthing pins connected to the protective earthing conductor   |
| Number of socket outlets            | 5 two-pole socket outlets with earthing pin, 10A/250V<br>2 two-pole socket outlets without earthing, 2.5A/250V |
| Switch                              | illuminated double pole mains switch   |
| Housing                             | made of self-extinguishing plastic   |
| Dimensions                          | 370x65x44mm  |
| Weight                              | 0.44kg   |



ILLUMINATED DOUBLE POLE MAINS SWITCH AND SLOW-BLOW AUTOMATIC FUSE



5 SOCKET OUTLETS 10A WITH EARTHING PIN, 2 UNEARTHED EURO SOCKETS, ALL OF THEM WITH SAFETY SHUTTERS



USAGE OF THE CABLE MANAGEMENT SYSTEM

The manufacturer reserves the right to change the technical parameters of the device, resulting from technological progress. ATTENTION! The technical data define the maximum values of surges against which the device protects.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [HSK Data](#) manufacturer:*

Other Similar products are found below :

[0015917161](#) [0022155065](#) [57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)  
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#)  
[65781-018](#) [65781-047](#) [65817-010LF](#) [65817-015LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [MHR-64-VUAL](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#)  
[801-43-006-10-002000](#) [803-43-024-10-001000](#) [803-93-012-10-001000](#) [8-1437020-4](#) [819-22-004-30-001101](#) [820-22-006-30-001101](#)  
[821-22-002-10-001101](#)