

Description


The HSP6032A is the high cell density trenched N-ch MOSFETs, which provide excellent RDSON and gate charge for most of the synchronous buck converter applications.

The HSP6032A meet the RoHS and Green Product requirement, 100% EAS guaranteed with full function reliability approved.

- Super Low Gate Charge
- 100% EAS Guaranteed
- Green Device Available
- Excellent CdV/dt effect decline
- Advanced high cell density Trench technology

Product Summary

| | | |
|------------------|-----|------------|
| V_{DS} | 60 | V |
| $R_{DS(ON),typ}$ | 7.1 | m Ω |
| I_D | 75 | A |

TO220 Pin Configuration

Absolute Maximum Ratings

| Symbol | Parameter | Rating | Units |
|-----------------------|---|------------|------------|
| V_{DS} | Drain-Source Voltage | 60 | V |
| V_{GS} | Gate-Source Voltage | ± 20 | V |
| $I_D@T_C=25^\circ C$ | Continuous Drain Current, V_{GS} @ 10V ₁ | 75 | A |
| $I_D@T_C=100^\circ C$ | Continuous Drain Current, V_{GS} @ 10V ₁ | 57 | A |
| I_{DM} | Pulsed Drain Current ₂ | 280 | A |
| EAS | Single Pulse Avalanche Energy ₃ | 80 | mJ |
| I_{AS} | Avalanche Current | 40 | A |
| $P_D@T_C=25^\circ C$ | Total Power Dissipation ₄ | 89 | W |
| T_{STG} | Storage Temperature Range | -55 to 150 | $^\circ C$ |
| T_J | Operating Junction Temperature Range | -55 to 150 | $^\circ C$ |

Thermal Data

| Symbol | Parameter | Typ. | Max. | Unit |
|-----------------|--|------|------|--------------|
| $R_{\theta JA}$ | Thermal Resistance Junction-ambient ₁ | --- | 60 | $^\circ C/W$ |
| $R_{\theta JC}$ | Thermal Resistance Junction-case ₁ | --- | 1.4 | $^\circ C/W$ |

Electrical Characteristics (T_J=25 °C, unless otherwise noted)

| Symbol | Parameter | Conditions | Min. | Typ. | Max. | Unit |
|---------------------|--|--|------|------|------|------|
| B _{VDS} | Drain-Source Breakdown Voltage | V _{GS} =0V, I _D =250uA | 60 | --- | --- | V |
| R _{DS(ON)} | Static Drain-Source On-Resistance ² | V _{GS} =10V, I _D =20A | --- | 7.1 | 8.5 | mΩ |
| V _{GS(th)} | Gate Threshold Voltage | V _{GS} =V _{DS} , I _D =250uA | 2 | --- | 4.5 | V |
| I _{DSS} | Drain-Source Leakage Current | V _{DS} =48V, V _{GS} =0V, T _J =25°C | --- | --- | 1 | uA |
| | | V _{DS} =48V, V _{GS} =0V, T _J =55°C | --- | --- | 5 | |
| I _{GSS} | Gate-Source Leakage Current | V _{GS} =±20V, V _{DS} =0V | --- | --- | ±100 | nA |
| R _g | Gate Resistance | V _{DS} =0V, V _{GS} =0V, f=1MHz | --- | 1.2 | --- | Ω |
| Q _g | Total Gate Charge (10V) | V _{DS} =30V, V _{GS} =10V, I _D =18A | --- | 57 | --- | nC |
| Q _{gs} | Gate-Source Charge | | --- | 8.7 | --- | |
| Q _{gd} | Gate-Drain Charge | | --- | 14 | --- | |
| T _{d(on)} | Turn-On Delay Time | V _{DD} =30V, V _{GS} =10V, R _G =3.3Ω, I _D =20A | --- | 16.2 | --- | ns |
| T _r | Rise Time | | --- | 41.2 | --- | |
| T _{d(off)} | Turn-Off Delay Time | | --- | 56.4 | --- | |
| T _f | Fall Time | | --- | 16.2 | --- | |
| C _{iss} | Input Capacitance | V _{DS} =30V, V _{GS} =0V, f=1MHz | --- | 3307 | --- | pF |
| C _{oss} | Output Capacitance | | --- | 201 | --- | |
| C _{rss} | Reverse Transfer Capacitance | | --- | 151 | --- | |

Diode Characteristics

| Symbol | Parameter | Conditions | Min. | Typ. | Max. | Unit |
|-----------------|--|---|------|------|------|------|
| I _S | Continuous Source Current ^{1,5} | V _G =V _D =0V, Force Current | --- | --- | 75 | A |
| V _{SD} | Diode Forward Voltage ² | V _{GS} =0V, I _S =1A, T _J =25°C | --- | --- | 1.2 | V |
| t _{rr} | Reverse Recovery Time | I _F =20A, dI/dt=100A/μs, | --- | 22 | --- | nS |
| Q _{rr} | Reverse Recovery Charge | T _J =25°C | --- | 72 | --- | nC |

Note :

- 1.The data tested by surface mounted on a 1 inch² FR-4 board with 2OZ copper.
- 2.The data tested by pulsed, pulse width ≤ 300us, duty cycle ≤ 2%
- 3.The EAS data shows Max. rating. The test condition is V_{DD}=50V, V_{GS}=10V, L=0.1mH, I_{AS}=40A
- 4.The power dissipation is limited by 150°C junction temperature
- 5.The data is theoretically the same as I_D and I_{DM}, in real applications, should be limited by total power dissipation.

Typical Characteristics




Fig.1 Typical Output Characteristics




Fig.2 On-Resistance vs Gate-Source Voltage




Fig.3 Forward Characteristics of Reverse




Fig.4 Gate-Charge Characteristics




Fig.5 Normalized $V_{GS(th)}$ vs T_J




Fig.6 Normalized $R_{DS(on)}$ vs T_J

N-Ch 60V Fast Switching MOSFETs




Fig.7 Capacitance




Fig.8 Safe Operating Area




Fig.9 Normalized Maximum Transient Thermal Impedance




Fig.10 Switching Time Waveform





Fig.11 Unclamped Inductive Switching



TO-220 Package Information



| Symbol | Dimensions In Millimeters | | Dimensions In Inches | |
|--------|---------------------------|--------|----------------------|-------|
| | Min. | Max. | Min. | Max. |
| A | 4.300 | 4.700 | 0.169 | 0.185 |
| A1 | 2.200 | 2.600 | 0.087 | 0.102 |
| b | 0.700 | 0.950 | 0.028 | 0.037 |
| b1 | 1.170 | 1.410 | 0.046 | 0.056 |
| c | 0.450 | 0.650 | 0.018 | 0.026 |
| c1 | 1.200 | 1.400 | 0.047 | 0.055 |
| D | 9.600 | 10.400 | 0.378 | 0.409 |
| E | 8.8500 | 9.750 | 0.348 | 0.384 |
| E1 | 12.650 | 12.950 | 0.498 | 0.510 |
| e | 2.540 TYP. | | 0.100TYP. | |
| e1 | 4.980 | 5.180 | 0.196 | 0.204 |
| F | 2.650 | 2.950 | 0.104 | 0.116 |
| H | 7.900 | 8.100 | 0.311 | 0.319 |
| h | 0.000 | 0.300 | 0.000 | 0.012 |
| L | 12.750 | 14.300 | 0.502 | 0.563 |
| L1 | 2.850 | 3.950 | 0.112 | 0.156 |
| V | 7.500 REF. | | 0.295 REF. | |
| Φ | 3.400 | 4.000 | 0.134 | 0.157 |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [MOSFET](#) category:

Click to view products by [HUASHUO](#) manufacturer:

Other Similar products are found below :

[614233C](#) [648584F](#) [NTNS3A92PZT5G](#) [IRFD120](#) [IRFF430](#) [JANTX2N5237](#) [2N7000](#) [2SK2464-TL-E](#) [FCA20N60_F109](#) [FDZ595PZ](#) [AOD464](#)
[2SK2267\(Q\)](#) [2SK2545\(Q,T\)](#) [405094E](#) [423220D](#) [MIC4420CM-TR](#) [VN1206L](#) [614234A](#) [715780A](#) [SSM6J414TU,LF\(T](#) [751625C](#)
[IPP60R600P6XKSA1](#) [RJK60S5DPK-M0#T0](#) [PSMN4R2-30MLD](#) [TK31J60W5,S1VQ\(O](#) [2SK2614\(TE16L1,Q\)](#) [DMN1017UCP3-7](#)
[EFC2J004NUZTDG](#) [FCAB21350L1](#) [P85W28HP2F-7071](#) [DMN1053UCP4-7](#) [NTE2384](#) [NTE2969](#) [NTE6400A](#) [DMN61D9UWQ-13](#)
[US6M2GTR](#) [DMN31D5UDJ-7](#) [SSM6P54TU,LF](#) [DMP22D4UFO-7B](#) [IPS60R3K4CEAKMA1](#) [DMN1006UCA6-7](#) [DMN16M9UCA6-7](#)
[STF5N65M6](#) [STU5N65M6](#) [C3M0021120D](#) [DMN13M9UCA6-7](#) [BSS340NWH6327XTSA1](#) [MCM3400A-TP](#) [DMTH10H4M6SPS-13](#)
[IRF40SC240ARMA1](#)