

VB 型片式铝电解电容

VB Series Chip Type Aluminum Electrolytic Capacitors


特点 Features

- 低阻抗。Low impedance.
- 适用于再流焊。Reflow soldering is available.
- 适用于高密度表面组装。available for high density surface mounting.
- 工作温度范围宽（-55℃ ~ +105℃）Operating over wide temperature range.
- ROHS 指令（2002/95/EC）已对应完毕。Adapted to the ROHS directive（2002/95/EC）。

主要技术性能 Specifications

项目 Items	特性 Characteristics						
工作温度范围 Operating Temperature Range	-55℃ ~+105℃						
额定电压范围 Rated Voltage Range	6.3V ~ 50V						
标称容量范围 Nominal Capacitance Range	1 ~ 1500μF						
标称容量允许偏差 Nominal Capacitance Tolerance	±20% (20℃, 120Hz)						
漏电流 Leakage Current	I ≤ 0.01C _R V _R or 3(μA), 取较大者 (2 分钟) C _R : 标称容量 (μF) U _R : 额定电压 (V) I ≤ 0.01C _R V _R or 3(μA) Whichever is greater (at 20℃, after 2 minutes) C _R : Nominal Capacitance (μF) U _R : Rated voltages (V)						
损耗角正切 (tgδ) Dissipation Factor (Max) 20℃, 120Hz	U _R (V)	6.3	10	16	25	35	50
	tgδ	0.26	0.20	0.16	0.14	0.12	0.12
耐久性 Load Life	+105℃施加额定电压 2000 小时后, 电容器应满足以下要求: After 2000 hours . application of rated voltage at 105℃, the capacitor shall meet the following requirement:						
	容量变化率 Capacitance Change	±30%初始值以内 Within ±30% of the initial value					
	损耗角正切 Dissipation Factor	≤ 300%初始规定值 Not more than 300% of the initial specified value					
	漏电流 Leakage Current	≤ 初始规定值 Not more than the initial specified value					
高温贮存 Shelf Life	+105℃ 贮存 1000 小时后, 电容器应满足以上耐久性要求 After storage for 1000 hours at +105℃, the capacitors shall meet the requirement of load life above						
低温特性 Low Temperature Stability 阻抗比 Impedance Ratio (120Hz)	U _R (V)	6.3	10	16	25	35	50
	Z(-25℃)/Z(+20℃)	3	2	2	2	2	2
	Z(-40℃)/Z(+20℃)	5	4	4	3	3	3
耐焊接热 Resistance to Soldering Heat	在 250℃的条件下, 电容器在热板上保持 30 秒, 然后从热板上取出电容器, 让其在室温下恢复, 电容器应满足以下要求: The capacitors shall be kept on the hot plate maintained at 250℃ for 30 seconds. After removing from the hot plate and restored at room temperature, they meet the following requirement.						
	容量变化率 Capacitance Change	±10%初始值以内 Within ±10% of the initial value					
	损耗角正切 (tgδ) Dissipation Factor	≤ 初始规定值 Not more than the initial specified value					
	漏电流 Leakage Current	≤ 初始规定值 Not more than the initial specified value					

尺寸图 Dimensions



(mm)

	4 × 5.4	5 × 5.4	6.3 × 5.4	6.3 × 7.7	8×10.5	10×10.5
A	1.8	2.1	2.4	2.4	2.9	3.2
B	4.3	5.3	6.6	6.6	8.3	10.3
C	4.3	5.3	6.6	6.6	8.3	10.3
E	1.0	1.3	2.2	2.2	3.1	4.5
L	5.4	5.4	5.4	7.7	10.5	10.5
H	0.5 ~ 0.8				0.8~1.1	

■ 标称电容量、额定电压、额定纹波电流与外形尺寸对应表

Nominal capacitance, rated voltage, rated ripple current and case size table

V	6.3			10			16			25			35			50		
	D×L mm	Impedance Ω	I~ mA															
1.0																4×5.4	5.00	30
2.2																4×5.4	5.00	30
3.3																4×5.4	5.00	30
4.7													4×5.4	1.8	80	5×5.4	1.52	85
10										4×5.4	1.80	80	5×5.4	0.76	150	6.3×5.4	0.88	165
22				4×5.4	1.80	80	5×5.4	0.76	150	5×5.4	0.76	150	5×5.4	0.76	150	6.3×5.4	0.88	165
33	5×5.4	0.76	150	5×5.4	0.76	150	6.3×5.4	0.44	230	6.3×5.4	0.44	230	6.3×5.4	0.44	230	6.3×7.7	0.68	185
47	5×5.4	0.76	150	6.3×5.4	0.44	230	6.3×5.4	0.44	230	6.3×5.4	0.44	230	6.3×7.7	0.34	280	6.3×7.7	0.68	185
100	6.3×5.4	0.44	230	6.3×5.4	0.44	230	6.3×5.4	0.44	230	6.3×7.7	0.34	280	8×10.5	0.17	600	8×10.5	0.34	300
220	6.3×5.4	0.44	230	6.3×7.7	0.34	280	6.3×7.7	0.34	280	8×10.5	0.17	600	8×10.5	0.17	600	10×10.5	0.18	670
330	6.3×7.7	0.34	280	8×10.5	0.17	600	8×10.5	0.17	600	8×10.5	0.17	600	10×10.5	0.09	850			
470	8×10.5	0.17	600	8×10.5	0.17	600	8×10.5	0.17	600	10×10.5	0.09	850						
1000	8×10.5	0.17	600	10×10.5	0.09	850												
1500	10×10.5	0.09	850															

I~ = Rated ripple current (mA) (105°C, 100kHz) I~ = 额定纹波电流 (mA) (105°C, 100kHz)

— 20°C 100 KHz 时的电阻 (Ω) MAX

■ 额定纹波电流的频率系数

Frequency coefficient of ripple current

Frequency 频率	50Hz	120Hz	300Hz	1KHz	≥ 10KHz
Coefficient 系数	0.35	0.50	0.64	0.83	1.00

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Aluminium Electrolytic Capacitors - SMD category](#):

Click to view products by [Huawei manufacturer](#):

Other Similar products are found below :

[EEV-FK1E332W](#) [ULV2H1R8MNL1GS](#) [MAL214099813E3](#) [CA025M4R70REB-0405](#) [HUB1800-S](#) [RYK-50V101MG5TT-FL](#)
[107AXZ016MQ5](#) [RVJ-50V101MH10U-R](#) [EMVH101GRA221MMN0S](#) [MAL214097402E3](#) [MAL215375471E3](#) [MAL224699909E3](#)
[MAL224699813E3](#) [MAL215099818E3](#) [AEH1213221M050R](#) [AEH1010331M025R](#) [AEA1010102M016R](#) [AEH1012471M016R](#)
[MAL213967339E3](#) [ZSC00AF2211EARL](#) [VB1E100MB054000CE0](#) [VD4.7UF400V90RV0094](#) [FZ470UF25V90RV0113](#)
[GVT1H476M0608CNVC](#) [GVE1V226M0506CNVC](#) [GVT1H226M0606CNVC](#) [ATB106M050D058](#) [ATB476M050F065](#) [ATB476M035E058](#)
[ATB107M016E058](#) [ATB107M035E077](#) [EMHL250ARA221MHA0G](#) [ATB477M016F102](#) [EMK1EM331FB0D00R](#) [EMF1CM221FB0D00R](#)
[EMF1CM331FB0D00R](#) [EMF1CM471FB0D00R](#) [EMK1JM101GB0D00R](#) [EMK1AM102GB0D00R](#) [EMK1HM221GB0D00R](#)
[DV221M6R3E055ETR](#) [DV221M025E077ETR](#) [RV331M025F105ETR](#) [HV100M035B055ETR](#) [VH1J101MG105000CE0](#)
[VD1H221MG105000CE0](#) [VD1C100MB054000CE0](#) [VD2A100ME077000CE0](#) [RVT1A101M0505](#) [VP1C221M0605](#)