

## VD 型片式铝电解电容

### VD Series Chip Type Aluminum Electrolytic Capacitors


#### 特点 Features

- 低阻抗。Low impedance.
- 适用于再流焊。Reflow soldering is available.
- 适用于高密度表面组装。available for high density surface mounting.
- 工作温度范围宽（-55℃ ~ +105℃）Operating over wide temperature range.
- ROHS 指令已对应完毕。Adapted to the ROHS directive.

#### 主要技术性能 Specifications

项目 Items	特性 Characteristics						
工作温度范围 Operating Temperature Range	-55℃ ~ +105℃						
额定电压范围 Rated Voltage Range	6.3V ~ 50V						
标称容量范围 Nominal Capacitance Range	1 ~ 1000μF						
标称容量允许偏差 Nominal Capacitance Tolerance	±20% (20℃, 120Hz)						
漏电流 Leakage Current	I ≤ 0.01C <sub>R</sub> V <sub>R</sub> or 3(μA), 取较大者 (2 分钟) C <sub>R</sub> : 标称容量 (μF) U <sub>R</sub> : 额定电压 (V) I ≤ 0.01C <sub>R</sub> V <sub>R</sub> or 3(μA) Whichever is greater (at 20℃, after 2 minutes) C <sub>R</sub> : Nominal Capacitance (μF) U <sub>R</sub> : Rated voltages (V)						
损耗角正切 (tgδ) Dissipation Factor (Max) 20℃, 120Hz	U <sub>R</sub> (V)	6.3	10	16	25	35	50
	tgδ	0.26(0.28)	0.20(0.24)	0.16(0.20)	0.14(0.16)	0.12(0.14)	0.12(0.14)
注: ( ) 为 Φ8 以上产品。							
耐久性 Load Life	+105℃施加额定电压 5000 小时后 (ΦD=4, 5 和 6.3 为 2000 小时), 电容器应满足以下要求: After 5000 hours (2000 hours for φD = 4, 5 and 6.3) . application of rated voltage at 105℃, the capacitor shall meet the following requirement:						
	容量变化率 Capacitance Change	±30%初始值以内 Within ±30% of the initial value					
	损耗角正切 Dissipation Factor	≤ 300%初始规定值 Not more than 300% of the initial specified value					
	漏电流 Leakage Current	≤ 初始规定值 Not more than the initial specified value					
高温贮存 Shelf Life	+105℃贮存 1000 小时后, 电容器应满足以上耐久性要求 After storage for 1000 hours at +105℃, the capacitors shall meet the requirement of load life above						
低温特性 Low Temperature Stability 阻抗比 Impedance Ratio (120Hz)	U <sub>R</sub> (V)	6.3	10	16	25	35	50
	Z(-25℃)/Z(+20℃)	3	2	2	2	2	2
	Z(-40℃)/Z(+20℃)	5	4	4	3	3	3
耐焊接热 Resistance to Soldering Heat	在 250℃的条件下, 电容器在热板上保持 30 秒, 然后从热板上取出电容器, 让其在室温下恢复, 电容器应满足以下要求: The capacitors shall be kept on the hot plate maintained at 250℃ for 30 seconds. After removing from the hot plate and restored at room temperature, they meet the following requirement.						
	容量变化率 Capacitance Change	±10%初始值以内 Within ±10% of the initial value					
	损耗角正切 (tgδ) Dissipation Factor	≤ 初始规定值 Not more than the initial specified value					
	漏电流 Leakage Current	≤ 初始规定值 Not more than the initial specified value					

尺寸图 Dimensions



\* Apply to 适用于  $\Phi 6.3 \times 7.7$

(mm)

	4 × 5.4	5 × 5.4	6.3 × 5.4	6.3 × 7.7	8x10.5	10x10.5
A	1.8	2.1	2.4	2.4	2.9	3.2
B	4.3	5.3	6.6	6.6	8.3	10.3
C	4.3	5.3	6.6	6.6	8.3	10.3
E	1.0	1.3	2.2	2.2	3.1	4.5
L	5.4	5.4	5.4	7.7	10.5	10.5
H	0.5 ~ 0.8				0.8~1.1	

■ 标称容量、额定电压、额定纹波电流与外形尺寸对应表

Nominal capacitance, rated voltage, rated ripple current and case size table

V	6.3			10			16			25			35			50		
	D×L mm	Impedance Ω	I~ mA	D×L mm	Impedance Ω	I~ mA	D×L mm	Impedance Ω	I~ mA	D×L mm	Impedance Ω	I~ mA	D×L mm	Impedance Ω	I~ mA	D×L mm	Impedance Ω	I~ mA
1.0																4×5.4	5.00	30
2.2																4×5.4	5.00	30
3.3																4×5.4	5.00	30
4.7													4×5.4	1.8	80	5×5.4	1.52	85
10										4×5.4	1.80	80	5×5.4	0.76	150	6.3×5.4	0.88	165
22				4×5.4	1.80	80	5×5.4	0.76	150	5×5.4	0.76	150	5×5.4	0.76	150	6.3×5.4	0.88	165
33	5×5.4	0.76	150	5×5.4	0.76	150	6.3×5.4	0.44	230	6.3×5.4	0.44	230	6.3×5.4	0.44	230	6.3×7.7	0.68	185
47	5×5.4	0.76	150	6.3×5.4	0.44	230	6.3×5.4	0.44	230	6.3×5.4	0.44	230	6.3×7.7	0.34	280	8x10.5	0.34	350
100	6.3×5.4	0.44	230	6.3×5.4	0.44	230	6.3×5.4	0.44	230	6.3×7.7	0.34	280	8x10.5	0.17	600	10x10.5	0.18	670
220	6.3×5.4	0.44	230	6.3×7.7	0.34	280	6.3×7.7	0.34	280	8x10.5	0.17	600	10x10.5	0.09	850			
330	6.3×7.7	0.34	280	8x10.5	0.17	600	8x10.5	0.17	600	10x10.5	0.09	850						
470	8x10.5	0.17	600	8x10.5	0.17	600	10x10.5	0.09	850									
1000	10x10.5	0.09	850	10x10.5	0.09	850												

I~=Rated ripple current (mA) (105°C, 100kHz) I~=额定纹波电流 (mA) (105°C, 100kHz)

20°C 100kHz 时的电阻 (Ω) MAX

■ 额定纹波电流的频率系数

Frequency coefficient of ripple current

Frequency 频率	50Hz	120Hz	300Hz	1KHz	≥ 10KHz
Coefficient 系数	0.35	0.50	0.64	0.83	1.00

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Aluminium Electrolytic Capacitors - SMD category](#):*

*Click to view products by [Huawei manufacturer](#):*

Other Similar products are found below :

[EEV-FK1E332W](#) [ULV2H1R8MNL1GS](#) [MAL214099813E3](#) [CA025M4R70REB-0405](#) [HUB1800-S](#) [34610](#) [RYK-50V101MG5TT-FL](#)  
[107AXZ016MQ5](#) [RVJ-50V101MH10U-R](#) [EMVH101GRA221MMN0S](#) [MAL214097402E3](#) [MAL215375471E3](#) [MAL224699909E3](#)  
[MAL224699813E3](#) [MAL215099014E3](#) [MAL215099017E3](#) [MAL215099117E3](#) [MAL215099818E3](#) [AEH1010331M025R](#)  
[AEA1010221M035R](#) [AEA1010470M080R](#) [AEH1010221M025R](#) [AEA1010102M016R](#) [AEA0810331M025R](#) [AEA1213102M025R](#)  
[AEA1213331M050R](#) [AEH1012471M016R](#) [MAL213967339E3](#) [ZSC00AF2211EARL](#) [VB1E100MB054000CE0](#) [RVT0J471M0607](#)  
[RVT1000UF10V34RV0081](#) [XT100UF50V90RV0067](#) [RVE100UF16V67RV0046](#) [RST22UF35V025](#) [RVT100UF16V67RV0120](#)  
[XT47UF50V90RV0082](#) [XT22UF50V90RV0083](#) [RST22UF50V026](#) [RST10UF16V013](#) [RST100UF25V004](#) [RST100UF35V009](#)  
[RST47UF25V035](#) [RST47UF50V038](#) [RST220UF25V019](#) [RSL220UF25V021](#) [XT10UF25V90RV0068](#) [FZ100UF50V90RV0066](#)  
[RST100UF16V003](#) [XT100UF10V90RV0060](#)