

Date Sheet



The "Huaxin" brand was founded in 2003 and has a history of 18 years. The company is mainly engaged in Hall elements, has a group of senior professional device design, integrated circuit design and test engineers, and has a first-class development and test platform. We have developed a number of high-end products with independent intellectual property rights, such as RF LDMOS series and RF VDMOS series, which represent China's integrated circuit level.

HX6382

Omnipolar Hall witch

HX6382 Hall-effect sensor is a temperature stable, stress-resistant, Low Tolerance of Sensitivity micro-power switch. Superior high-temperature performance is made possible through a dynamic offset cancellation that utilizes chopper-stabilization. This method reduces the offset voltage normally caused by device over molding, temperature dependencies, and thermal stress.

HX6382 is special made for low operation voltage, 1.65V, to active the chip which includes the following on a single silicon chip: voltage regulator, Hall voltage generator, small-signal amplifier, chopper stabilization, Schmitt trigger, CMOS output driver. Advanced CMOS wafer fabrication processing is used to take advantage of low-voltage requirements, component matching, very low input-offset errors, and small component geometries. This device requires the presence of omni-polar magnetic fields for operation.

The package type is in a Halogen Free version has been verified by third party Lab.

Features and Benefits

- CMOS Hall IC Technology
- Strong RF noise protection
- 1.65 to 3.5V for battery-powered applications
- Omni polar, output switches with absolute value of North or South pole from magnet
- Operation down to 1.65V, Micro power consumption
- High Sensitivity for reed switch replacement applications
- Multi Small Size option
- Low sensitivity drift in crossing of Temp. range
- Ultra Low power consumption at 5uA (Avg)
- High ESD Protection, HBM > ±4KV(min)
- Totem-pole output

Applications

- Solid state switch
- Handheld Wireless Handset Awake Switch
- Lid close sensor for battery powered devices
- Magnet proximity sensor for reed switch replacement in low duty cycle applications
- Water Meter
- Floating Meter
- PDVD
- NB


Ordering Information

<p style="text-align: center; font-weight: bold; color: yellow;">XXXXXX</p> <p style="text-align: center; font-weight: bold; color: green;">XXXXXX</p> <p style="text-align: center; font-weight: bold; color: blue;">XXXX</p> <p style="text-align: center; font-weight: bold; color: red;">XX-X</p> <div style="margin-top: 20px;"> <p>Sorting Code</p> <p>Package type</p> <p>Temperature Code</p> <p>Part number</p> <p>Company Name and product Category</p> </div>	<p>Company Name and Product Category HX:HX Hall Effect/MP:HX Power IC</p> <p>Part number 6286,6275,6278,6287,6383,6474,6571,6572,6573,6574...</p> <p>If part # is just 3 digits, the fourth digit will be omitted.</p> <p>Temperature range E: 85 °C, I: 105 °C, K: 125 °C, L: 150 °C</p> <p>Package type UA:TO-92S,VK:TO-92S(4pin),VF:TO-92S(5pin),SO:SOT-23, SQ:QFN-3,ST:TSOT-23,SN:SOT-553,SF:SOT-89(5pin), SS:TSOT-26,SD:DFN-6</p> <p>Sorting α, β, Blank.....</p>
--	---

Part No.	Temperature Suffix	Package Type
HX6382EST	E (-40°C to + 85°C)	ST (TSOT-23)
HX6382EUA	E (-40°C to + 85°C)	UA (TO-92S)

Custom sensitivity selection is available by HX sorting technology

Functional Diagram



Note: Static sensitive device; please observe ESD precautions. Reverse V_{DD} protection is not included. For reverse voltage protection, a 100Ω resistor in series with V_{DD} is recommended.

HBM > ±4KV which is verified by third party lab.

Absolute Maximum Ratings At($T_a=25^\circ\text{C}$)

Characteristics		Values	Unit
Supply voltage(V_{DD})		4.5	V
Output Voltage (V_{out})		4.5	V
Reverse Voltage (V_{DD}) (V_{OUT})		-0.3	V
Magnetic flux density		Unlimited	Gauss
Output current (I_{OUT})		1	mA
Operating temperature range(T_a)		-40 to +85	$^\circ\text{C}$
Storage temperature range (T_s)		-65 to +150	$^\circ\text{C}$
Maximum Junction Temp(T_j)		150	$^\circ\text{C}$
Thermal Resistance	(θ_{JA}) ST / UA	310 / 206	$^\circ\text{C}/\text{W}$
	(θ_{JC}) ST / UA	223 / 148	$^\circ\text{C}/\text{W}$
Package Power Dissipation (P_D)	ST / UA	400 / 606	mW


Note: Exceeding the absolute maximum ratings may cause permanent damage. Exposure to absolute maximum-rated conditions for extended periods may affect device reliability.

Electrical Specifications

DC Operating Parameters : $T_a=25^\circ\text{C}$, $V_{DD}=3.0\text{V}$

Parameters	Test Conditions	Min	Typ	Max	Units	
Supply Voltage (V_{DD})	Operating	1.65		3.5	V	
Supply Current (I_{DD})	Awake State		1.4	3	mA	
	Sleep State		3.6	7	μA	
	Average		5	10	μA	
Output Leakage Current	Output off			1	μA	
Output High Voltage(V_{OH})	$I_{OUT}=0.5\text{mA}$ (Source)	$V_{DD}-0.2$			V	
Output Low Voltage(V_{OL})	$I_{OUT}=0.5\text{mA}$ (Sink)			0.2	V	
Awake mode time(T_{aw})	Operating		40	80	μs	
Sleep mode time(T_{sl})	Operating		40	80	mS	
Duty Cycle (D, C)			0.1		%	
Electro-Static Discharge	HBM	4			KV	
Operate Point	(B_{OPN})	N pole to branded side, $B > BOP$, V_{out} On	10		30	Gauss
	(B_{OPS})	S pole to branded side, $B > BOP$, V_{out} On	-30		-10	Gauss
Release Point	(B_{RPN})	N pole to branded side, $B < BRP$, V_{out} Off	5		25	Gauss
	(B_{RPS})	S pole to branded side, $B < BRP$, V_{out} Off	-25		-5	Gauss
Hysteresis,(BHYS)	$ BOP_x - BRP_x $		10		Gauss	

Typical Application circuit




C1 : 10nF
 C2 : 100pF

Sensor Location, package dimension and marking


ST Package(TSOT-23)

(Top View)




Hall Plate Chip Location

(Bottom view)




(For reference only) Land Pattern




NOTES:

- PINOUT (See Top View at left):
Pin 1 VDD
Pin 2 Output
Pin 3 GND
- Controlling dimension: mm;
- Lead thickness after solder plating will be 0.254mm maximum

UA Package



Hall Chip location




NOTES:

- Controlling dimension: mm
- Leads must be free of flash and plating voids
- Do not bend leads within 1 mm of lead to package interface.
- PINOUT:
Pin 1 VDD
Pin 2 GND
Pin 3 Output

Output Pin Assignment

(Top view)



Warm reminder

1. Hall is a sensitive device. Please take electrostatic protection measures during use and storage.

2. During the installation process, the Hall should try to avoid applying mechanical stress to the Hall body. If the pins need to be bent, please operate at a distance of 3 mm from the root of the lead.

3. Recommended soldering temperature: soldering with electric soldering iron, the recommended temperature is 350°C, the longest is 5 seconds.

Wave soldering: The recommended maximum temperature is 260°C, the longest is 3 seconds

Infrared reflow soldering: recommended maximum 245°C, maximum 10 seconds

4. It is not recommended to exceed the parameters in the data sheet. Although the Hall will work normally under the limit parameters, it may cause damage to the Hall or the actual product under extreme conditions for a long time. In order to ensure the normal operation of the Hall and the product For safety and stability, please use it within the scope of the data sheet.

For the latest version of this document, go to our website at
www.wxhjkj.com

Or for additional information contact Huaxin Direct:
Anny : 15995280078 E-mail : sales1@wxhjkj.com

Huaxin has the final right to interpret the above product data

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Board Mount Hall Effect/Magnetic Sensors](#) category:

Click to view products by [HUAXIN](#) manufacturer:

Other Similar products are found below :

[HGPRDT005A](#) [AH277AZ4-AG1](#) [AV-10379](#) [AV-10448](#) [SS41C](#) [AH1894-Z-7](#) [TLE4917](#) [50017859-003](#) [TY-13101](#) [TLE4976L](#) [SS85CA](#)
[BU52002GUL-E2](#) [BU52003GUL-E2](#) [AH277AZ4-BG1](#) [TLE49614MXTSA1](#) [AH211Z4-AG1](#) [AH3360-FT4-7](#) [TLE4941-1](#) [SS460S-](#)
[100SAMPLE](#) [50065820-03](#) [AH374-P-A](#) [AH3372-P-B](#) [AH1806-P-A](#) [TLE49595UFXHALA1](#) [SS460P-T2](#) [AH1913-W-7](#) [AH3373-P-B](#)
[TLE9852QXXUMA1](#) [TLE5046ICAKLRHALA1](#) [TLE49421CHAMA2](#) [AH1903-FA-EVM](#) [AH8502-FDC-EVM](#) [AH3774-P-EVM](#)
[TLE4998S3XALA1](#) [TLE5011FUMA1](#) [TLE5027CE6747HAMA1](#) [TLE5109A16E1210XUMA1](#) [TLI4966GHTSA1](#) [TLI4906KHTSA1](#)
[MA710GQ-P](#) [S-57K1NBL2A-M3T2U](#) [S-57P1NBL9S-M3T4U](#) [S-576ZNL2B-L3T2U](#) [S-576ZNL2B-A6T8U](#) [S-57P1NBL0S-M3T4U](#) [S-](#)
[57A1NSL1A-M3T2U](#) [S-57K1RBL1A-M3T2U](#) [S-57P1NBH9S-M3T4U](#) [S-57P1NBH0S-M3T4U](#) [S-57A1NSH1A-M3T2U](#)