Data Sheet

Within Series Adaptor 33_N-50-0-52/199_U

Description

N-precision plug (male) / N-precision jack (female)

For Test & Measurement applications Quick-screw coupling mechanism, with reduced number of turns Precision adaptor

Interface standard Series N-precision - IEC 60169-16_MIL-STD-348A/402_CECC 22210

Technical Data

Electrical Data

Impedance Interface frequency max. VSWR	50 Ω 18 GHz DC - 18 GHz ≤ 1.03 + 0.01 f (GHz)
Electrical length	35.62 mm
Mechanical Data	500
Number of matings	500
Weight	0.0455 kg

Operating temperature -55 °C to 70 °C 2011/65/EU (RoHS - including compliant 2015/863 and 2017/2102)

Material Data

Interface - N-precision plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer contact	Stainless Steel	
Body	Stainless Steel	
Insulator	Air Dielectric - Bead - PPH	
Coupling nut	Stainless Steel	

Interface - N-precision jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer contact	Stainless Steel	
Body	Stainless Steel	
Insulator	Air Dielectric - Bead - PPH	

Related Documents

Outline drawing DOU-00013715 **Ordering Information** Single package 33_N-50-0-52/199_UE Remarks

Operating specification acc. IEEE Std 287: temperature 13 °C to 33 °C





Data Sheet

Within Series Adaptor 33_N-50-0-52/199_U

HUBER+SUHNER

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, AS/EN9100, ISO/TS 16949 and IRIS.

Waiver: Fact and figures herein are for information only and do not represent any warranty of any kind.

www.hubersuhner.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Adapters - In Series category:

Click to view products by Huber & Suhner manufacturer:

Other Similar products are found below :

 5916-1103-603
 5919-1503-000
 5919-9503-000
 651A505
 82-5552
 9030-9523-502
 PN2C
 A0407000
 R114703000W
 R125771001

 R127871001
 R141710000W
 R141723161
 R141730000
 R143730700
 R143770000
 R161703000W
 R161791530W

 R201705000
 R222705200
 R222M40010W
 R222M40050
 R223703180
 R316754000
 R405006000
 R443162000
 AD78TL
 HRM-513S

 1996352-2
 2157155-1
 252169-75
 AD158
 2101130-1
 252186
 R114704000W
 R114720000W
 R125705001
 R125705701
 R125771000

 R125771001W
 R127704001
 R127.870.001
 R127872001
 R141717000
 R142710000
 R143703000
 R143704000
 R143705700