Data Sheet



Within Series Adaptor 33_N-Q50-0-4/133_N

Description

Adaptor plug/jack

N Quick-mate plug (male) / N jack (female)

Quick-mate coupling mechanism, pluggable without tightening For Test & Measurement applications

Interface standards

Series N Quick-mate - HUBER+SUHNER Quick-mate Series N - IEC 61169-16_MIL-STD-348A/304_CECC 22210



8 to 11 GHz

≥ 16.5 dB

Technical Data

Electrical Data

 Impedance
 50 Ω

 Interface frequency max.
 11 GHz

 Frequency range
 DC to 5 GHz

 Return loss
 ≥ 29.4 dB

Mechanical Data

Number of matings 500
Weight 0.0372 kg

Environmental Data

Operating temperature 2011/65/EU (RoHS - including 2015/863 and 2017/2102)

-65 °C to 165 °C compliant

Material Data

Interface - N Quick-mate plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

5 to 8 GHz

≥ 20.1 dB

Interface - N jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

Related Documents

Outline drawing DOU-00013724

Ordering Information

Single package 33_N-Q50-0-4/133_NE

Remarks

Durability of QUICK MATE interface: 1000 matings

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, AS/EN9100, ISO/TS 16949 and IRIS.

www.hubersuhner.com

Waiver: Fact and figures herein are for information only and do not represent any warranty of any kind.

Document: DOC-0000194307 Y / PDO N / date of publication: 17.07.2020 09:19:25 / uncontrolled copy

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Adapters - In Series category:

Click to view products by Huber & Suhner manufacturer:

Other Similar products are found below:

5916-1103-603 5919-1503-000 5919-9503-000 651A505 82-5552 9030-9523-502 PN2C A0407000 R114703000W R125771001

R127871001 R141710000W R141723161 R141730000 R143730700 R143770000 R161703000W R161753000W R161791530W

R201705000 R222705200 R222M40010W R222M40050 R223703180 R316754000 R405006000 R443162000 AD78TL HRM-513S

1996352-2 2157155-1 252169-75 AD158 2101130-1 252186 R114704000W R114720000W R125705001 R125705701 R125771000

R125771001W R127704001 R127.870.001 R127872001 R141717000 R142710000 R142723000 R143703000 R143704000 R143705700