

RF Attenuator 5904_N-50-6/199_N

Description

Standard Attenuator, Medium Power



Product Configuration

Connector (side 1 / side 2) N plug (male) / N jack (female)
 Interface Standards IEC 60169-16_MIL-STD-348A/304_CECC 22210

Technical Data

Electrical Data

| | | |
|-----------------------------|---|--------|
| Nominal impedance | 50 Ω | |
| Nominal attenuation | 4 dB | |
| Frequency range | DC to 6 GHz | |
| Frequency sub range (GHz) | DC to 4 | 4 to 6 |
| Attenuation deviation (±dB) | 0.3 | 0.3 |
| VSWR max. | 1.15 | 1.2 |
| Power rating | 5 Watt average power up to 25 °C ambient temperature, linearly derated to 1 Watt at 125 °C ambient temperature. | |

Mechanical Data

Weight 0.052 kg

Environmental Data

Operating temperature -65 °C to 125 °C
 2011/65/EC (RoHS) compliant

Material Data

| Piece Part (side 1) | Material | Surface Plating |
|---------------------|--------------------------------|----------------------|
| Centre contact | Copper Beryllium Alloy | Gold Plating |
| Outer contact | Stainless Steel | Passivated (Plating) |
| Body | Aluminium | Anodized |
| Insulator | PTFE (Polytetrafluoroethylene) | |
| Coupling nut | Stainless Steel | Passivated (Plating) |
| Piece Part (side2) | Material | Surface Plating |
| Centre contact | Copper Beryllium Alloy | Gold Plating |
| Outer contact | Stainless Steel | Passivated (Plating) |
| Body | Aluminium | Anodized |
| Insulator | PTFE (Polytetrafluoroethylene) | |

Related Documents

Outline drawing DOU-00113012

Ordering Information

Single packaging 5904_N-50-6/199_NE

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Attenuators - Interconnects](#) category:

Click to view products by [Huber & Suhner](#) manufacturer:

Other Similar products are found below :

[R411803119](#) [R413806115](#) [R413808000](#) [R413810115](#) [R413850115](#) [R414510000](#) [R414701000](#) [R415303000](#) [BNC-13](#) [R411800121](#)
[R411801121](#) [R412412124](#) [R412450000](#) [R413800000](#) [R413805000](#) [R413830000](#) [R413840115](#) [R414730000](#) [R415420000](#) [R415703000](#)
[R416010000](#) [R420003110](#) [R411801000](#) [R411815121](#) [R413305000](#) [R413801000](#) [R414520000](#) [R411808121](#) [R412500124](#) [R412414124](#)
[R412501124](#) [HMC-C584](#) [R413802000](#) [R412400124](#) [R411700124](#) [R417310130](#) [R411801119](#) [R412419124](#) [R411703124](#) [R412401124](#)
[R443131000](#) [R417130110](#) [R414700000](#) [R414505000](#) [R411802119](#) [R417720128](#) [R420706110](#) [R413811000](#) [R413803115](#) [R414501000](#)