Data Sheet



RF TERMINATION Type 65_BNC-50-0-2/133_N

Description

Standard Termination, Low Power

With chain



Product Configuration

Connector BNC plug (male)

Interface standards IEC 60169-8_MIL-STD-348A/301_CECC 22120

Technical Data

Electrical Data

Nominal Impedance 50 Ω Frequency range 0 to 2 GHz

 Frequency sub range
 DC to 1 GHz
 1 to 1.5 GHz
 1.5 to 2 GHz

 VSWR max.
 1.05
 1.1
 1.2

Power rating 1 Watt average power up to 30 °C ambient temperature, linearly derated to 0 Watt at 130 °C ambient

temperature.

2000 Watt peak power

Mechanical Data

 Weight
 0.016 kg

 Chain length
 75 mm

 Eye diameter
 4 mm

Environmental Data

Operating temperature 2011/65/EU (RoHS - including 2015/863 and 2017/2102) -40 °C to 130 °C compliant

Material Data

Piece Part	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Chain	Brass	SUCOPLATE (R) Plating
Eye	Brass	SUCOPLATE (R) Plating

Ordering Information

Single Packaging Packaging 65_BNC-50-0-2/133_NE

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Terminators category:

Click to view products by Huber & Suhner manufacturer:

Other Similar products are found below:

M39030/3-04S M39030/3-04S M39030/3-09S M39030/3-11N TNG1-9-78-D3 TNA2-50 TNG1-6-78 TNH1-1-50 TNGFL1-1-78

R4042N5000 53S1RR-001N3 142275 56S1RR-001N4 65_BNC-50-0-7/133_NE 71S1RR-001N4 02S17R-001D3 R404240120 R404260000

HT-10-2 FL LCX 50-OHM-RSMA M39030/3-04N TNA1-6-50 131-3801-811 TNA1-1-50 65_N-50-0-51/113_NE 65_BNC-50-0-2/133_NE

65_N-50-0-1/133_NE 65002_N-50-1/122_NE 65_MMCX-50-0-31/111_OE 18K15R-0.5E3 2702702 TRM-2161-M0-35M-02 53S17R
001N3 1100.19.0001 6701.01.B 18S24H-40ML5 TRM-2053-M0-NNN-02 R404759000 M39030/6-02N TRM-2080-M0-NNN-07 TRM
2053-MC-NNN-02 M39030/3-03S SF8012-6009 6701.01.A 65_MCX-50-0-4/111_NE 65_716-50-0-2/003_-E 65_SMB-50-0-1/111_NE

M39030/3-12N 82-5722-RFX 8018-6174