# **Data Sheet**



# RF TERMINATION Type 65\_N-50-0-51/113\_N

## **Description**

Standard Termination, Low Power



## **Product Configuration**

Connector N plug (male)

Interface standards IEC 60169-16\_MIL-STD-348A/304\_CECC 22210

#### **Technical Data**

**Electrical Data** 

Nominal Impedance 50  $\Omega$  Frequency range 0 to 6 GHz

Frequency sub range DC to 3 GHz 3 to 6 GHz VSWR max. 1.1 1.15

Power rating 1 Watt average power up to 85 °C ambient temperature, linearly derated to 0 Watt at 115 °C ambient

temperature.

**Mechanical Data** 

 Weight
 0.0238 kg

 Matings
 100

**Environmental Data** 

Operating temperature -40 °C to 85 °C

Water and dust resistance IP20 (according to IEC 60529, data refer to the coupled state)

2011/65/EU (RoHS - including compliant 2015/863 and 2017/2102)

#### **Material Data**

Piece Part	Material	Surface Plating
Centre contact	Brass	SUCOPRO Plating
Outer contact	Brass	SUCOPRO Plating
Body	Brass	SUCOPRO Plating
Insulator	PTFE (Polytetrafluoroethylene)	
Coupling nut	Brass	SUCOPLATE (R) Plating

### **Related Documents**

Outline drawing DOU-00008585

#### **Ordering Information**

 Single Packaging
 65\_N-50-0-51/113\_NE

 Bulk 100 pcs Packaging
 65\_N-50-0-51/113\_NY

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Terminators category:

Click to view products by Huber & Suhner manufacturer:

Other Similar products are found below:

M39030/3-04S M39030/3-04S M39030/3-11N TNG1-9-78-D3 TNA2-50 TNG1-6-78 TNH1-1-50 TNGFL1-1-78

R4042N5000 53S1RR-001N3 142275 56S1RR-001N4 65\_BNC-50-0-7/133\_NE 71S1RR-001N4 02S17R-001D3 R404240120 R404260000

HT-10-2 FL LCX 50-OHM-RSMA M39030/3-04N TNA1-6-50 131-3801-811 TNA1-1-50 65\_N-50-0-51/113\_NE 65\_BNC-50-0-2/133\_NE

65\_N-50-0-1/133\_NE 65002\_N-50-1/122\_NE 65\_MMCX-50-0-31/111\_OE 18K15R-0.5E3 2702702 TRM-2161-M0-35M-02 53S17R
001N3 1100.19.0001 6701.01.B 18S24H-40ML5 TRM-2053-M0-NNN-02 R404759000 M39030/6-02N TRM-2053-MC-NNN-02

M39030/3-03S SF8012-6009 6701.01.A 65\_MCX-50-0-4/111\_NE 65\_716-50-0-2/003\_-E 65\_SMB-50-0-1/111\_NE M39030/3-12N 82
5722-RFX 8018-6174 SF8018-6005