Data Sheet



RF TERMINATION Type 65_QMA-50-0-4/111_N

Description

Standard Termination, Low Power



Product Configuration

Connector QMA jack (female)
Interface standards QMA QLF compliant

Technical Data

Electrical Data

Nominal Impedance 50 Ω Frequency range 0 to 6 GHz

Frequency sub range DC to 3 GHz 3 to 6 GHz VSWR max. 1.1 1.15

Power rating 1 Watt average power up to 85 °C ambient temperature, linearly derated to 0 Watt at 115 °C ambient

temperature.

Mechanical Data

 Weight
 0.0017 kg

 Matings
 100

Environmental Data

Operating temperature -40 °C to 115 °C

Water and dust resistance IP20 (according to IEC 60529, data refer to the coupled state)

2011/65/EU (RoHS - including compliant 2015/863 and 2017/2102)

Material Data

Piece Part	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Brass	SUCOPRO Plating
Body	Brass	SUCOPRO Plating
Insulator	PTFE (Polytetrafluoroethylene)	

Related Documents

Outline drawing DOU-00008691

Ordering Information

Single Packaging 65_QMA-50-0-4/111_NE Packaging

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Terminators category:

Click to view products by Huber & Suhner manufacturer:

Other Similar products are found below:

M39030/3-04S M39030/3-04S M39030/3-11N TNG1-9-78-D3 TNA2-50 TNG1-6-78 TNH1-1-50 TNGFL1-1-78

R4042N5000 53S1RR-001N3 142275 56S1RR-001N4 65_BNC-50-0-7/133_NE 71S1RR-001N4 02S17R-001D3 R404240120 R404260000

HT-10-2 FL LCX 50-OHM-RSMA M39030/3-04N TNA1-6-50 131-3801-811 TNA1-1-50 65_N-50-0-51/113_NE 65_BNC-50-0-2/133_NE

65_N-50-0-1/133_NE 65002_N-50-1/122_NE 65_MMCX-50-0-31/111_OE 18K15R-0.5E3 2702702 TRM-2161-M0-35M-02 53S17R
001N3 1100.19.0001 6701.01.B 18S24H-40ML5 TRM-2053-M0-NNN-02 R404759000 M39030/6-02N TRM-2053-MC-NNN-02

M39030/3-03S SF8012-6009 6701.01.A 65_MCX-50-0-4/111_NE 65_716-50-0-2/003_-E 65_SMB-50-0-1/111_NE M39030/3-12N 82
5722-RFX 8018-6174 SF8018-6005