

## RF Attenuator 6840\_N-50-1/1--\_N

### Description

Standard Attenuator, Low Power



### Product Configuration

Connector (side 1 / side 2) N plug (male) / N jack (female)  
Interface Standards IEC 60169-16\_MIL-STD-348A/304\_CECC 22210

### Technical Data

#### Electrical Data

Nominal impedance 50 Ω  
Nominal attenuation 40 dB  
Frequency range DC to 6 GHz  
Attenuation deviation (±dB) 1.5  
VSWR max. 1.25  
Power rating 2 Watt average power up to 25 °C ambient temperature, linearly derated to 1.1 Watt at 85 °C ambient temperature.

#### Mechanical Data

Weight 0.0657 kg

#### Environmental Data

Operating temperature -20 °C to 85 °C  
2011/65/EU (RoHS - including 2015/863 and 2017/2102) compliant

#### Material Data

Piece Part (side 1)	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer contact	Brass	
Body	Brass	Tri-metal Plating
Insulator	PTFE (Polytetrafluoroethylene)	
Coupling nut	Brass	
Piece Part (side2)	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer contact	Brass	
Body	Brass	Tri-metal Plating
Insulator	PTFE (Polytetrafluoroethylene)	

### Related Documents

Outline drawing DOU-00113052

### Ordering Information

Single packaging 6840\_N-50-1/1--\_NE

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Attenuators - Interconnects](#) category:*

*Click to view products by [Huber & Suhner](#) manufacturer:*

Other Similar products are found below :

[R411803119](#) [R413806115](#) [R413808000](#) [R413810115](#) [R413850115](#) [R414510000](#) [R414701000](#) [BNC-13](#) [R411800121](#) [R411801121](#)  
[R412412124](#) [R412450000](#) [R413800000](#) [R413805000](#) [R413830000](#) [R413840115](#) [R414730000](#) [R415420000](#) [R415703000](#) [R416010000](#)  
[R420003110](#) [R411801000](#) [R411815121](#) [R413305000](#) [R413801000](#) [R414520000](#) [R411808121](#) [R412500124](#) [R412414124](#) [R412501124](#)  
[HMC-C584](#) [R413802000](#) [R412400124](#) [R411700124](#) [R417310130](#) [R411801119](#) [R412419124](#) [R411703124](#) [R412401124](#) [R443131000](#)  
[R417130110](#) [R414700000](#) [R414505000](#) [R411802119](#) [R417720128](#) [R420706110](#) [R413811000](#) [R413803115](#) [R414501000](#) [R417903128](#)