

Flexible triaxial cable

G_03332 Item: 22510149

Description

G: RF cables with PE dielectrics

Triax (RG58 alternative core), 50 Ohm, 2 GHz, 85°C, ø7.3 mm, PVC jacket



Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Copper	Strand-07	0.95 mm
Dielectric	PE (Polyethylene)		2.95 mm
Outer conductor	Copper	Braid, 95%	3.6 mm
Jacket	PVC (Polyvinyl chloride)	RAL 9005 - bk	5 mm +/- 0.15
2 nd Screen	Copper	Braid, 91 %	5.7 mm
Outer Jacket	PVC (Polyvinyl chloride)	RAL 9005 - bk	7.3 mm +/- 0.3

Print: HUBER+SUHNER G 03332 50 Ohm (production order number)

Electrical Data

Impedance	50 Ω +/- 2
Operating Frequency	2 GHz
Capacitance	100.7 pF/m
Velocity of signal propagation	66 %
Signal delay	5.02 ns/m
Screening effectiveness	≥ 40 dB (up to 2 GHz)
Operating voltage	≤ 2.5 kV _{rms} (at sea level)
Test voltage	5 kV _{rms} (50 Hz/1 min)

Mechanical Data

Weight		9 kg/100 m
Min. bending radius	static	36 mm
	dynamic	75 mm
		146 mm

Environmental Data

Temperature range	-25 °C ... +85 °C
Installation temperature	-20 °C... +60 °C
Halogen test	n/a
Halogen free	No
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant
1907/2006/EC (REACH)	compliant
2000/53/EC (ELV)	compliant
2012/19/EU (WEEE)	no special marking needed

Additional Information

Extended temperature range -40°C to +85°C is feasible for static applications.

Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group W2 3 mm / 50+75 Ohm

Flexible triaxial cable

G_03332 Item: **22510149**

Matrix typical Attenuation [formula: $(a \cdot f^{0.5} + b \cdot f)$] and maximum Power CW [formula: $(p/f^{0.5})$]

Coefficients:

a = 0.4027

b = 0.08

$f_{\max} = 2$

P at 1GHz = 75

Frequency (GHz)	Nom. attenuation (dB / m) sea level 25° C ambient temperature	Nom. attenuation (dB / ft) sea level 25° C ambient temperature	Max. CW power (W) sea level 40° C ambient temperature
0,1	0,14	0,041	237
0,2	0,2	0,060	168
0,3	0,24	0,075	137
0,4	0,29	0,087	119
0,5	0,32	0,099	106
0,6	0,36	0,110	97
0,7	0,39	0,120	90
0,8	0,42	0,129	84
0,9	0,45	0,138	79
1,0	0,48	0,147	75
1,1	0,51	0,156	72
1,2	0,54	0,164	68
1,3	0,56	0,172	66
1,4	0,59	0,179	63
1,5	0,61	0,187	61
1,6	0,64	0,194	59
1,7	0,66	0,201	58
1,8	0,68	0,209	56
1,9	0,71	0,216	54
2,0	0,73	0,222	53

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Coaxial Cables](#) category:

Click to view products by [Huber & Suhner](#) manufacturer:

Other Similar products are found below :

[89880-003-1000](#) [CY2389-000](#) [8221-010-U1000](#) [9116-010-U500](#) [1322R-010-1000](#) [1807A-B59-U1000](#) [2020K8421-9X-CS3417](#) [9251-010-1000](#) [9275-010-U1000](#) [935240-000](#) [980704-001](#) [CF2823-000](#) [33312-010-500](#) [CZ1589-000](#) [5022W0809-0CS3263](#) [10610-4-4](#) [EF8108-000](#) [1673B TIN100](#) [672525-001](#) [144517-000](#) [735A1-008-1000](#) [8212-010-U500](#) [480414-000](#) [7915A 009U1000](#) [5024A1311-0](#) [1281S5 010250](#) [1530A 010U1000](#) [9248 010U1000](#) [9244 0101000](#) [1694A 0081000](#) [1190A 0101000](#) [8241F J5C1000](#) [1674A TIN50](#) [7915A 0091000](#) [TRCH-50-2](#) [9066 0031000](#) [7805R 008100](#) [1674A TIN100](#) [9116SB 0101000](#) [9271 0061000](#) [1613A 0101000](#) [1807A B591000](#) [5339Q5 009U500](#) [539945 0091000](#) [9116R 0101000](#) [89207 010100](#) [9058 0101000](#) [8241A 0101000](#) [DA7805R 0101000](#) [C6424](#)