

Flexible triaxial cable

G_03362-01 Item: 22511961

Description

G: RF cables with PE dielectrics

Triax (RG58 alternative core), 50 Ohm, 2 GHz, 85°C, ø7.2 mm, LSFH jacket



Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Copper, Tin plated	Strand-19	0.9 mm
Dielectric	PE (Polyethylene)		2.95 mm
Outer conductor	Copper, Tin plated	Braid, 96%	3.6 mm
Jacket	LSFH (modified polyethylene)	RAL 9005 - bk	4.95 mm +/- 0.15
2 nd Screen	Copper, Tin plated	Braid, 96 %	5.6 mm
Outer Jacket	LSFH (modified polyethylene)	RAL 9005 - bk	7.2 mm +/- 0.2

Print: HUBER+SUHNER G 03362-01 50 Ohm (production order number)

Electrical Data

Impedance	50 Ω +/- 2
Operating Frequency	2 GHz
Capacitance	101 pF/m
Velocity of signal propagation	66 %
Signal delay	5 ns/m
Operating voltage	≤ 2.5 kV _{rms} (at sea level)
Test voltage	5 kV _{rms} (50 Hz/1 min)

Mechanical Data

Weight		9.7 kg/100 m
Min. bending radius	static	36 mm
	dynamic	75 mm
		110 mm

Environmental Data

Temperature range	-40 °C ... +85 °C
Installation temperature	-20 °C... +60 °C
Halogen test	IEC 60754
Halogen free	Yes
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant
1907/2006/EC (REACH)	compliant
2000/53/EC (ELV)	compliant
2012/19/EU (WEEE)	no special marking needed

Additional Information

Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group W2 3 mm / 50+75 Ohm

Flexible triaxial cable

G_03362-01 **Item: 22511961**

Matrix typical Attenuation [formula: $(a \cdot f^{0.5} + b \cdot f)$] and maximum Power CW [formula: $(p/f^{0.5})$]

Coefficients:

a = 0.3455

b = 0.2373

f_{max} = 2

P at 1GHz = 100

Frequency (GHz)	Nom. attenuation (dB / m) sea level 25° C ambient temperature	Nom. attenuation (dB / ft) sea level 25° C ambient temperature	Max. CW power (W) sea level 40° C ambient temperature
0,1	0,13	0,041	316
0,2	0,2	0,062	224
0,3	0,26	0,079	183
0,4	0,31	0,096	158
0,5	0,36	0,111	141
0,6	0,41	0,125	129
0,7	0,46	0,139	120
0,8	0,5	0,152	112
0,9	0,54	0,165	105
1,0	0,58	0,178	100
1,1	0,62	0,190	95
1,2	0,66	0,202	91
1,3	0,7	0,214	88
1,4	0,74	0,226	85
1,5	0,78	0,237	82
1,6	0,82	0,249	79
1,7	0,85	0,260	77
1,8	0,89	0,271	75
1,9	0,93	0,283	73
2,0	0,96	0,294	71

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Coaxial Cables](#) category:

Click to view products by [Huber & Suhner](#) manufacturer:

Other Similar products are found below :

[89880-003-1000](#) [CY2389-000](#) [8221-010-U1000](#) [9116-010-U500](#) [1322R-010-1000](#) [1807A-B59-U1000](#) [2020K8421-9X-CS3417](#) [9251-010-1000](#) [9275-010-U1000](#) [935240-000](#) [980704-001](#) [CF2823-000](#) [33312-010-500](#) [CZ1589-000](#) [5022W0809-0CS3263](#) [10610-4-4](#) [EF8108-000](#) [1673B TIN100](#) [672525-001](#) [144517-000](#) [735A1-008-1000](#) [8212-010-U500](#) [480414-000](#) [7915A 009U1000](#) [5024A1311-0](#) [1281S5 010250](#) [1530A 010U1000](#) [9248 010U1000](#) [9244 0101000](#) [1694A 0081000](#) [1190A 0101000](#) [8241F J5C1000](#) [1674A TIN50](#) [7915A 0091000](#) [TRCH-50-2](#) [9066 0031000](#) [7805R 008100](#) [1674A TIN100](#) [9116SB 0101000](#) [9271 0061000](#) [1613A 0101000](#) [1807A B591000](#) [5339Q5 009U500](#) [539945 0091000](#) [9116R 0101000](#) [89207 010100](#) [9058 0101000](#) [8241A 0101000](#) [DA7805R 0101000](#) [C6424](#)