

## Flexible RF cable

**RG\_179\_B/U** Item: 22510044

### Description

RG: RG type RF cables

RG179, 75 Ohm, 3 GHz, 200°C, ø2.54 mm, FEP jacket



### Technical Data

#### Construction

	Material	Detail	Diameter
Centre conductor	Steel, Copper+Silver plated	Strand-07	0.31 mm
Dielectric	PTFE (Polytetrafluoroethylene)		1.55 mm
Outer conductor	Copper, Silver plated	Braid, 94%	2 mm
Jacket	FEP (Fluorinated ethylene propylene)	RAL 8015 - br	2.54 mm +/- 0.13

Print: HUBER+SUHNER RG 179 B/U 75 Ohm (production order number)

#### Electrical Data

Impedance	75 Ω +/- 3
Operating Frequency	3 GHz
Capacitance	63 pF/m
Velocity of signal propagation	69 %
Signal delay	4.83 ns/m
Screening effectiveness	≥ 41 dB (up to 1 GHz)
Operating voltage	≤ 0.75 kV <sub>rms</sub> (at sea level)
Test voltage	1.5 kV <sub>rms</sub> (50 Hz/1 min)

#### Mechanical Data

Weight		1.48 kg/100 m
Min. bending radius	static	15 mm
		25 mm
	dynamic	38 mm

#### Environmental Data

Temperature range	-65 °C ... +200 °C
Installation temperature	-20 °C... +60 °C
Flame propagation test	IEC 60332-1,
Halogen free	No
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant
1907/2006/EC (REACH)	compliant

### Additional Information

MIL reference: M17/94-RG179

#### Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

#### Suitable Connectors

Cable group U5 2 mm / 75 Ohm

## Flexible RF cable

**RG\_179\_B/U** Item: 22510044

**Matrix** typical Attenuation [ formula:  $(a \cdot f^{0.5} + b \cdot f)$  ] and maximum Power CW [ formula:  $(p/f^{0.5})$  ]

Coefficients:

a = 0.73

b = 0.1014

f<sub>max</sub> = 3

P at 1GHz = 115

Frequency (GHz)	Nom. attenuation (dB / m) sea level 25° C ambient temperature	Nom. attenuation (dB / ft) sea level 25° C ambient temperature	Max. CW power (W) sea level 40° C ambient temperature
0,15	0,3	0,091	297
0,3	0,43	0,131	210
0,45	0,54	0,163	171
0,6	0,63	0,191	148
0,75	0,71	0,216	133
0,9	0,78	0,239	121
1,05	0,85	0,260	112
1,2	0,92	0,281	105
1,35	0,99	0,300	99
1,5	1,05	0,319	94
1,65	1,11	0,337	90
1,8	1,16	0,354	86
1,95	1,22	0,371	82
2,1	1,27	0,387	79
2,25	1,32	0,403	77
2,4	1,37	0,419	74
2,55	1,42	0,434	72
2,7	1,47	0,449	70
2,85	1,52	0,464	68
3,0	1,57	0,478	66

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Coaxial Cables](#) category:*

*Click to view products by [Huber & Suhner](#) manufacturer:*

Other Similar products are found below :

[89880-003-1000](#) [CY2389-000](#) [8221-010-U1000](#) [9116-010-U500](#) [1322R-010-1000](#) [1807A-B59-U1000](#) [2020K8421-9X-CS3417](#) [9251-010-1000](#) [9275-010-U1000](#) [935240-000](#) [980704-001](#) [CF2823-000](#) [33312-010-500](#) [CZ1589-000](#) [5022W0809-0CS3263](#) [10610-4-4](#) [EF8108-000](#) [1673B TIN100](#) [672525-001](#) [144517-000](#) [735A1-008-1000](#) [8212-010-U500](#) [480414-000](#) [7915A 009U1000](#) [5024A1311-0](#) [1281S5 010250](#) [1530A 010U1000](#) [9248 010U1000](#) [9244 0101000](#) [1694A 0081000](#) [1190A 0101000](#) [8241F J5C1000](#) [1674A TIN50](#) [7915A 0091000](#) [TRCH-50-2](#) [9066 0031000](#) [7805R 008100](#) [1674A TIN100](#) [9116SB 0101000](#) [9271 0061000](#) [1613A 0101000](#) [1807A B591000](#) [5339Q5 009U500](#) [539945 0091000](#) [9116R 0101000](#) [89207 010100](#) [9058 0101000](#) [8241A 0101000](#) [DA7805R 0101000](#) [C6424](#)