

## Flexible RF cable

**RG\_188\_A/U** Item: 22510046

### Description

RG: RG type RF cables

RG188, 50 Ohm, 3 GHz, 205°C, ø2.6 mm, PFA jacket



### Technical Data

#### Construction

	Material	Detail	Diameter
Centre conductor	Steel, Copper+Silver plated	Strand-07	0.54 mm
Dielectric	PTFE (Polytetrafluoroethylene)		1.55 mm
Outer conductor	Copper, Silver plated	Braid, 94%	2 mm
Jacket	PFA (Perfluoroalkoxy)	RAL 9010 - wh	2.6 mm +/- 0.1

Print: HUBER+SUHNER RG 188 A/U 50 Ohm (production order number)

#### Electrical Data

Impedance	50 Ω +/- 2
Operating Frequency	3 GHz
Capacitance	97 pF/m
Velocity of signal propagation	69 %
Signal delay	4.86 ns/m
Screening effectiveness	≥ 39 dB (up to 1 GHz)
Operating voltage	≤ 0.85 kV <sub>rms</sub> (at sea level)
Test voltage	1.7 kV <sub>rms</sub> (50 Hz/1 min)

#### Mechanical Data

Weight		1.7 kg/100 m
Min. bending radius	static	15 mm
		26 mm
	dynamic	39 mm

#### Environmental Data

Temperature range	-80 °C ... +205 °C
Installation temperature	-20 °C... +60 °C
Flame propagation test	IEC 60332-3,
Halogen free	No
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant
1907/2006/EC (REACH)	compliant

### Additional Information

#### Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

#### Suitable Connectors

Cable group	U2 2 mm / 50 Ohm
-------------	------------------

## Flexible RF cable

**RG\_188\_A/U** Item: 22510046

**Matrix** typical Attenuation [ formula:  $(a \cdot f^{0.5} + b \cdot f)$  ] and maximum Power CW [ formula:  $(p/f^{0.5})$  ]

Coefficients:

a = 0.7501

b = 0.0884

f<sub>max</sub> = 3

P at 1GHz = 180

Frequency (GHz)	Nom. attenuation (dB / m) sea level 25° C ambient temperature	Nom. attenuation (dB / ft) sea level 25° C ambient temperature	Max. CW power (W) sea level 40° C ambient temperature
0,15	0,3	0,093	465
0,3	0,44	0,133	329
0,45	0,54	0,165	268
0,6	0,63	0,193	232
0,75	0,72	0,218	208
0,9	0,79	0,241	190
1,05	0,86	0,263	176
1,2	0,93	0,283	164
1,35	0,99	0,302	155
1,5	1,05	0,320	147
1,65	1,11	0,338	140
1,8	1,17	0,355	134
1,95	1,22	0,372	129
2,1	1,27	0,388	124
2,25	1,32	0,404	120
2,4	1,37	0,419	116
2,55	1,42	0,434	113
2,7	1,47	0,448	110
2,85	1,52	0,463	107
3,0	1,56	0,477	104

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Coaxial Cables](#) category:*

*Click to view products by [Huber & Suhner](#) manufacturer:*

Other Similar products are found below :

[89880-003-1000](#) [CY2389-000](#) [8221-010-U1000](#) [9116-010-U500](#) [1322R-010-1000](#) [1807A-B59-U1000](#) [2020K8421-9X-CS3417](#) [9251-010-1000](#) [9275-010-U1000](#) [935240-000](#) [980704-001](#) [CF2823-000](#) [33312-010-500](#) [CZ1589-000](#) [5022W0809-0CS3263](#) [10610-4-4](#) [EF8108-000](#) [1673B TIN100](#) [672525-001](#) [144517-000](#) [735A1-008-1000](#) [8212-010-U500](#) [480414-000](#) [7915A 009U1000](#) [5024A1311-0](#) [1281S5 010250](#) [1530A 010U1000](#) [9248 010U1000](#) [9244 0101000](#) [1694A 0081000](#) [1190A 0101000](#) [8241F J5C1000](#) [1674A TIN50](#) [7915A 0091000](#) [TRCH-50-2](#) [9066 0031000](#) [7805R 008100](#) [1674A TIN100](#) [9116SB 0101000](#) [9271 0061000](#) [1613A 0101000](#) [1807A B591000](#) [5339Q5 009U500](#) [539945 0091000](#) [9116R 0101000](#) [89207 010100](#) [9058 0101000](#) [8241A 0101000](#) [DA7805R 0101000](#) [C6424](#)