

Flexible RF cable

RG_400_/U Item: 22510080

Description

RG: RG type RF cables

RG400, 50 Ohm, 6 GHz, 200°C, ø4.95 mm, FEP jacket



Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Copper, Silver plated	Strand-19	1 mm
Dielectric	PTFE (Polytetrafluoroethylene)		2.95 mm
Outer conductor	Copper, Silver plated	Braid, 97%	3.6 mm
Outer conductor	Copper, Silver plated	Braid, 94 %	4.2 mm
Jacket	FEP (Fluorinated ethylene propylene)	RAL 8015 - br	4.95 mm +/- 0.1

Print: HUBER+SUHNER RG 400 U 50 Ohm (production order number)

Electrical Data

Impedance	50 Ω +/- 2
Operating Frequency	6 GHz
Capacitance	94 pF/m
Velocity of signal propagation	69 %
Signal delay	4.75 ns/m
Screening effectiveness	≥ 81 dB (up to 6 GHz)
Operating voltage	≤ 1.7 kV _{rms} (at sea level)
Test voltage	3.4 kV _{rms} (50 Hz/1 min)

Mechanical Data

Weight		6.4 kg/100 m
Min. bending radius	static	30 mm
	dynamic	50 mm
		75 mm

Environmental Data

Temperature range	-65 °C ... +200 °C
Installation temperature	-20 °C... +60 °C
Flame propagation test	IEC 60332-3,
Halogen free	No
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant
1907/2006/EC (REACH)	compliant

Additional Information

MIL reference: M17/128-RG400

Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group U11 3 mm / 50 Ohm

Flexible RF cable

RG_400_/U Item: 22510080

Matrix typical Attenuation [formula: $(a \cdot f^{0.5} + b \cdot f)$] and maximum Power CW [formula: $(p/f^{0.5})$]

Coefficients:

a = 0.3894

b = 0.0925

$f_{max} = 6$

P at 1GHz = 365

Frequency (GHz)	Nom. attenuation (dB / m) sea level 25° C ambient temperature	Nom. attenuation (dB / ft) sea level 25° C ambient temperature	Max. CW power (W) sea level 40° C ambient temperature
0,3	0,24	0,073	666
0,6	0,36	0,109	471
0,9	0,45	0,138	385
1,2	0,54	0,164	333
1,5	0,62	0,188	298
1,8	0,69	0,210	272
2,1	0,76	0,231	252
2,4	0,83	0,252	236
2,7	0,89	0,271	222
3,0	0,95	0,290	211
3,3	1,01	0,309	201
3,6	1,07	0,327	192
3,9	1,13	0,344	185
4,2	1,19	0,362	178
4,5	1,24	0,379	172
4,8	1,3	0,395	167
5,1	1,35	0,412	162
5,4	1,4	0,428	157
5,7	1,46	0,444	153
6,0	1,51	0,460	149

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Coaxial Cables](#) category:

Click to view products by [Huber & Suhner](#) manufacturer:

Other Similar products are found below :

[89880-003-1000](#) [CY2389-000](#) [8221-010-U1000](#) [9116-010-U500](#) [1322R-010-1000](#) [1807A-B59-U1000](#) [2020K8421-9X-CS3417](#) [9251-010-1000](#) [9275-010-U1000](#) [935240-000](#) [980704-001](#) [CF2823-000](#) [33312-010-500](#) [CZ1589-000](#) [5022W0809-0CS3263](#) [10610-4-4](#) [EF8108-000](#) [1673B TIN100](#) [672525-001](#) [144517-000](#) [735A1-008-1000](#) [8212-010-U500](#) [480414-000](#) [7915A 009U1000](#) [5024A1311-0](#) [1281S5 010250](#) [1530A 010U1000](#) [9248 010U1000](#) [9244 0101000](#) [1694A 0081000](#) [1190A 0101000](#) [8241F J5C1000](#) [1674A TIN50](#) [7915A 0091000](#) [TRCH-50-2](#) [9066 0031000](#) [7805R 008100](#) [1674A TIN100](#) [9116SB 0101000](#) [9271 0061000](#) [1613A 0101000](#) [1807A B591000](#) [5339Q5 009U500](#) [539945 0091000](#) [9116R 0101000](#) [89207 010100](#) [9058 0101000](#) [8241A 0101000](#) [DA7805R 0101000](#) [C6424](#)