

Polyamide-Fitting DUO-PA


NPT



Material	Polyamide
Seal	NBR
Protection Category	IP 68 – 10 bar / IP 69K (NEMA 6 – 150 PSIG) on the cable gland
Operating Temperature	-40 °C – +100 °C (-40 °F – +212 °F)
Colours	black (RAL 9005)



- // 2 in 1 cable gland and conduit fitting
- // Easy disassembly without tools



AG	∅ mm	GL mm	H mm	D mm	mm	fits to Polyamide-Conduit DN	Number
NPT 1/2"	10–14	13	46	29	27	14	1.542.1214.70
NPT 1/2"	07–12	13	46	29	27	14	1.542.1214.71
NPT 3/4"	13–18	14	50	30	33	17	1.542.3417.70
NPT 3/4"	09–16	14	50	30	33	17	1.542.3417.71
NPT 1"	18–24	19	60	39	42	23	1.542.1023.70
NPT 1"	13–20	19	60	39	42	23	1.542.1023.71
NPT 1 1/2"	22–31	20	69	45	53	29	1.542.6429.70

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Conduit Fittings & Accessories](#) category:

Click to view products by [Hummel](#) manufacturer:

Other Similar products are found below :

[790-3006](#) [790-3150](#) [RE42](#) [LT20090](#) [LTB15045](#) [LTB20045](#) [LTB3890](#) [CGE195](#) [790-3154](#) [790-3008](#) [790-3014](#) [790-3020](#) [790-3152](#) [790-3156](#) [790-3166](#) [790-3002](#) [790-3162](#) [C2016-P](#) [C2012-P](#) [561-87BG11BLK](#) [1.511.1601.50](#) [55502675](#) [2676](#) [302-TB](#) [655241-000](#) [C17](#) [262-420](#) [TMC165-BR](#) [RBDP-BLA-20D236U](#) [RBDP-BLA-30D346U](#) [SPL25/075/M](#) [CN21](#) [SRN21](#) [3405B](#) [4975](#) [VC12516](#) [RC156-0500](#) [DM0523-1/2A](#) [1035A](#) [DMS0250-1A](#) [DMS0313-1A](#) [1040A](#) [1050A](#) [R1/8A](#) [DMPC0490-1/2A](#) [DMPC0521-1/2A](#) [DMPC0552-1/2A](#) [1070A](#) [R1/2A](#) [E1-7/8B](#)