


HSK-M-EMC-Ex / HSK-M-EMC-PVDF-Ex

PG, NPT



| | |
|-----------------------|---|
| Material | Nickel plated brass |
| Clamping insert | Polyamide / PVDF |
| Seal | Buna-N / FKM |
| O-Ring | Buna-N / FKM |
| Protection | IP 68 – 10 bar / IP 69K (NEMA 6 – 150 PSIG) |
| Operating Temperature | -20 °C – 95 °C (-4 °F – 203 °F) -60 °C – 95 °C (-76 °F – 203 °F) / -20 °C – 130 °C (-4 °F – 266 °F) (PVDF) |

// With pre-assembled dust disc upon request



| AG | ∅ _k mm | GL mm | H mm | ⌀ _m mm | Number HSK-M-EMC-Ex -20 °C – 95 °C | Number HSK-M-EMC-Ex -60 °C – 95 °C | Number HSK-M-PVDF-EMC-Ex -20 °C – 130 °C |
|----------|----------------------|----------|---------|----------------------|--|--|--|
| PG 7 | 3–6,5 | 5 | 19 | 14 | 1.616.0700.01 | 1.646.0700.01 | 1.666.0700.01 |
| PG 7 | 2–5 | 5 | 19 | 14 | 1.616.0700.15 | 1.646.0700.15 | 1.666.0700.15 |
| PG 9 | 4–8 | 6 | 21 | 17 | 1.616.0900.01 | 1.646.0900.01 | 1.666.0900.01 |
| PG 9 | 2–6 | 6 | 21 | 17 | 1.616.0900.15 | 1.646.0900.15 | 1.666.0900.15 |
| PG 11 | 6–10 | 6 | 22 | 20 | 1.616.1100.01 | 1.646.1100.01 | 1.666.1100.01 |
| PG 11 | 3–7 | 6 | 22 | 20 | 1.616.1100.15 | 1.646.1100.15 | 1.666.1100.15 |
| PG 13,5 | 7–12 | 6,5 | 24 | 22 | 1.616.1300.01 | 1.646.1300.01 | 1.666.1300.01 |
| PG 13,5 | 5–9 | 6,5 | 24 | 22 | 1.616.1300.15 | 1.646.1300.15 | 1.666.1300.15 |
| PG 16 | 10–14 | 6,5 | 23 | 24 | 1.616.1600.01 | 1.646.1600.01 | 1.666.1600.01 |
| PG 16 | 7–12 | 6,5 | 23 | 24 | 1.616.1600.15 | 1.646.1600.15 | 1.666.1600.15 |
| PG 21 | 14–18 | 7 | 24 | 30 | 1.616.2100.01 | 1.646.2100.01 | 1.666.2100.01 |
| PG 21 | 10–16 | 7 | 24 | 30 | 1.616.2100.15 | 1.646.2100.15 | 1.666.2100.15 |
| PG 29 | 20–25 | 8 | 29 | 40 | 1.616.2900.01 | 1.646.2900.01 | 1.666.2900.01 |
| PG 29 | 13–20 | 8 | 29 | 40 | 1.616.2900.15 | 1.646.2900.15 | 1.666.2900.15 |
| PG 36 | 22–32 | 8 | 35 | 50 | 1.616.3600.01 | 1.646.3600.01 | 1.666.3600.01 |
| PG 36 | 20–26 | 8 | 35 | 50 | 1.616.3600.15 | 1.646.3600.15 | 1.666.3600.15 |
| PG 42 | 32–38 | 9 | 37 | 57 | 1.616.4200.01 | 1.646.4200.01 | 1.666.4200.01 |
| PG 42 | 25–31 | 9 | 37 | 57 | 1.616.4200.15 | 1.646.4200.15 | 1.666.4200.15 |
| PG 48 | 37–44 | 10 | 38 | 64 | 1.616.4800.01 | 1.646.4800.01 | 1.666.4800.01 |
| PG 48 | 29–35 | 10 | 38 | 64 | 1.616.4800.15 | 1.646.4800.15 | 1.666.4800.15 |
| NPT 3/8" | 4–8 | 15 | 21 | 17/19 | 1.616.3800.70 | 1.646.3800.70 | 1.666.3800.70 |
| NPT 3/8" | 2–6 | 15 | 21 | 17/19 | 1.616.3800.71 | 1.646.3800.71 | 1.666.3800.71 |
| NPT 1/2" | 7–12 | 13 | 24 | 22/24 | 1.616.1200.70 | 1.646.1200.70 | 1.666.1200.70 |
| NPT 1/2" | 5–9 | 13 | 24 | 22/24 | 1.616.1200.71 | 1.646.1200.71 | 1.666.1200.71 |
| NPT 3/4" | 14–18 | 13 | 25 | 30 | 1.616.3400.70 | 1.646.3400.70 | 1.666.3400.70 |
| NPT 3/4" | 10–16 | 13 | 25 | 30 | 1.616.3400.71 | 1.646.3400.71 | 1.666.3400.71 |

Plastic
Metal
EMC
Special applications, DIN
Accessories
Ex
EMC-Ex
Ex Accessories
EXIOS

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Cable Glands, Strain Reliefs & Cord Grips](#) category:

Click to view products by [Hummel](#) manufacturer:

Other Similar products are found below :

[1300980012](#) [DBZM-6828](#) [1498](#) [15190-103 R2](#) [1.587.3400.71](#) [300623](#) [07402002](#) [CD21NS-01](#) [VC-M-KV-PG16 1X3/1X8](#) [35935](#) [35882](#)
[M4340GAE](#) [4597](#) [NG-9516 Gasket](#) [52006157](#) [52006176](#) [BM4963L](#) [53629556](#) [53629570](#) [53629675](#) [52025230](#) [52024853](#) [52103160](#)
[52115810](#) [53017640](#) [53019051](#) [53019071](#) [53112270](#) [53112330](#) [53112840](#) [53112879](#) [53112929](#) [53111470](#) [53015270](#) [53015090](#) [53018090](#)
[PG-29](#) [36681](#) [36550](#) [36310](#) [35880](#) [1300990004](#) [Z5.507.2321.0](#) [CGB295-SG](#) [5320816](#) [1.089.1399.19](#) [1.089.2106.19](#) [1.089.2905.19](#)
[1.089.3699.19](#) [1.089.4801.19](#)