

Outflow valve turnable with key control

Item number 2531120001



Technical data

Connection size 1 (AG1)	G 1/2
Connection type 1 (AT1)	External thread
Connection type 2 (AT2)	Draining
Length (L)	32 mm
Width (B)	32 mm
Height (H)	29 mm
Thread Length 1 (GL1)	7 mm
Wrench size 1 (SW1)	19 mm
Wrench size 2 (SW2)	5 mm
Suitable for	Heating
Outlet	Rotating
Operation	Key operation
Material moulded seal	EPDM
Material plastic cap	PA
Material body/spindle	Nickel-plated brass

Outflow valve turnable with key control


Item number 2531120001

Material spindle	Nickel-plated brass
Material	Nickel-plated brass
Max. operating pressure	10 bar , 16 bar (with closed spindle and a max. operating temperature of 100°C)
Max. operating temperature heating	130 °C

Commercial data

Packaging Unit	50
EAN code	4033878101193
Weight	0.039 kg
ETIM 7	EC010071
ETIM 8	EC010071
eCl@ss 10.1	22-39-04-11
Customs tariff number	84818039

Note:



Outflow valve turnable with key control

Item number 2531120001

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Mounting Fixings](#) category:

Click to view products by [Hummel](#) manufacturer:

Other Similar products are found below :

[007541](#) [M3783-7001](#) [7717-8DAP](#) [FPK-02-R10](#) [PMS27488-001-01](#) [1-18023-0](#) [H-118-2](#) [1302030464](#) [1302010957](#) [1302263564](#) [1302340393](#)
[1404-0016-78](#) [14540](#) [1566](#) [1566](#) [BR16A](#) [NT20SATT01](#) [22594-8](#) [KBB-141](#) [915060](#) [SF4011-60101](#) [97-CS-50](#) [1671](#) [1855-54](#) [T-2085-SP](#)
[20800240002](#) [21899-4](#) [2193](#) [2518](#) [25745-1](#) [H-118-1](#) [354467](#) [37184](#) [4658](#) [4665](#) [4731](#) [BRACKET-RA-30](#) [5500083](#) [HS5659MB98SN](#) [561-](#)
[T001](#) [4222522019-542](#) [LF9Z-1SB22](#) [4601463120-542](#) [4674](#) [100101850001](#) [EN3155-015F2020](#) [WMLX-109](#) [374170](#) [MS05CW-20-16PN-](#)
[SIL](#) [20607-1](#)