

参数表

2CL40KV/3A 高压硅堆采用高可靠的台面结构及扩散工艺，环氧树脂真空灌注密闭封装。

2CL40KV/3A High voltage silicon assembly adopts high reliable mesa structure with the diffusion craft work, and epoxy resin molded in a compact structure.

▼ 产品特点 Feature

- ❖ 雪崩电压击穿保护特性 Avalanche Characteristic
- ❖ 优异的抗浪涌电流冲击特性 Excellent surge current resistance
- ❖ 高速开关响应特性 High speed switch response characteristics
- ❖ 采用新型环氧树脂真空封装技术，表面具有抗腐蚀性
Epoxy resin molded in vacuum, have anticorrosion in the surface
- ❖ 工作结温-50°C—+150°C T_j:50°C—+150°C
- ❖ 特殊耐高温性能芯片，可承受严酷恶劣的使用条件
Special high temperature resistant chip that can withstand harsh working conditions

▼ 产品 2D 图示

Graphical Representation




极限值 (绝对最大值) Absolute Maximum Ratings	参数名称 Item	符号 Symbol	单位 Unit	测试条件 Conditions	数值 Rating
	反向重复峰值电压 Repetitive Peak Reverse Voltage	V _{RRM}	KV	T _a =25°C I _R =5.0μA	40
	反向工作峰值电压 Peak Working Reverse Voltage	V _{RWM}	KV	T _a =25°C I _R =5.0μA	40
	正向平均电流 Average Forward Current	I _{F(AV)}	A	正弦半波 50Hz, 电阻负载, T _{break} =50°C (50Hz Half-sine Wave, Resistance load @T _{break} =50°C)	3.0
	反向恢复时间 Reverse Recovery Time	trr	nS		--
	正向(不重复)浪涌电流 Surge Forward Current	I _{FSM}	A	正弦半波持续时间 0.01S 50Hz 0.01S @ Half-Sine wave 50Hz	120
	工作环境温度 Operating Ambient Temperature	T _a	°C		-55 ~ +175
	存贮温度 Storage Temperature	T _{stg}	°C		-40 ~ +125
电特性 Electrical Characteristics	正向峰值电压 Forward Peak Voltage	V _{FM}	V	@ T _a =25°C I _F =3A	≥48
	反向峰值电流 Peak Reverse Current	I _{RRM1}	μA	@ T _a =25°C V _{RM} =V _{RRM}	5.0
		I _{RRM2}	μA	@ T _a =100°C V _{RM} =V _{RRM}	50.0


▼ 外形尺寸图示 Outline Drawings

(单位: 毫米 mm)

尺寸/ 图号	长 (L)	宽 (W)	高 (H)	电极 (M)
Fig①	300	50	25	5/6




▼ 特性曲线图 Characteristic Curve




正向特性曲 (2CL40KV/3A)

Forward Characteristics



反向特性曲线 (2CL40KV/3A)

Reverse Characteristics



反向雪崩电压分布 (2CL40KV/3A)
Avalanche Breakdown Voltage Distribution

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Diodes - General Purpose, Power, Switching category:

Click to view products by HVDIODE manufacturer:

Other Similar products are found below :

[MMBD3004S-13-F](#) [RD0306T-H](#) [BAV17-TR](#) [BAV19-TR](#) [HSC285TRF-E](#) [1N3611](#) [NTE156A](#) [NTE574](#) [NTE6244](#) [1SS181-TP](#) [1SS193,LF](#)
[1SS400CST2RA](#) [SDAA13](#) [SHN2D02FUTW1T1G](#) [LS4151GS08](#) [1N4449](#) [1N456A](#) [1N4934-E3/73](#) [1N914B](#) [1N914BTR](#) [1SS226-TP](#)
[RFUH20TB3S](#) [D291S45T](#) [BAV300-TR](#) [BAW56DWQ-7-F](#) [BAW75-TAP](#) [MM230L-CAA](#) [IDW40E65D1](#) [JAN1N3600](#) [LL4151-GS18](#)
[053684A](#) [SMMSD4148T3G](#) [707803H](#) [NSVDAN222T1G](#) [CDSZC01100-HF](#) [LL4150-M-08](#) [1N4454-TR](#) [BAV199E6433HTMA1](#) [BAS28-7](#)
[BAW56HDW-13](#) [BAS28 TR](#) [VS-HFA04SD60STR-M3](#) [NSVM1MA152WKT1G](#) [RGP30D-E3/73](#) [BAV99TQ-13-F](#) [BAS21DWA-7](#) [NTE6250](#)
[NTE582-4](#) [NTE582-6](#) [MMDB30-E28X](#)