

#### **Features**

- Average Rectified Output Current: I<sub>O</sub>=150 mA
- Power Dissipation of 200mw

### **Package Marking and Ordering Information**

Product ID	Pack	Marking	Qty(PCS)	
H1SS355TE-17	SOD-323	T4	3000	



**SOD-323** 



# Maxmim Ratings (Ta=25 unless otherwise noted)


Parameter	Symbol	Limit	Unit
Non-Repetitive Peak Reverse Voltage	$V_{RM}$	100	V
Peak Repetitive Peak Reverse Voltage	$V_{RRM}$		
Working Peak Reverse Voltage	$V_{RWM}$	100	V
DC Blocking Voltage	$V_R$		
RMS Reverse Voltage	$V_{R(RMS)}$	71	٧
Forward Continuous Current	I <sub>FM</sub>	300	mA
Average Rectified Output Current	l <sub>0</sub>	150	mA
Non-Repetitive Peak Forward Surge Current @t=8.3ms	I <sub>FSM</sub>	2.0	А
Power Dissipation	Pd	200	mW
Thermal Resistance from Junction to Ambient	$R_{\theta JA}$	625	°C/W
Operation Junction and Storage Temperature Range	$T_{J}, T_{STG}$	-55~+150	°C


### Electrcal Charcteristics (Ta=25 unless otherwise specified)


Parameter	Symbol	Min	Тур	Max	Unit	Conditions
	V <sub>F1</sub>			0.715	V	I <sub>F</sub> =1mA
Famusard voltage	V <sub>F2</sub>			0.855	V	I <sub>F</sub> =10mA
Forward voltage	$V_{F3}$			1.0	V	I <sub>F</sub> =50mA
	$V_{F4}$			1.25	V	I <sub>F</sub> =150mA
Reverse current	I <sub>R1</sub>			1	μA	V <sub>R</sub> =75V
Reverse current	I <sub>R2</sub>			25	nA	V <sub>R</sub> =20V
Capacitance between terminals	Ст			2	pF	V <sub>R</sub> =0V,f=1MHz
Reverse recovery time	t <sub>rr</sub>			4	ns	$I_F=I_R=10$ mA $Irr=0.1$ X $I_R$ , $R_L=100$ $\Omega$




### **Typical Characteristics**














# **SOD-323 Package Outline Dimensions**







Symbol	Dimensions In Millimeters		Dimensions In Inches		
	Min	Max	Min	Max	
Α		1.100		0.043	
A1	0.000	0.100	0.000	0.004	
A2	0.800	1.000	1.000 0.031		
b	0.250	0.350	0.010	0.014	
С	0.080	0.150	0.003	0.006	
D	1.200	1.400	0.047	0.055	
E	1.600	1.800	0.063	0.071	
E1	2.500	2.750	0.098	0.108	
L	0.475 REF		0.019 REF		
L1	0.250	0.400	0.010	0.016	
θ	0°	8°	0°	8°	



#### **Attention**

- Any and all HUA XUAN YANG ELECTRONICS products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your HUA XUAN YANG ELECTRONICS representative nearest you before using any HUA XUAN YANG ELECTRONICS products described or contained herein in such applications.
- HUA XUAN YANG ELECTRONICS assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein.
- Specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- HUA XUAN YANG ELECTRONICS CO.,LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any or all HUA XUAN YANG ELECTRONICS products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of HUA XUAN YANG ELECTRONICS CO.,LTD.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production.

  HUA XUAN YANG ELECTRONICS believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the HUA XUAN YANG ELECTRONICS product that you intend to use.

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Diodes - General Purpose, Power, Switching category:

Click to view products by HXY MOS manufacturer:

Other Similar products are found below:

MMBD3004S-13-F 1N3611 NTE156A NTE6244 1SS400CST2RA SDAA13 SHN2D02FUTW1T1G 1N4449 1N456A 1N914BTR

D291S45T BAS 16-02L E6327 BAS 16-02V H6327 BAS 21U E6327 BAS 28 E6327 BAW56DWQ-7-F BAW75-TAP MM230L-CAA

IDW40E65D1 JAN1N3600 JAN1N4454UR-1 SMMSD4148T3G BYW95B/A52A NSVDAN222T1G CDSZC01100-HF BAV70HDW-7

BAS28-7 JANTX1N6640 BAW56HDW-13 BAS28 TR VS-HFA04SD60STR-M3 1SS388-TP BAV99TQ-13-F BAV99HDW-13 1N4004

MMDB30-E28X LS4148 IDV15E65D2 W0503RH200S0L W0503SH200S0L M0268SJ200NLF M0268RJ200NLF S3MBF US1J

DAN217U-TP SHV-06JNS-Q IDW30C65D1 IDW80C65D1 VS-HFA30TA60CSR-M3 M1MA152WAT1