

Features

- Average Forward Current:I_{F(AV)}=1A
- Polarity: Color band denotes cathode

Package Marking and Ordering Information

Product ID	Pack	Marking	Qty(PCS)				
SS12~SS120	SMA	SS1 *	2000				







Maxmim Ratings (Ta=25 unless otherwise noted)

14	Symbol	Unit		SS1									
ltem			Test Conditions	2	3	4	5	6	8	10	15	20	
Repetitive Peak Reverse Voltage	V_{RRM}	٧		20	30	40	50	60	80	100	150	200	
Maximum RMS Voltage	VRMS	٧		14	21	28	35	42	56	70	105	140	
Average Forward Current	I _{F(AV)}	Α	60Hz Half-sine wave, Resistance load, FIG.1	1.0									
Surge(Non-repetitive)Forward Current	I _{FSM}	Α	60Hz Half-sine wave, 1 cycle,Ta=25℃	30									
Junction Temperature	TJ	$^{\circ}$		-55~+125 -55~+150									
Storage Temperature	T _{STG}	$^{\circ}$		-55 ~ +150									

Electrcal Charcteristics (Ta=25 unless otherwise specified)

			T (0 1111			SS1									
Item	Symbol	Unit	t Test Condition			3	4	5	6	8	10	15	20		
Peak Forward Voltage	V _F	٧	I _F =		0.55		0.70		0.85		0.95				
Peak Reverse Current	I _{RRM1}	Λ	\/ -\/	T _a =25℃	0.5				0.1						
	I _{RRM2}	mA	$V_{RM}=V_{RRM}$	T _a =100°C			10			5.0					
Thermal	$R_{\theta J-A}$	°C/	Between junct	65											
Resistance(Typical)	$R_{\theta J-L}$	W	Between junct	tion and terminal	20										

Notes:

Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. with 0.2" \times 0.2" (5.0 mm \times 5.0 mm) copper pad areas

Typical Characteristics

FIG.1: FORWARD CURRENT DERATING CURVE




FIG2:Surge Forward Current Capadility




FIG.3: TYPICAL FORWARD CHARACTERISTICS






FIG.4: TYPICAL REVERSE CHARACTERISTICS



SMA Package Outline Dimensions



Dimensions in inches and (millimeters)



Attention

- Any and all HUA XUAN YANG ELECTRONICS products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your HUA XUAN YANG ELECTRONICS representative nearest you before using any HUA XUAN YANG ELECTRONICS products described or contained herein in such applications.
- HUA XUAN YANG ELECTRONICS assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein.
- Specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- HUA XUAN YANG ELECTRONICS CO.,LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any or all HUA XUAN YANG ELECTRONICS products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of HUA XUAN YANG ELECTRONICS CO.,LTD.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production.

 HUA XUAN YANG ELECTRONICS believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the HUA XUAN YANG ELECTRONICS product that you intend to use.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Schottky Diodes & Rectifiers category:

Click to view products by HXY MOS manufacturer:

Other Similar products are found below:

MA4E2039 MMBD301M3T5G RB160M-50TR D83C BAS16E6433HTMA1 BAS 3010S-02LRH E6327 BAT 54-02LRH E6327

NRVBAF360T3G NSR05F40QNXT5G NTE555 JANS1N6640 SS3003CH-TL-E GA01SHT18 CRS10I30A(TE85L,QM MBRA140TRPBF

MBRB30H30CT-1G BAT 15-04R E6152 JANTX1N5712-1 DMJ3940-000 SB007-03C-TB-E NRVBB20100CTT4G NRVBM120LT1G

NTSB30U100CT-1G CRG04(T5L,TEMQ) ACDBA1100LR-HF ACDBA1200-HF ACDBA240-HF ACDBA3100-HF CDBQC0530L-HF

ACDBA260LR-HF ACDBA1100-HF 10BQ015-M3/5BT NRVBM120ET1G VSSB410S-M3/5BT 1N5819T-G PDS1040Q-13 B160BQ-13-F

SDM05U20CSP-7 BAS 70-07 E6433 B140S1F-7 HSM560Je3/TR13 DDB2265-000 ZHCS506QTA HSM190Je3/TR13 B330AF-13

ACDBUC0230-HF SDM1U100S1F-7 MBR10200CTF-G1 CDLL5712 DMF2822-000