

Features

- Two DTC143T chips in a package
- Transistor elements are independent, eliminating interference
- Mounting cost and area can be cut in half



SOT-363

Package Marking and Ordering Information

Product ID	Pack	Marking	Qty(PCS)
UMH3N	SOT-363	НЗ	3000




Maxmim Ratings (Ta=25 unless otherwise noted)


maximi itatingo (ia 20 amoso otnorwico notoa)			
Parameter	Symbol	Value	Units
Collector-base voltage	V _{(BR)CBO}	50	V
Collector-emitter voltage	$V_{(BR)CEO}$	50	V
Emitter-base voltage	$V_{(BR)EBO}$	5	V
Collector current	Ic	100	mA
Collector Power dissipation	Pc	150	mW
Junction temperature	Tj	150	°C
Storage temperature	Tstg	-55~150	$^{\circ}$


Electrcal Charcteristics (Ta=25 unless otherwise specified)


Parameter	Symbol	Min.	Тур	Max.	Unit	Conditions
Collector-base breakdown voltage	$V_{(BR)CBO}$	50			V	Ic=50μA
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	50			V	Ic=1mA
Emitter-base breakdown voltage	$V_{(BR)EBO}$	5			V	I _E =50μA
Collector cut-off current	I _{CBO}			0.5	μA	V _{CB} =50V
Emitter cut-off current	I _{EBO}			0.5	μA	V _{EB} =4V
Collector-emitter saturation voltage	V _{CE(sat)}			0.3	V	$I_C=5mA,I_B=0.25mA$
DC current transfer ratio	h _{FE}	100		600		$V_{CE}=5V,I_{C}=1mA$
Input resistance	R ₁	3.29	4.7	6.11	ΚΩ	
Transition frequency	f⊤		250		MHz	V_{CE} =10V , I_{E} =-5mA, f =100MHz


Typical Electrical




















SOT-363 Package Outline Dimensions







Symbol	Dimensions In Millimeters		Dimensions In Inches		
	Min	Max	Min	Max	
Α	0.900	1.100	0.035	0.043	
A1	0.000	0.100	0.000	0.004	
A2	0.900	1.000	0.035	0.039	
b	0.150	0.350	0.006	0.014	
С	0.100	0.150	0.004	0.006	
D	2.000	2.200	0.079	0.087	
E	1.150	1.350	0.045	0.053	
E1	2.150	2.400	0.085	0.094	
е	0.650 TYP		0.026 TYP		
e1	1.200	1.400	0.047	0.055	
L	0.525 REF		0.021 REF		
L1	0.260	0.460	0.010	0.018	
θ	0°	8°	0°	8°	



Attention

- Any and all HUA XUAN YANG ELECTRONICS products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your HUA XUAN YANG ELECTRONICS representative nearest you before using any HUA XUAN YANG ELECTRONICS products described or contained herein in such applications.
- HUA XUAN YANG ELECTRONICS assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein.
- Specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- HUA XUAN YANG ELECTRONICS CO.,LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any or all HUA XUAN YANG ELECTRONICS products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of HUA XUAN YANG ELECTRONICS CO.,LTD.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production.

 HUA XUAN YANG ELECTRONICS believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the HUA XUAN YANG ELECTRONICS product that you intend to use.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Bipolar Transistors - Pre-Biased category:

Click to view products by HXY MOS manufacturer:

Other Similar products are found below:

DRC9A14E0L DTA124GKAT146 DTA144WETL DTA144WKAT146 DTC113EET1G DTC115TETL DTC115TKAT146
DTC144VUAT106 MUN5241T1G BCR158WH6327XTSA1 NSBA114TDP6T5G SMUN5330DW1T1G SSVMUN5312DW1T2G
RN1303(TE85L,F) RN1306(TE85L,F) EMH15T2R SMUN2214T3G SMUN5335DW1T1G NSBC143ZPDP6T5G NSVDTA143ZET1G
SMUN2214T1G FMA7AT148 DTC114EUA-TP SMUN5237DW1T1G SMUN5213DW1T1G SMUN5114DW1T1G SMUN2111T1G
DTC124ECA-TP DTA114ECA-TP DTC113EM3T5G NSVMUN5135DW1T1G NSVMUN2237T1G NSVDTC143ZM3T5G
SMUN5335DW1T2G SMUN5216DW1T1G NSVMUN5316DW1T1G NSVMUN5215DW1T1G NSVMUN5213DW1T3G
NSVMUN2112T1G NSVIMD10AMT1G NSVEMC2DXV5T1G NSVDTC144WET1G NSVDTC123JET1G NSVDTA143EM3T5G
NSVB1706DMW5T1G NSBC143EDP6T5G RN2101,LF(CT NSBA144WDXV6T1G DTA115TET1G NSBC115TDP6T5G