

IB916 with Heat spreader



IB916 with Heatsink

Features

- Onboard 7th Generation Intel® Core™ U-series processor
- 2x DDR4-2133 SO-DIMM, Max 32GB, Non-ECC
- Supports eDP, DisplayPort and HDMI 1.4
- 2x Intel® PCI-E GbE LAN
- Watchdog timer, Digital I/O, mSATA, iSMART, TPM(2.0)
- 2x USB 2.0, 4x USB 3.0, 4x COM, 2x SATA III
- 1x Mini PCI-E slot

System

| | |
|-----------------|--|
| CPU | BGA1356 for 7th Generation Intel® Core™ U-series i7 / i5 / i3 / Celeron® DC processors, up to 3.4GHz |
| System Memory | 2x DDR4-2133 SO-DIMM, Max 32GB (Non-ECC) |
| System Chipset | Integrated in 7th Generation Intel® Core™ U-series processor |
| BIOS | AMI |
| Watchdog Timer | 256 levels |
| SSD | 1x mSATA |
| H/W Monitor | Yes |
| Expansion Slots | 1x Mini PCI-E (Full-sized) |

Graphics

| | |
|-------------------|--|
| VGA Controller | 7th Generation Intel® Core™ U-series processor integrated graphics |
| VGA Memory | Shared memory |
| Display Interface | Supports eDP, DisplayPort and HDMI |

LAN

| | |
|------------|--|
| Controller | IB916AF series: Intel® I219LM LAN PHY IB916F series : Intel® I219V LAN PHY Intel® I211AT PCI-E Gigabit LAN(as 2nd LAN) |
| Connector | 2x RJ-45 on board |

Multi I/O

| | |
|-------------|--|
| I/O Chipset | Fintek F81846AD-I 1x RS232/422/485(jumperless selection), 3x RS232, 2x SATA III |
| USB | 4 ports USB3.0 on board 2 ports USB2.0 on via pin header |
| Audio | 7th Generation Intel® Core™ U-series processor built-in HD Audio controller + Realtek ALC662 codec |
| Others | Digital I/O, +9V~ +24V DC-in, iSMART, TPM(2.0) |


Mechanical and Environmental

| | |
|------------------------|----------------------------|
| Dimensions | 102mm x 147mm (4" x 5.8") |
| Max. Power Requirement | TBD |
| Operating Temperature | 0°C~60°C (32°F~140°F) |
| Storage Temperature | -20°C~80°C (-4°F~176°F) |
| Relative Humidity | 90% (non-condensing @60°C) |

Ordering Information

| | |
|-------------------|---|
| IB916AF-7600 | 3.5", Intel® Core™ i7-7600U(2.8GHz/3.9GHz), dual PCI-E GbE LAN, eDP, DP & HDMI, TPM(2.0), iSMART, mSATA, iAMT(11.6) |
| IB916AF-7300 | 3.5", Intel® Core™ i5-7300U(2.6GHz/3.5GHz), dual PCI-E GbE LAN, eDP, DP & HDMI, TPM(2.0), mSATA, iSMART |
| IB916F-7100 | 3.5", Intel® Core™ i3-7100U(2.4GHz), dual PCI-E GbE LAN, eDP, DP & HDMI, TPM(2.0), mSATA, iSMART |
| IB916F-3965 (MOQ) | 3.5", Intel® Celeron® 3965U(2.2GHz), dual PCI-E GbE LAN, eDP, DP & HDMI, TPM(2.0), mSATA, iSMART |
| HSIB916-A | Heatsink for IB916/IB917 |
| HSIB916-1 | Heat spreader for IB916/IB917 |
| IB76A | Cable Kit w/ USB, COM, Power cable, SATA+Power cable |

Dimensions and Drawing



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Single Board Computers](#) category:

Click to view products by [Ibase](#) manufacturer:

Other Similar products are found below :

[MANO882VPGGA-H81](#) [SSD3200W-S-SLC-INN 20-101-0738](#) [MVME61006E-2173R](#) [SHB230DGGGA-RC](#) [IMB210VGGA](#) [IB915F-3955](#)
[MI958F-16C](#) [S2600WFT](#) [S2600STB](#) [BBS2600BPS](#) [BLKNUC7I3DNHNC1978015](#) [DEV-17745](#) [BEAGLEBOARD POCKET](#) [MICROSOM](#)
[I2 + WIFI/BT](#) [HUMMINGBOARD-I2EX](#) [BASE + WIFI/BT](#) [HUMMINGBOARD-I4 PRO + WIFI/BT](#) [VAB-600-B](#) [RT5350F-OLINUXINO-](#)
[EVB](#) [MITX-440-DVI-2E](#) [ATCA-7365-D-24GB](#) [NITX-315-DEVKIT](#) [A13-SOM-512](#) [NITX-315](#) [BANANA PI BPI-M1+](#) [A13-SOM-WIFI-](#)
[4GB](#) [AM3359-SOM-EVB-IND](#) [UPS-APLC2-A10-0432](#) [DFR0419](#) [UPS-APLP4-A10-0864](#) [UPS-APLP4-A10-0432](#) [UPS-APLP4-A10-08128](#)
[MI977F-Q27](#) [BBBLUE](#) [IB811F-I30](#) [DFR0470-ENT](#) [Nit6Q_i](#) [M2M \(TELIT\)](#) [RELAY](#) [PROFESSIONAL](#) [GCS22.2.080.2.2.I](#)
[GCS22.8.100.4.2.I](#) [GLS11.2.053.2.2.E](#) [A20-OLINUXINO-LIME-E16GS16M](#) [A20-OLINUXINO-LIME-S16M](#) [A20-OLINUXINO-LIME2-](#)
[E16GS16M](#) [A20-OLINUXINO-MICRO-E16GS16M](#) [A20-OLINUXINO-MICRO-S16M](#) [BANANA PI BPI-W2](#) [T2-OLINUXINO-LIME2-](#)
[S16M-IND](#)