

Features

- Universal input 100-240VAC
- Interchangeable Power Supply
- Approved to UKCA, CE, cULus, TUV, RCM (C-Tick), RoHS & REACH
- UL/IEC/EN 62368-1 Safety Approved
- Meets Efficiency Level VI
- EMC Class B Certified
- Single Output 5-30V DC
- OVP, OCP, OTP & Short Circuit



Ideal Power's 15DYS824-xyW-K 24W AC/DC External Adapter Interchangeable Power Supply (PSU) Series are certified to UKCA, CE, cULus, TUV, RCM (C-Tick), RoHS, REACH & UL/IEC/EN 62368-1 Standards and comply with (EU) 2019/1782, Level VI Efficiency Regulations. These are primarily used in ITE, Audio & Video Industries and customised solutions are available upon request.

Models

Model Number	Output Voltage	Output Current	Output Power
15DYS824-050400W-K	5VDC	4A	20W
15DYS824-075282W-K	7.5VDC	2.82A	21.15W
15DYS824-090250W-K	9VDC	2.5A	22.5W
15DYS824-120200W-K	12VDC	2A	24W
15DYS824-150160W-K	15VDC	1.6A	24W
15DYS824-180133W-K	18VDC	1.33A	24W
15DYS824-240100W-K	24VDC	1A	24W
15DYS824-300080W-K	30VDC	0.80A	24W

Input Data

	Min	Typical	Max	Units	Notes
Input Voltage	90	--	264	V AC	100-240VAC +/- 10%
Input Frequency	47	--	63	Hz	50-60Hz +/- 5%
Input Current	--	0.7	--	A	
Inrush Current	0	--	60	A	At cold start, 100 / 240V AC
Leakage Current	--	--	0.25	mA	

Output Data

	Min	Typical	Max	Units	Notes
Output Voltage		5		%	
Ripple & Noise		1		%	
Over Current Protection	Typically, 115-135% of Rated Current				
Short Circuit Protection	Continuous short circuit proof. Will recover if fault condition is removed				
Over Voltage Protection	Will recover if fault condition is removed				

Environmental Data

	Min	Typical	Max	Units	Notes
Operating Temperature	0		+40	°C	
Storage Temperature	-20		+80	°C	
Operating Humidity	10		90	°C	Operating 10% to 90%
Operating Humidity	5		95	°C	Storage 5% to 95%

Other Information

	Min	Typical	Max	Units	Notes
Isolation					2KVdc, between primary and secondary circuit
MTBF	50,000			hrs	
Weight					200 +/-10g
Dimensions	Refer to mechanical drawings				

EMC Emissions (2014/30/EU)


	Standard	Test Level	Criteria	Notes
Conducted	EN 55032	Pass	B	EMC Directive 2014/30/EU
Radiated	EN 55032	Pass	B	
Harmonic Standard	EN 61000-3-2		Class D	P.F. shall >0.95 @100Vac input and >0.9 @240Vac input

EMC Immunity (2014/30/EU)

	Standard	Test Level	Criteria	Notes
EMS	EN 55035			
EMS	EN 61204-3			
ESD	IEC 61000-4-2		B	Contact: +/- 4KV; Air: +/- 8KV
RS	IEC 61000-4-3			Frequency: 80-1000MHz. Field Strength: 3V/M ' 80% AM (1KHz)
EFT	IEC 61000-4-4		A/B	0.5/1.0KV on input AC power ports
Surge	IEC 61000-4-5		A	Line to Line: +/- 1KV (peak); Line to F.G: +/- 2KV (peak)
Conducted				
PfMF				
Dips and Interruptions				


Safety Approvals

	Safety Standards
RoHS/REACH	RoHS Directive (EU) 2015/863 & REACH (205 SVHC)
CE LVD Directive 2014/35/EU	Yes (UK/European) – Only applicable for UK & EURO plugs.
cULus	Yes – Only applicable for US plug.
TUV	Yes (German/European) – Only applicable for EURO plug.
RCM & C-Tick	Yes – Only applicable for Australian plug.

Mechanical Drawing


AC – DC

Mechanical Drawing (Continued)



AC - DC

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for IDEAL POWER manufacturer:

Other Similar products are found below :

[25HK-AY-120A200-DH](#) [5210952C-12-3A](#) [15DYS850-090500W-K](#) [15DYS605-120050W-5](#) [15DYS6150-1201000P](#) [15DYS824-050400W-K](#)
[15DYS6150-3600416P](#) [15DYS818-090200W-K](#) [15DYS824-075280W-K](#) [15DYS6150-4800312P](#) [15DYS618-090200W-K](#) [5211012D-12-3A](#)
[25HK-AW-150A100-CP](#) [15DYS865-150400W](#) [15DYS865-180350W](#) [15DYS818-150120W-K](#) [15DYS650-300168W](#) [5210952E-24-3A](#)
[15DYS850-090500W](#) [25HK-AW-090A167-CP](#) [15DYS865-240270W](#) [15DYS650-240210W](#) [15DYS850-240210W](#) [25HK-AB-060A300-D56](#)
[15DYS865-120500W](#) [25HK-AY-240A100-CP](#) [15DYS824-090250W-K](#) [15DYS650-120420W-K](#) [15DYS850-240210W-K](#) [15DYS865-](#)
[300216W](#) [15DYS650-180280W](#) [25HK-AY-090A266-CP](#) [15DYS612-120100W-3](#) [15DYS818-150120W-3](#) [15DYS850-120420W](#) [25HK-AB-](#)
[090A250-D56](#) [15DYS850-120420W-K](#) [15DYS6150-2400625P](#) [25HK-AB-150A200-CP6](#) [25HK-AB-050A400-CP6](#) [25HK-AP-240A025-CP-](#)
[3A](#) [25HK-AP-050A120-CP-3A](#) [15DYS602-120500W](#) [15DYS818-050300W-K](#) [15DYS818-050300W-3](#) [25HK-AY-050A300-DH](#) [25HK-AY-](#)
[050A300-CP](#) [25HK-AP-120A050-CP-3A](#) [25HK-AW-120A125-CP](#) [15DYS812-120100W-3](#)