

TECHNICAL DATA SHEET

Nonferrous alloy type TA

General notes:

- » **Titanium Grade 1** (unalloyed titanium)
- » engineering materials with extraordinary combination of properties: relatively low density (4.5 g/cm³), good mechanical properties and a very high melting point that allows the use at high temperatures (1600 °F, 870°C)
- » good corrosion resistance at room temperature to air, marine and a variety of industrial environments
- » good cold formability, high ductility
- » fully non-magnetic (100%)
- » generally it is used when in addition to the corrosion resistance, high strength-to-weight ratio is required
- » bio-compatible (maintain cell integrity, no inflammatory response)
- » typical applications include handling of components in cleaning/chemical processes also at high temperature, histology, biology, medicine, surgery

Composition

Component	Wt. %	Component	Wt. %	Component	Wt. %
Ti	99.5	C	≤0.1	Fe	≤0.2
O	≤0.18	N	≤0.03	H	≤0.015

Mechanical properties

State	annealed
Density	4.51 g/cm³
Hardness, Vickers	190 HV
Tensile strength, ultimate	330 MPa
Tensile strength, yield	240 MPa
Elongation, break	30%
Modulus of elasticity	100 GPa

Thermal properties

Coef. of lin. therm expansion	9.2 E-6/°C	0°C-315°C
Specific heat capacity	0.52 J/(g K)	
Continuos use temperature	350°C	
Thermal conductivity	16 W/(m K)	

Electrical properties

Resistivity	0.45 E-4 Ohm.cm
-------------	------------------------

This document contains information based on average values as obtained from the results of laboratory tests and observations made on the material. Ideal-tek SA declines all responsibility from an improper use of the product described in this document.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Soldering & Desoldering Stations](#) category:

Click to view products by [Ideal-Tek](#) manufacturer:

Other Similar products are found below :

[GS1116](#) [WESD51D](#) [BH-010](#) [T0058768747](#) [CA0202](#) [CA0201](#) [WXD2N](#) [Q-7100-9000](#) [ALFA](#) [T0058757898](#) [WXD2010N](#) [T0058768762](#)
[145-2000-ESDN](#) [T0058758721N](#) [0008473](#) [WTL1000-1](#) [700-3051-ESD](#) [0051514699N](#) [0051512199N](#) [T0058768725N](#) [ZD-415R](#) [ZD-415R-H](#)
[WELPB102](#) [HR-2550A](#) [T130-1.0I](#) [T0051011299N](#) [CVC-7CN0004P](#) [CVC-9CH0025S](#) [CVC-8CH0010S](#) [CV-H5-DSHP](#) [CS-2F](#)
[WLSK3023C](#) [WLSK8023C](#) [AP-SF](#) [AT-SA](#) [AT-SB](#) [DN-SF](#) [DR-SF](#) [DS-SF](#) [HD-SF](#) [0016344](#) [00B.SA.0](#) [0120CDK](#) [0551903](#) [0DIG20A45](#)
[0IC1100A](#) [0ICV2000XV](#) [0T56](#) [CL-SFE/1 FILTERS](#) [PX0410/03P/5055](#)