

Stainless steel type SA

General notes:

- » **Low carbon austenitic steel** (Material number 1.4435, DIN X2CrNiMo18-14-3, AISI number 316L)
- » contains from 16.5 to 18.5 wt% chromium and has important quantities of nickel and molybdenum as additional alloying elements
- » non-magnetizable (80%)
- » good corrosion resistance to most chemicals, salts and acids
- » generally used where corrosion resistance and toughness are primary requirements
- » typical applications include tweezers for the electronic industry, watch-makers, jewelers and laboratory and medical applications in moderately aggressive chemical environments

Composition

| Component | Wt.% | Component | Wt.% | Component | Wt.% |
|-----------|---------|-----------|-----------|-----------|-----------|
| C | ≤0.03 | Si | ≤1.0 | Mn | ≤2.0 |
| P | ≤0.045 | S | ≤0.03 | Cr | 17.0-19.0 |
| Mo | 2.5-3.0 | Ni | 12.5-15.0 | | |

Mechanical properties

| | |
|----------------------------|-----------------------------|
| State | annealed |
| Density | 8.0 g/cm³ |
| Hardness, Vickers | 230 HV |
| Tensile strength, ultimate | 500-700 MPa |
| Tensile strength, yield | 290 |
| 0.2% Yield stress | ≥ 200 MPa |
| Elongation, break | 40% |
| Modulus of elasticity | 200 GPa |

Thermal properties

| | | |
|-------------------------------|---------------------|------------|
| Coef. of lin. therm expansion | 16.0 E-6/°C | 20°C-100°C |
| Coef. of lin. therm expansion | 17.0 E-6/°C | 20°C-300°C |
| Specific heat capacity | 0.50 J/(g·K) | |
| Thermal conductivity | 15 W/(m·K) | |
| Continuous use temperature | 350°C | |
| Max service temperature, air | 925°C | |

Electrical properties

| | |
|-------------|------------------------|
| Resistivity | 0.75 E-4 Ohm.cm |
|-------------|------------------------|

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Hand Tools](#) category:

Click to view products by [Ideal-Tek](#) manufacturer:

Other Similar products are found below :

[58284-1](#) [662908-1](#) [68764-0001](#) [690619-6](#) [D20419-189](#) [7-354778-7](#) [768531-1](#) [821903-5](#) [822253-1](#) [854183-1](#) [854358-1](#) [992258-1](#) [1-21046-3](#)
[1-22278-0](#) [1-22278-2](#) [1-24954-2](#) [125529-5](#) [126513-1](#) [1-305579-8](#) [1320846-1](#) [1338618-1](#) [1338968-2](#) [1-354779-0](#) [1-354779-2](#) [1-354779-4](#)
[1424443-1](#) [1424289-1](#) [1424444-1](#) [MS24256A16](#) [1-525442-0](#) [1532195-2](#) [1538773-2](#) [1-59681-8](#) [1-59907-5](#) [1-692134-3](#) [1725760-1](#) [HT-](#)
[920A-124-HTELE-RPL-KIT](#) [1976923-1](#) [1976969-1](#) [2063794-1](#) [2063795-1](#) [2-21002-1](#) [2-21002-3](#) [2-21002-4](#) [2-21002-7](#) [2-21002-9](#) [2-21004-](#)
[0](#) [229399-2](#) [229707-1](#) [911737-2](#)