









Cables and Connectors *FDD / HDD Cable*

| SATA HDD Cable | | | |
|-------------------|---|--|---|
| |  |  |  |
| Model Name | 32801-000703-400-RS | 32102-000100-100-RS | 32000-080700-RS |
| Cable Type | SATA HDD cable | SATA power cable | SATA + Power cable |
| Connector | SATA 7-pin | 4-pin + 2 x SATA 15-pin | SATA 7-pin + 4-pin |
| Connector Type | Lockable | SATA power connector | |
| Length | 50 cm | 15 cm | SATA cable 20 cm Power cable 10 cm |

| SATA HDD Cable | | |
|-------------------|---|---|
| |  |  |
| Model Name | 32801-000201-300-RS | 32801-000100-300-RS |
| Cable Type | SATA + Power cable | SATA + Power cable |
| Connector | SATA 7-pin + 2-pin wafer (P=2 mm) | SATA 7-pin + 4-pin wafer (P=2.54 mm) |
| Connector Type | 2-pin PH 2.0 | 4-pin PH 2.54 mm |
| Length | SATA cable 15 cm Power cable 15 cm | SATA cable 20 cm Power cable 20 cm |

| IDE HDD Cable | | | |
|-------------------|---|---|---|
| |  |  |  |
| Model Name | 32200-000009-RS | 32221-001000-101-RS | 32200-025001-RS |
| Cable Type | IDE HDD flat cable | IDE HDD flat cable | IDE HDD flat cable |
| Connector | 44p-44p | 44p-44p | 44p-40p-40p |
| Connector Type | 2.0mm -2.0mm | 2.0mm -2.0mm | 2.0mm-2.54mm-2.54mm |
| Length | 40 cm | 25 cm | 20 cm + 15 cm |

| IDE HDD Cable | | | |
|-------------------|---|---|---|
| |  |  |  |
| Model Name | 32225-002000-200-RS | 32221-001700-100-RS | CB-HD32-RS |
| Cable Type | ATA-66 HDD flat cable | ATA-33 HDD flat cable | IDE HDD flat cable |
| Connector | 40p-40p-40p | 44p-40p-40p | 40p-44p |
| Connector Type | 2.54mm | 2.0mm-2.54mm-2.54mm | 2.54mm-2.0mm |
| Length | 30 cm + 15 cm | 20 cm + 15 cm | IDE cable: 39 cm Power cable: 20 cm |

Part numbers listed in the product catalog are for reference purposes. IEI reserves the right to implement substitution parts when the function is not affected.

1
Industrial
Computing
Solutions

2
Video
Capture
Solutions






3
Industrial
Computer
Chassis






4
Open
Frame
Monitor






5
Power Supply/
Peripherals





6
All-in-One
System

Cables and Connectors *Paralle / Serial Cable*

| | Serial cable | | | | |
|-------------------|---|---|---|---|---|
| |  |  |  |  |  |
| Model Name | 45002-008103-RS | 19800-000300-100-RS | 19800-010900-200-RS | 19800-000051-RS | 19800-003600-100-RS |
| Cable Type | Serial port | Serial port cable | Serial port cable | Serial port cable | Serial port cable |
| Board Side | N/A | 10-pin (2x5) connector (2.0 mm) | 10-pin (2x5) connector (2.54 mm) | 2 x 10-pin (2x5) connector (2.54 mm) | 2 x 10-pin (2x5) connector (2.54mm) |
| Board Side Pitch | 2.54 mm | 2.0 mm | 2.54 mm | 2.54 mm | 2.54 mm |
| Device Side | 2 x DE9M | DE9M | DE9M | 2 x DE9M | 2 x DE9M |
| Bracket | Yes | Yes | Yes | Yes | Yes |
| Length | 9 cm | 30 cm | 50 cm | 23 cm | 40 cm |

| | Serial cable | | | | |
|-------------------|---|---|---|---|---|
| |  |  |  |  |  |
| Model Name | 19800-000112-RS | 32205-000702-100-RS | 32200-000049-RS | 32205-001203-200-RS | 32205-002000-100-RS |
| Cable Type | Serial port cable | Serial port cable | Serial port cable | Serial port cable | Serial port cable |
| Board Side | 2 x 10-pin (2x5) connector (2.0 mm) | 10-pin (2x5) connector (2.54 mm) | 10-pin (2x5) connector (2.0 mm) | 40-pin (2x20) connector (2.54 mm) | 40-pin (2x20) connector (2.0 mm) |
| Board Side Pitch | 2.0 mm | 2.54 mm | 2.0 mm | 2.54 mm | 2.0 mm |
| Device Side | 2 x DE9M | DE9M | DE9M | 4 x DE9M | 4 x DE9M |
| Bracket | Yes | No | No | No | No |
| Length | 30 cm | 23 cm | 20 cm | 40/40/40/40 cm | 30 cm |

| | Serial cable | | | | |
|-------------------|---|---|---|---|---|
| |  |  |  |  |  |
| Model Name | 32200-025401-RS | 32205-002500-100-RS | 19800-004400-200-RS | 19800-004300-100-RS | 32200-026500-RS |
| Cable Type | Serial port cable | RS-422/485 cable | RS-232 & RS-422/485 cable | RS-232 & RS-422/485 cable | RS-232 & RS-422/485 cable |
| Board Side | 40-pin (2x20) connector (2.0 mm) | 16-pin (2x8) connector (2.54 mm) | 14-pin (2x7) connector (2.54 mm) | 14-pin (2x7) connector (2.0 mm) | 14-pin (2x7) connector (2.0 mm) |
| Board Side Pitch | 2.0 mm | 2.54 mm | 2.54 mm | 2.0 mm | 2.0 mm |
| Device Side | 4 x DE9M | 4 x DE9M | 2 x DE9M | 2 x DE9M | 2 x DE9M |
| Bracket | No | No | Yes | Yes | No |
| Length | 30 cm | 12 cm | 25.5 cm | 25 cm | 29 cm |

| | Serial cable | Paralle cable | | |
|-------------------|---|---|--|---|
| |  |  |  |  |
| Model Name | 32205-003800-300-RS | 19800-000049-RS | 19800-003500-100-RS | 32200-015100-RS |
| Cable Type | RS-422/485 cable | Parallel port cable | Parallel and serial port cable | Parallel port cable |
| Board Side | 4-pin (1x4) connector (2.0 mm) | 26-pin (2x13) connector (2.54 mm) | 26-pin (2x13) connector (2.0 mm) 10-pin (2x5) connector (2.0 mm) | 26-pin (2x13) connector (2.0 mm) |
| Board Side Pitch | 2.0 mm | 2.54 mm | 2.0 mm | 2.0 mm |
| Device Side | DE9M | DB25F | DB25F + DE9M | DB25F |
| Bracket | No | Yes | Yes | No |
| Length | 20 cm | 24 cm | 24 cm | 28 cm |

Part numbers listed in the product catalog are for reference purposes. IEI reserves the right to implement substitution parts when the function is not affected.

1

Industrial Computing Solutions

2

Video Capture Solutions

3

Industrial Computer Chassis

4

Open Frame Monitor





5





Power Supply/ Peripherals





6






All-in-One System

Cables and Connectors *USB / Keyboard / Mouse / Power Cable*

| USB cable | | | | |
|-------------------|---|---|--|---|
| |  |  |  |  |
| Model Name | 32001-010800-100-RS | 32001-006404-100-RS | 19800-000100-200-RS | 19800-003100-300-RS |
| Cable type | USB cable | USB cable | USB cable | USB cable |
| Board side | 2 x 4-pin connector (2.54 mm) | 2 x 4-pin connector (2.0 mm) | 2 x 8-pin (2x4) connector (2.54 mm) | 2 x 4-pin (1x4) connector (2.54 mm) |
| Board side pitch | 2.54 mm | 2.00 mm | 2.54 mm | 2.54 mm |
| Device side | 2 x USB | 2 x USB | 4 x USB | 2 x USB |
| Bracket | No | No | Yes | Yes |
| Length | 20 cm | 22 cm | 30 cm | 30 cm |

| USB cable | | | | |
|-------------------|---|---|--|---|
| |  |  |  |  |
| Model Name | CB-USB02A-RS | 32000-044300-RS | 32000-073400-RS | 32001-008600-200-RS |
| Cable type | USB cable | USB cable | USB cable | USB cable |
| Board side | 1 x 8-pin (2x4) connector (2.0 mm) | 1 x 8-pin (2x4) connector (2.54 mm) | 2 x 5-pin connector (2.0 mm) for WAFER-8523, WAFER-945GSE3 only | 1 x 8-pin (2x4) connector (2.0 mm) |
| Board side pitch | 2.0 mm | 2.54 mm | 2.0 mm | 2.0 mm |
| Device side | 2 x USB | 2 x USB | 2 x USB | 2 x USB |
| Bracket | Yes | No | No | No |
| Length | 30 cm | 21 cm | 40 cm | 21 cm |

| Keyboard / Mouse cable | | | | |
|------------------------|---|---|--|---|
| |  |  |  |  |
| Model Name | 19800-000066-RS | 19800-000075-RS | 32006-000300-100-RS | 32000-023800-RS |
| Cable type | Keyboard and mouse cable | Y-Cable | Y-Cable | Y-Cable |
| Board side | 2 x 5-pin (1x5) connector (2.54 mm) | 1 x 6-pin (1x6) connector (2.0 mm) | 1 x male PS/2 | 1 x 6-pin (1x6) connector (2.0 mm) |
| Board side pitch | 2.54 mm | 2.0 mm | | 2.0 mm |
| Device side | 2 x Female PS/2 | 2 x Female PS/2 | 2 x Female PS/2 | 2 x Female PS/2 |
| Bracket | Yes | Yes | No | No |
| Length | 30 cm | 22 cm | 12 cm (KB) + 14 (MS) | 13 cm |

| Power cable | | | | | |
|-------------------|---|---|---|---|---|
| |  |  |  |  |  |
| Model Name | 32100-087100-RS | 32102-022100-100-RS | 32102-005100-200-RS | 32100-192900-RS | 32100-130300-RS |
| Cable type | 12V power cable | ATX function cable | 12V power cable | 12V power cable | Power cable for PC/104 CPU module |
| Board side | 1 x 4-pin (2x2) connector | 1 x 20-pin ATX power connector | 1 x 4-pin (2x2) connector | 1 x 4-pin (2x2) connector | 1 x 4-pin (1x4) molex |
| Device side | 2 x 4-pin (1x4) molex | 1 x 4-pin (1x4) molex 1 x 3-pin PS_ON connector | With lock screw | 4-pin 3.5 mm terminal block | 3-pin 3.5 mm terminal block |
| Bracket | No | No | No | No | No |
| Length | 13 cm | 30 cm | 25 cm | 25 cm | 10 cm |

Part numbers listed in the product catalog are for reference purposes. IEI reserves the right to implement substitution parts when the function is not affected.

Cables and Connectors *Audio / LAN / VGA / Adapter Cable*

| | Audio cable | | |
|-------------------|---|---|---|
| |  |  |  |
| Model Name | 19800-000111-RS | 32007-002600-100-RS | 32000-028800-RS |
| Cable type | Audio cable | Audio cable | Audio cable |
| Board side | 10-pin (2x5) connector (2.0 mm) | 10-pin (2x5) connector (2.0 mm) | 12-pin (2x6) connector (2.54 mm) |
| Board side pitch | 2.0 mm | 2.0 mm | 2.54 mm |
| Device side | 3 x Audio jacks | 3 x Audio jacks | 4 x Audio jacks |
| Bracket | Yes | No | No |
| Length | 30 cm | 30 cm | 25 cm |

| | LAN cable | VGA cable | |
|-------------------|---|---|---|
| |  |  |  |
| Model Name | 32013-001700-100-RS | 32003-000800-100-RS | 32000-033804-RS |
| Cable type | LAN cable | VGA cable | VGA cable |
| Board side | 10-pin (2x5) connector (2.0 mm) | 10-pin (2x5) connector (2.54 mm) | 10-pin (2x5) connector (2.0 mm) |
| Board side pitch | 2.0 mm | 2.54 mm | 2.0 mm |
| Device side | 1 x RJ-45 | 1 x DB15F | 1 x DB15F |
| Bracket | No | No | No |
| Length | 31 cm | 30 cm | 30 cm |

Part numbers listed in the product catalog are for reference purposes. IEI reserves the right to implement substitution parts when the function is not affected.

Rackmount Slide *Optional Chassis Accessories*

| | SLIDE | | |
|-------------------|---|--|---|
| |  |  |  |
| Model Name | SLIDE-18 | SLIDE-24 | EXTENDER-6 |
| Specification | 18" rackmount slide | 24" rackmount slide | 6" extender |
| Description | For rackmount chassis w/ depth up to 500 | For rackmount chassis w/ depth up to 600 | For 18" or 24" slider |

DIN Rail Kit

| | KIT | |
|-------------------|---|---|
| |  |  |
| Model Name | DK-100-R10 | DK-84MB |
| Specification | 110 mm (W) x 100 mm (D) | 168 mm (W) x 96 mm (D) |
| Description | VESA 100 to DIN-rail kit | DIN mount kit for ECW-281 series, black, RoHS |

1 Industrial Computing Solutions

2 Video Capture Solutions

3 Industrial Computer Chassis

4 Open Frame Monitor

5 Power Supply/ Peripherals

6 All-in-One System

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Specialised Cables category](#):

Click to view products by [IEI manufacturer](#):

Other Similar products are found below :

[603PT6](#) [603SS6L](#) [604PT6](#) [604SS6](#) [706000D02F200](#) [910640](#) [1200740077](#) [1200740114](#) [AC172](#) [ACL-SSI-4](#) [R88ACAKA0015SRE](#)
[R88ACAWL005SDE](#) [R88ACRGD0R3C](#) [1300150047](#) [1300660036](#) [1302262116](#) [1300150149](#) [1300220020](#) [1300220104](#) [1300220119](#)
[1301240492](#) [1301810221](#) [1365323-1](#) [1613055](#) [176P12](#) [1971465-2](#) [20240400003](#) [20240400013](#) [2085828-1](#) [20886510030](#) [2-22733-8](#) [22733-](#)
[8](#) [CB-BATACC-RS](#) [CB-JST3PSW-RS](#) [25AC84](#) [25AK84X](#) [25AU25](#) [25FN82](#) [3011-03](#) [AC118](#) [ACL-HHS-1M\(CAT5E\)](#)
[SSL009PC2DC012N](#) [FC2A-KC6C](#) [2085828-2](#) [20886510150](#) [CCSFCBF2](#) [R88A-CRWB020N](#) [416216000-3](#) [426062900-3](#) [426064500-3](#)