

Extremely high accuracy & stability, sealed, on-site resistance standards requiring no oil or temperature bath. The SRL Series is available in a wide range of off-the-shelf and custom values and combinations.

- Very high stability
- Very low temperature coefficient
- No need for stabilization in a temperature-controlled bath

- Wide choice of values and custom values - 1 mΩ to 10 TΩ
- Combination units available
- Calibration report at 3 temperatures - Temperature chart and  $\alpha$  and  $\beta$  provided
- Very low hysteresis
- Direct plug-in unit for most DMM's - Fluke, Keysight, and others



**SRL-10 kΩ High-Accuracy Resistance Standard**

### AVAILABLE UNITS



**SRL-10GΩ High-Accuracy Resistance Standard**



**SRL-Series High-Accuracy Resistance Standard Combination Unit**



**SRL-DMM Version:** Available in any value as a direct plug-in for most DMM's; this avoids external leads and noise pickup. (Part number SRL-XXX-DMM Model, e.g. SRL-10K-8508)

### SPECIFICATIONS

#### Retrace:

**1 Ω to 19 MΩ:** Permanent shift in resistance value is <2 ppm for 23°C to 0°C to 23°C cycle, and 23°C to 40°C to 23°C cycle

#### Calibration Report:

Initial SI traceable calibration data provided in 0.5°C increments for temperature range of 18°C to 28°C.

#### Operating Temperature:

Temperature range of 18°C to 28°C

#### Calibration Conditions:

At 23°C, low power, traceable to SI  
 <1 MΩ: Five-wire  
 1 MΩ - 20 MΩ: Three-wire  
 ≥100 MΩ: Four-wire

#### Terminals:

Gold-plated, tellurium-copper, low-thermal-emf binding posts on standard 3/4 inch spacing. A **GROUND** terminal is provided on all units.

#### Dimensions:

**for 1 mΩ:** 16 cm H x 9 cm Dia (6.3" x 3.55")  
**all others:** 8.6 cm H x 10.5 cm W x 12.7 cm D (3.4" x 4.15" x 5")

#### Weight:

**for 1 mΩ:** 0.9 kg (2 lbs)  
**all others:** 0.73 kg (1.6 lb)

#### Other available terminals:

- DMM direct input compatibles
- BNC, Triax, and custom connectors

#### Transit Case:

(see page 3)



# High-Accuracy, High-Stability Resistance Standards

## SRL Series

### SPECIFICATIONS

Nominal Value	Model Number	Adjustment to Nominal	Stability per year (max change)	Max Resistance Change 18-28°C from 23 °C	Max Applied Input			Typical change at 1 kHz	Terminals	
					0 ppm change*	<1 ppm change**	<3 ppm change**			
1 mΩ	SRL-0.001	±100 ppm	±50 ppm	25 ppm/°C †				<100 ppm	4 bp's + gnd	
10 mΩ	SRL-0.01	±5 ppm	±15 ppm	5 ppm/°C	25 mW	50 mW	200 mW		4 bp's + gnd	
19 mΩ	SRL-0.019	±5 ppm	±15 ppm	5 ppm/°C	25 mW	50 mW	200 mW		4 bp's + gnd	
20 mΩ	SRL-0.02	±5 ppm	±15 ppm	5 ppm/°C	25 mW	50 mW	200 mW		4 bp's + gnd	
100 mΩ	SRL-0.1	±5 ppm	±12 ppm	2 ppm/°C	50 mW	100 mW	250 mW		4 bp's + gnd	
190 mΩ	SRL-0.19	±5 ppm	±12 ppm	2 ppm/°C	50 mW	100 mW	250 mW		4 bp's + gnd	
200 mΩ	SRL-0.2	±5 ppm	±12 ppm	2 ppm/°C	50 mW	100 mW	250 mW		4 bp's + gnd	
1 Ω	SRL-1	±2 ppm	±8 ppm	3 ppm tot	175 mW	350 mW	850 mW		4 bp's + gnd	
1.9 Ω	SRL-1.9	±2 ppm	±8 ppm	3 ppm tot	175 mW	350 mW	850 mW		4 bp's + gnd	
2 Ω	SRL-2	±2 ppm	±8 ppm	3 ppm tot	175 mW	350 mW	850 mW		4 bp's + gnd	
10 Ω	SRL-10	±2 ppm	±8 ppm	3 ppm tot	100 mW	200 mW	500 mW		4 bp's + gnd	
19 Ω	SRL-19	±2 ppm	±8 ppm	3 ppm tot	100 mW	200 mW	500 mW		4 bp's + gnd	
20 Ω	SRL-20	±2 ppm	±8 ppm	3 ppm tot	100 mW	200 mW	500 mW		4 bp's + gnd	
25 Ω	SRL-25	±2 ppm	±8 ppm	3 ppm tot	100 mW	200 mW	500 mW		4 bp's + gnd	
30 Ω	SRL-30	±2 ppm	±8 ppm	3 ppm tot	100 mW	200 mW	500 mW		4 bp's + gnd	
50 Ω	SRL-50	±2 ppm	±8 ppm	3 ppm tot	100 mW	200 mW	500 mW		4 bp's + gnd	
100 Ω	SRL-100	±2 ppm	±6 ppm	3 ppm tot	100 mW	200 mW	500 mW		4 bp's + gnd	
190 Ω	SRL-190	±2 ppm	±6 ppm	3 ppm tot	100 mW	200 mW	500 mW		4 bp's + gnd	
200 Ω	SRL-200	±2 ppm	±6 ppm	3 ppm tot	100 mW	200 mW	500 mW		4 bp's + gnd	
350 Ω	SRL-350	±2 ppm	±6 ppm	3 ppm tot	100 mW	200 mW	500 mW		4 bp's + gnd	
400 Ω	SRL-400	±2 ppm	±6 ppm	3 ppm tot	100 mW	200 mW	500 mW		4 bp's + gnd	
1 kΩ	SRL-1K	±2 ppm	±6 ppm	3 ppm tot	100 mW	200 mW	500 mW		4 bp's + gnd	
1 kΩ	SRL-1K-TC	±2 ppm	±6 ppm	2 ppm tot	100 mW	200 mW	500 mW		4 bp's + gnd	
1.9 kΩ	SRL-1.9K	±2 ppm	±6 ppm	2 ppm tot	100 mW	200 mW	500 mW		4 bp's + gnd	
2 kΩ	SRL-2K	±2 ppm	±6 ppm	2 ppm tot	100 mW	200 mW	500 mW		4 bp's + gnd	
4 kΩ	SRL-4K	±2 ppm	±4 ppm	2 ppm tot	100 mW	200 mW	500 mW		4 bp's + gnd	
10 kΩ	SRL-10K	±2 ppm	±4 ppm	1.5 ppm tot	100 mW	200 mW	500 mW		4 bp's + gnd	
19 kΩ	SRL-19K	±2 ppm	±4 ppm	2 ppm tot	100 mW	200 mW	500 mW		4 bp's + gnd	
20 kΩ	SRL-20K	±2 ppm	±4 ppm	2 ppm tot	100 mW	200 mW	500 mW		4 bp's + gnd	
100 kΩ	SRL-100K	±2 ppm	±6 ppm	2 ppm tot	100 mW	200 mW	500 mW		4 bp's + gnd	
190 kΩ	SRL-190K	±2 ppm	±8 ppm	2 ppm tot	100 mW	200 mW	500 mW		4 bp's + gnd	
200 kΩ	SRL-200K	±2 ppm	±8 ppm	2 ppm tot	100 mW	200 mW	500 mW		4 bp's + gnd	
1 MΩ	SRL-1M	±2 ppm	±8 ppm	2 ppm tot	100 mW	200 mW	500 mW		2 bp's + gnd	
1.9 MΩ	SRL-1.9M	±2 ppm	±9 ppm	3 ppm tot	100 mW	200 mW	500 mW		2 bp's + gnd	
2 MΩ	SRL-2M	±2 ppm	±9 ppm	3 ppm tot	100 mW	200 mW	500 mW		2 bp's + gnd	
10 MΩ	SRL-10M	±2 ppm	±9 ppm	3 ppm tot	500 V	1000 V	2500 V		<2 %	2 bp's + gnd
19 MΩ	SRL-19M	±2 ppm	±10 ppm	4 ppm tot	1000 V	2000 V	5000 V		<2 %	2 bp's + gnd
20 MΩ	SRL-20M	±2 ppm	±10 ppm	4 ppm tot	1000 V	2000 V	5000 V	2 bp's + gnd		
100 MΩ	SRL-100M	±10 ppm	±20 ppm	5 ppm/°C	2000 V	4000 V	5000 V	NA	2 bp's + gnd + guard	
190 MΩ	SRL-190M	±10 ppm	±20 ppm	5 ppm/°C	2000 V	5000 V			2 bp's + gnd + guard	
200 MΩ	SRL-200M	±10 ppm	±20 ppm	5 ppm/°C	5000 V				2 bp's + gnd + guard	
1 GΩ	SRL-1G	±0.1%	±200 ppm	23 ppm/°C	5000 V				2 bp's + gnd + guard	
1.9 GΩ	SRL-1.9G	±0.1%	±200 ppm	23 ppm/°C	5000 V				2 bp's + gnd + guard	
2 GΩ	SRL-2G	±0.1%	±200 ppm	23 ppm/°C	5000 V				2 bp's + gnd + guard	
10 GΩ	SRL-10G	±0.1%	±500 ppm	25 ppm/°C	5000 V				2 bp's + gnd + guard	
19 GΩ	SRL-19G	±0.1%	±500 ppm	25 ppm/°C	5000 V				2 bp's + gnd + guard	
20 GΩ	SRL-20G	±0.1%	±500 ppm	25 ppm/°C	5000 V				2 bp's + gnd + guard	
100 GΩ	SRL-100G	±0.3%	±500 ppm	25 ppm/°C	5000 V				2 bp's + gnd + guard	
190 GΩ	SRL-190G	±0.3%	±500 ppm	25 ppm/°C	5000 V				2 bp's + gnd + guard	
200 GΩ	SRL-200G	±0.3%	±500 ppm	25 ppm/°C	5000 V				2 bp's + gnd + guard	
1 TΩ	SRL-1T	±0.5%	±500 ppm	50 ppm/°C	5000 V			2 bp's + gnd + guard		
1.9 TΩ	SRL-1.9T	±0.7%	±1000 ppm	100 ppm/°C	5000 V			2 bp's + gnd + guard		
2 TΩ	SRL-2T	±0.7%	±1000 ppm	100 ppm/°C	5000 V			2 bp's + gnd + guard		
XXX Ω	SRL-XXX	customer-selected value and power specifications								

\* negligible effect of self-heating; do not exceed voltage limits where given.

\*\* non-permanent self-heating change; exceeding this value may cause a permanent change in the resistance..

† Maximum dissipation: in air - 1 W; in oil - 4 W

### ORDERING INFORMATION

Standard model Select from table above  
 Custom value SRL-XXX  
 DMM direct plug-in Add -DMM at the end of part number  
 Transit case for SRL units SRC-100, for 2 units  
 SRC-10-n, for n units

#### -N Option

Dual N-type terminal connections with ground terminal to fully shielded metal case. Inner enclosure can be separately driven with guard voltage.



IET LABS, INC. in the GenRad Tradition

www.ietlabs.com  
 TEL: (516) 334-5959 • EMAIL: info@ietlabs.com

### TRANSIT CASES

Optional **Model SRC-100** or **SRC-10-n** lightweight transit cases provides mechanical protection and insulation from temperature

changes during transportation or shipping. It is suitable for transporting and storing two or more units.



*SRC-100 Transit Case  
for 2 units*



*SRC-10-n Transit Case  
for n units (5 units shown)*



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Component Testers](#) category:*

*Click to view products by [IET LABS](#) manufacturer:*

Other Similar products are found below :

[410-413](#) [FLUKE 9062](#) [2840](#) [2841](#) [570A](#) [35135](#) [C.A 6608](#) [C.A 6609](#) [815](#) [FLUKE-9040EUR](#) [881](#) [895](#) [880-220V](#) [894](#) [AK57X](#) [770734](#)  
[LCR200](#) [PRT200](#) [UM200](#) [T5-H5-1AC-KIT/US](#) [VT-1100](#) [69127](#) [ET40](#) [ET45](#) [ET45VP](#) [ET60](#) [HVNCVT-1](#) [NCVT2P](#) [NCVT2PKIT](#)  
[NCVT3P](#) [NCVT-6](#) [RT110](#) [RT210](#) [RT250](#) [RT310](#) [35100](#) [35130](#) [VS-AVT-C02-L03](#) [1212598](#) [PRM-5](#) [T3LCR1002](#) [T3LCR1300](#)  
[T3LCR1100](#) [VS-AVT-RKBB2](#) [VS-AVT-RKBB3](#) [VS-AVT-RKBB4](#) [NCVT-4IR](#) [LCR55A](#) [ET30B](#) [ET40B](#)