

## Final datasheet

### EasyPACK™ 2B module with TRENCHSTOP™ 5 H5 and CoolSiC™ Schottky diode and PressFIT / NTC

#### Features

- Electrical features
  - $V_{CES} = 650 \text{ V}$
  - $I_{C\text{ nom}} = 40 \text{ A} / I_{CRM} = 80 \text{ A}$
  - CoolSiC™ Schottky diode gen 5
  - Low switching losses
  - Increased blocking voltage capability up to 650 V
  - Suitable Infineon gate drivers can be found under <https://www.infineon.com/gdfinder>
- Mechanical features
  - Rugged mounting due to integrated mounting clamps
  - AlN substrate with low thermal resistance
  - Compact design
  - PressFIT contact technology



Typical appearance


#### Potential applications

- Three-level applications
- UPS systems
- Solar applications
- Motor drives

#### Product validation

- Qualified for industrial applications according to the relevant tests of IEC 60747, 60749 and 60068

#### Description



## Table of contents

<b>Description</b> .....	1
<b>Features</b> .....	1
<b>Potential applications</b> .....	1
<b>Product validation</b> .....	1
<b>Table of contents</b> .....	2
<b>1 Package</b> .....	3
<b>2 IGBT, Inverter</b> .....	3
<b>3 Diode, Inverter</b> .....	5
<b>4 IGBT, 3-Level</b> .....	6
<b>5 Diode, 3-Level</b> .....	7
<b>6 NTC-Thermistor</b> .....	8
<b>7 Characteristics diagrams</b> .....	9
<b>8 Circuit diagram</b> .....	17
<b>9 Package outlines</b> .....	18
<b>10 Module label code</b> .....	19
<b>Revision history</b> .....	20
<b>Disclaimer</b> .....	21

## 1 Package

**Table 1 Insulation coordination**

Parameter	Symbol	Note or test condition	Values	Unit
Isolation test voltage	$V_{ISOL}$	RMS, $f = 50 \text{ Hz}$ , $t = 60 \text{ s}$	3.0	kV
Isolation test voltage NTC	$V_{ISOL(NTC)}$	RMS, $f = 50 \text{ Hz}$ , $t = 60 \text{ s}$	3.0	kV
Internal isolation		basic insulation (class 1, IEC 61140)	AIN	
Comparative tracking index	$CTI$		> 200	
Relative thermal index (electrical)	$RTI$	housing	140	°C

**Table 2 Characteristic values**

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Stray inductance module	$L_{SCE}$			36		nH
Module lead resistance, terminals - chip	$R_{CC'+EE'}$	$T_H = 25 \text{ °C}$ , per switch		8.2		mΩ
Storage temperature	$T_{stg}$		-40		125	°C
Mounting force per clamp	$F$		40		80	N
Weight	$G$			42		g

**Note:** The current under continuous operation is limited to 25A rms per connector pin

## 2 IGBT, Inverter

**Table 3 Maximum rated values**

Parameter	Symbol	Note or test condition		Values	Unit
Collector-emitter voltage	$V_{CES}$		$T_{vj} = 25 \text{ °C}$	650	V
Implemented collector current	$I_{CN}$			40	A
Continuous DC collector current	$I_{CDC}$	$T_{vj\ max} = 175 \text{ °C}$	$T_H = 115 \text{ °C}$	20	A
Repetitive peak collector current	$I_{CRM}$	$t_p$ limited by $T_{vj\ op}$		80	A
Gate-emitter peak voltage	$V_{GES}$			±20	V

**Table 4 Characteristic values**

<b>Parameter</b>	<b>Symbol</b>	<b>Note or test condition</b>	<b>Values</b>			<b>Unit</b>
			<b>Min.</b>	<b>Typ.</b>	<b>Max.</b>	
Collector-emitter saturation voltage	$V_{CE\text{ sat}}$	$I_C = 20 \text{ A}, V_{GE} = 15 \text{ V}$	$T_{vj} = 25^\circ\text{C}$		1.32	1.81
			$T_{vj} = 125^\circ\text{C}$		1.39	
			$T_{vj} = 150^\circ\text{C}$		1.41	
Gate threshold voltage	$V_{GE\text{th}}$	$I_C = 0.35 \text{ mA}, V_{CE} = V_{GE}, T_{vj} = 25^\circ\text{C}$		3.85	4.60	5.35
Gate charge	$Q_G$	$V_{GE} = \pm 15 \text{ V}, V_{CC} = 300 \text{ V}$			0.152	
Internal gate resistor	$R_{G\text{int}}$	$T_{vj} = 25^\circ\text{C}$			0	$\Omega$
Input capacitance	$C_{ies}$	$f = 100 \text{ kHz}, T_{vj} = 25^\circ\text{C}, V_{CE} = 25 \text{ V}, V_{GE} = 0 \text{ V}$			1.94	$\text{nF}$
Reverse transfer capacitance	$C_{res}$	$f = 100 \text{ kHz}, T_{vj} = 25^\circ\text{C}, V_{CE} = 25 \text{ V}, V_{GE} = 0 \text{ V}$			0.007	$\text{nF}$
Collector-emitter cut-off current	$I_{CES}$	$V_{CE} = 650 \text{ V}, V_{GE} = 0 \text{ V}$	$T_{vj} = 25^\circ\text{C}$			0.018
Gate-emitter leakage current	$I_{GES}$	$V_{CE} = 0 \text{ V}, V_{GE} = 20 \text{ V}, T_{vj} = 25^\circ\text{C}$				100
Turn-on delay time (inductive load)	$t_{don}$	$I_C = 20 \text{ A}, V_{CC} = 300 \text{ V}, V_{GE} = \pm 15 \text{ V}, R_{Gon} = 7.5 \Omega$	$T_{vj} = 25^\circ\text{C}$		0.011	
			$T_{vj} = 125^\circ\text{C}$		0.012	
			$T_{vj} = 150^\circ\text{C}$		0.012	
Rise time (inductive load)	$t_r$	$I_C = 20 \text{ A}, V_{CC} = 300 \text{ V}, V_{GE} = \pm 15 \text{ V}, R_{Gon} = 7.5 \Omega$	$T_{vj} = 25^\circ\text{C}$		0.009	
			$T_{vj} = 125^\circ\text{C}$		0.014	
			$T_{vj} = 150^\circ\text{C}$		0.015	
Turn-off delay time (inductive load)	$t_{doff}$	$I_C = 20 \text{ A}, V_{CC} = 300 \text{ V}, V_{GE} = \pm 15 \text{ V}, R_{Goff} = 7.5 \Omega$	$T_{vj} = 25^\circ\text{C}$		0.078	
			$T_{vj} = 125^\circ\text{C}$		0.099	
			$T_{vj} = 150^\circ\text{C}$		0.105	
Fall time (inductive load)	$t_f$	$I_C = 20 \text{ A}, V_{CC} = 300 \text{ V}, V_{GE} = \pm 15 \text{ V}, R_{Goff} = 7.5 \Omega$	$T_{vj} = 25^\circ\text{C}$		0.018	
			$T_{vj} = 125^\circ\text{C}$		0.029	
			$T_{vj} = 150^\circ\text{C}$		0.046	
Turn-on energy loss per pulse	$E_{on}$	$I_C = 20 \text{ A}, V_{CC} = 300 \text{ V}, L_\sigma = 35 \text{ nH}, V_{GE} = \pm 15 \text{ V}, R_{Gon} = 7.5 \Omega, di/dt = 1100 \text{ A}/\mu\text{s} (T_{vj} = 150^\circ\text{C})$	$T_{vj} = 25^\circ\text{C}$		0.17	
			$T_{vj} = 125^\circ\text{C}$		0.2	
			$T_{vj} = 150^\circ\text{C}$		0.21	
Turn-off energy loss per pulse	$E_{off}$	$I_C = 20 \text{ A}, V_{CC} = 300 \text{ V}, L_\sigma = 35 \text{ nH}, V_{GE} = \pm 15 \text{ V}, R_{Goff} = 7.5 \Omega, dv/dt = 6250 \text{ V}/\mu\text{s} (T_{vj} = 150^\circ\text{C})$	$T_{vj} = 25^\circ\text{C}$		0.1	
			$T_{vj} = 125^\circ\text{C}$		0.2	
			$T_{vj} = 150^\circ\text{C}$		0.22	
Thermal resistance, junction to heat sink	$R_{thJH}$	per IGBT, $\lambda_{\text{grease}} = 1 \text{ W}/(\text{m}\cdot\text{K})$			1.36	

**(table continues...)**

**Table 4 (continued) Characteristic values**

<b>Parameter</b>	<b>Symbol</b>	<b>Note or test condition</b>	<b>Values</b>			<b>Unit</b>
			<b>Min.</b>	<b>Typ.</b>	<b>Max.</b>	
Temperature under switching conditions	$T_{vj\ op}$		-40		150	°C

### 3 Diode, Inverter

**Table 5 Maximum rated values**

<b>Parameter</b>	<b>Symbol</b>	<b>Note or test condition</b>		<b>Values</b>		<b>Unit</b>
Repetitive peak reverse voltage	$V_{RRM}$		$T_{vj} = 25 \text{ }^\circ\text{C}$	650		V
Implemented forward current	$I_{FN}$			25		A
Continuous DC forward current	$I_F$			20		A
Repetitive peak forward current	$I_{FRM}$	$t_P = 1 \text{ ms}$		50		A
$I^2t$ - value	$I^2t$	$t_P = 10 \text{ ms}, V_R = 0 \text{ V}$	$T_{vj} = 125 \text{ }^\circ\text{C}$	55		$\text{A}^2\text{s}$
			$T_{vj} = 150 \text{ }^\circ\text{C}$	50		

**Table 6 Characteristic values**

<b>Parameter</b>	<b>Symbol</b>	<b>Note or test condition</b>	<b>Values</b>			<b>Unit</b>
			<b>Min.</b>	<b>Typ.</b>	<b>Max.</b>	
Forward voltage	$V_F$	$I_F = 20 \text{ A}, V_{GE} = 0 \text{ V}$	$T_{vj} = 25 \text{ }^\circ\text{C}$	1.65	2.15	V
			$T_{vj} = 125 \text{ }^\circ\text{C}$	1.55		
			$T_{vj} = 150 \text{ }^\circ\text{C}$	1.50		
Peak reverse recovery current	$I_{RM}$	$V_{CC} = 300 \text{ V}, I_F = 20 \text{ A}, V_{GE} = -15 \text{ V}, -di_F/dt = 1100 \text{ A}/\mu\text{s} (T_{vj} = 150 \text{ }^\circ\text{C})$	$T_{vj} = 25 \text{ }^\circ\text{C}$	14		A
			$T_{vj} = 125 \text{ }^\circ\text{C}$	18		
			$T_{vj} = 150 \text{ }^\circ\text{C}$	20		
Recovered charge	$Q_r$	$V_{CC} = 300 \text{ V}, I_F = 20 \text{ A}, V_{GE} = -15 \text{ V}, -di_F/dt = 1100 \text{ A}/\mu\text{s} (T_{vj} = 150 \text{ }^\circ\text{C})$	$T_{vj} = 25 \text{ }^\circ\text{C}$	0.77		$\mu\text{C}$
			$T_{vj} = 125 \text{ }^\circ\text{C}$	1.2		
			$T_{vj} = 150 \text{ }^\circ\text{C}$	1.44		
Reverse recovery energy	$E_{rec}$	$V_{CC} = 300 \text{ V}, I_F = 20 \text{ A}, V_{GE} = -15 \text{ V}, -di_F/dt = 1100 \text{ A}/\mu\text{s} (T_{vj} = 150 \text{ }^\circ\text{C})$	$T_{vj} = 25 \text{ }^\circ\text{C}$	0.16		$\text{mJ}$
			$T_{vj} = 125 \text{ }^\circ\text{C}$	0.22		
			$T_{vj} = 150 \text{ }^\circ\text{C}$	0.27		
Thermal resistance, junction to heat sink	$R_{thJH}$	per diode, $\lambda_{grease} = 1 \text{ W}/(\text{m}\cdot\text{K})$		1.78		K/W

(table continues...)

**Table 6 (continued) Characteristic values**

<b>Parameter</b>	<b>Symbol</b>	<b>Note or test condition</b>	<b>Values</b>			<b>Unit</b>
			<b>Min.</b>	<b>Typ.</b>	<b>Max.</b>	
Temperature under switching conditions	$T_{vj\ op}$		-40		150	°C

## 4 IGBT, 3-Level

**Table 7 Maximum rated values**

<b>Parameter</b>	<b>Symbol</b>	<b>Note or test condition</b>		<b>Values</b>		<b>Unit</b>
Collector-emitter voltage	$V_{CES}$			650		V
Implemented collector current	$I_{CN}$			40		A
Continuous DC collector current	$I_{CDC}$	$T_{vj\ max} = 175\text{ °C}$	$T_H = 115\text{ °C}$	20		A
Repetitive peak collector current	$I_{CRM}$	$t_p$ limited by $T_{vj\ op}$		80		A
Gate-emitter peak voltage	$V_{GES}$			±20		V

**Table 8 Characteristic values**

<b>Parameter</b>	<b>Symbol</b>	<b>Note or test condition</b>	<b>Values</b>			<b>Unit</b>
			<b>Min.</b>	<b>Typ.</b>	<b>Max.</b>	
Collector-emitter saturation voltage	$V_{CE\ sat}$	$I_C = 20\text{ A}, V_{GE} = 15\text{ V}$	$T_{vj} = 25\text{ °C}$		1.32	1.81
			$T_{vj} = 125\text{ °C}$		1.39	
			$T_{vj} = 150\text{ °C}$		1.41	
Gate threshold voltage	$V_{GE\ th}$	$I_C = 0.35\text{ mA}, V_{CE} = V_{GE}, T_{vj} = 25\text{ °C}$		3.85	4.60	5.35
Gate charge	$Q_G$	$V_{GE} = \pm 15\text{ V}, V_{CC} = 300\text{ V}$			0.152	
Internal gate resistor	$R_{Gint}$	$T_{vj} = 25\text{ °C}$			0	Ω
Input capacitance	$C_{ies}$	$f = 100\text{ kHz}, T_{vj} = 25\text{ °C}, V_{CE} = 25\text{ V}, V_{GE} = 0\text{ V}$			1.94	nF
Reverse transfer capacitance	$C_{res}$	$f = 100\text{ kHz}, T_{vj} = 25\text{ °C}, V_{CE} = 25\text{ V}, V_{GE} = 0\text{ V}$			0.007	nF
Collector-emitter cut-off current	$I_{CES}$	$V_{CE} = 650\text{ V}, V_{GE} = 0\text{ V}$	$T_{vj} = 25\text{ °C}$		0.018	mA
Gate-emitter leakage current	$I_{GES}$	$V_{CE} = 0\text{ V}, V_{GE} = 20\text{ V}, T_{vj} = 25\text{ °C}$			100	nA
Turn-on delay time (inductive load)	$t_{don}$	$I_C = 20\text{ A}, V_{CC} = 300\text{ V}, V_{GE} = \pm 15\text{ V}, R_{Gon} = 3.9\text{ Ω}$	$T_{vj} = 25\text{ °C}$		0.011	
			$T_{vj} = 125\text{ °C}$		0.012	
			$T_{vj} = 150\text{ °C}$		0.012	

(table continues...)

**Table 8 (continued) Characteristic values**

<b>Parameter</b>	<b>Symbol</b>	<b>Note or test condition</b>	<b>Values</b>			<b>Unit</b>
			<b>Min.</b>	<b>Typ.</b>	<b>Max.</b>	
Rise time (inductive load)	$t_r$	$I_C = 20 \text{ A}$ , $V_{CC} = 300 \text{ V}$ , $V_{GE} = \pm 15 \text{ V}$ , $R_{Gon} = 3.9 \Omega$	$T_{vj} = 25^\circ\text{C}$		0.005	$\mu\text{s}$
			$T_{vj} = 125^\circ\text{C}$		0.006	
			$T_{vj} = 150^\circ\text{C}$		0.006	
Turn-off delay time (inductive load)	$t_{doff}$	$I_C = 20 \text{ A}$ , $V_{CC} = 300 \text{ V}$ , $V_{GE} = \pm 15 \text{ V}$ , $R_{Goff} = 3.9 \Omega$	$T_{vj} = 25^\circ\text{C}$		0.069	$\mu\text{s}$
			$T_{vj} = 125^\circ\text{C}$		0.085	
			$T_{vj} = 150^\circ\text{C}$		0.091	
Fall time (inductive load)	$t_f$	$I_C = 20 \text{ A}$ , $V_{CC} = 300 \text{ V}$ , $V_{GE} = \pm 15 \text{ V}$ , $R_{Goff} = 3.9 \Omega$	$T_{vj} = 25^\circ\text{C}$		0.021	$\mu\text{s}$
			$T_{vj} = 125^\circ\text{C}$		0.052	
			$T_{vj} = 150^\circ\text{C}$		0.065	
Turn-on energy loss per pulse	$E_{on}$	$I_C = 20 \text{ A}$ , $V_{CC} = 300 \text{ V}$ , $L_\sigma = 35 \text{ nH}$ , $V_{GE} = \pm 15 \text{ V}$ , $R_{Gon} = 3.9 \Omega$ , $di/dt = 3500 \text{ A}/\mu\text{s}$ ( $T_{vj} = 150^\circ\text{C}$ )	$T_{vj} = 25^\circ\text{C}$		0.08	$\text{mJ}$
			$T_{vj} = 125^\circ\text{C}$		0.09	
			$T_{vj} = 150^\circ\text{C}$		0.09	
Turn-off energy loss per pulse	$E_{off}$	$I_C = 20 \text{ A}$ , $V_{CC} = 300 \text{ V}$ , $L_\sigma = 35 \text{ nH}$ , $V_{GE} = \pm 15 \text{ V}$ , $R_{Goff} = 3.9 \Omega$ , $dv/dt = 6210 \text{ V}/\mu\text{s}$ ( $T_{vj} = 150^\circ\text{C}$ )	$T_{vj} = 25^\circ\text{C}$		0.11	$\text{mJ}$
			$T_{vj} = 125^\circ\text{C}$		0.19	
			$T_{vj} = 150^\circ\text{C}$		0.21	
Thermal resistance, junction to heat sink	$R_{thJH}$	per IGBT, $\lambda_{grease} = 1 \text{ W}/(\text{m}\cdot\text{K})$			1.36	K/W
Temperature under switching conditions	$T_{vj\ op}$		-40		150	°C

## 5 Diode, 3-Level

**Table 9 Maximum rated values**

<b>Parameter</b>	<b>Symbol</b>	<b>Note or test condition</b>		<b>Values</b>		<b>Unit</b>
Repetitive peak reverse voltage	$V_{RRM}$			$T_{vj} = 25^\circ\text{C}$	650	V
Continuous DC forward current	$I_F$				20	A
Repetitive peak forward current	$I_{FRM}$	$t_P = 1 \text{ ms}$			40	A
$I^2t$ - value	$I^2t$	$t_P = 10 \text{ ms}$ , $V_R = 0 \text{ V}$	$T_{vj} = 125^\circ\text{C}$	65	$\text{A}^2\text{s}$	
			$T_{vj} = 150^\circ\text{C}$	65		

**Table 10 Characteristic values**

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Forward voltage	$V_F$	$I_F = 20 \text{ A}, V_{GE} = 0 \text{ V}$	$T_{vj} = 25^\circ\text{C}$		1.45	1.85
			$T_{vj} = 125^\circ\text{C}$		1.60	
			$T_{vj} = 150^\circ\text{C}$		1.65	
Peak reverse recovery current	$I_{RM}$	$V_{CC} = 300 \text{ V}, I_F = 20 \text{ A}, V_{GE} = 15 \text{ V}, -di_F/dt = 3500 \text{ A}/\mu\text{s} (T_{vj} = 150^\circ\text{C})$	$T_{vj} = 25^\circ\text{C}$		19	
			$T_{vj} = 125^\circ\text{C}$		17	
			$T_{vj} = 150^\circ\text{C}$		16	
Recovered charge	$Q_r$	$V_{CC} = 300 \text{ V}, I_F = 20 \text{ A}, V_{GE} = 15 \text{ V}, -di_F/dt = 3500 \text{ A}/\mu\text{s} (T_{vj} = 150^\circ\text{C})$	$T_{vj} = 25^\circ\text{C}$		0.13	
			$T_{vj} = 125^\circ\text{C}$		0.12	
			$T_{vj} = 150^\circ\text{C}$		0.12	
Reverse recovery energy	$E_{rec}$	$V_{CC} = 300 \text{ V}, I_F = 20 \text{ A}, V_{GE} = 15 \text{ V}, -di_F/dt = 3500 \text{ A}/\mu\text{s} (T_{vj} = 150^\circ\text{C})$	$T_{vj} = 25^\circ\text{C}$		0.015	
			$T_{vj} = 125^\circ\text{C}$		0.015	
			$T_{vj} = 150^\circ\text{C}$		0.015	
Thermal resistance, junction to heat sink	$R_{thJH}$	per diode, $\lambda_{grease} = 1 \text{ W}/(\text{m}\cdot\text{K})$			1.92	
Temperature under switching conditions	$T_{vj op}$		-40		150	°C

## 6 NTC-Thermistor

**Table 11 Characteristic values**

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Rated resistance	$R_{25}$	$T_{NTC} = 25^\circ\text{C}$		5		kΩ
Deviation of $R_{100}$	$\Delta R/R$	$T_{NTC} = 100^\circ\text{C}, R_{100} = 493 \Omega$	-5		5	%
Power dissipation	$P_{25}$	$T_{NTC} = 25^\circ\text{C}$			20	mW
B-value	$B_{25/50}$	$R_2 = R_{25} \exp[B_{25/50}(1/T_2 - 1/(298,15 \text{ K}))]$		3375		K
B-value	$B_{25/80}$	$R_2 = R_{25} \exp[B_{25/80}(1/T_2 - 1/(298,15 \text{ K}))]$		3411		K
B-value	$B_{25/100}$	$R_2 = R_{25} \exp[B_{25/100}(1/T_2 - 1/(298,15 \text{ K}))]$		3433		K


**Note:** For an analytical description of the NTC characteristics please refer to AN2009-10, chapter 4.

## 7 Characteristics diagrams

### Output characteristic (typical), IGBT, Inverter

$I_C = f(V_{CE})$


$V_{GE} = 15 \text{ V}$



### Output characteristic field (typical), IGBT, Inverter

$I_C = f(V_{CE})$


$T_{vj} = 150^\circ\text{C}$



### Transfer characteristic (typical), IGBT, Inverter

$I_C = f(V_{GE})$


$V_{CE} = 20 \text{ V}$



### Gate charge characteristic (typical), IGBT, Inverter

$V_{GE} = f(Q_G)$


$I_C = 20 \text{ A}, T_{vj} = 25^\circ\text{C}$



**Capacity characteristic (typical), IGBT, Inverter**


$$C = f(V_{CE})$$

$$f = 100 \text{ kHz}, V_{GE} = 0 \text{ V}, T_{vj} = 25^\circ\text{C}$$

**Switching times (typical), IGBT, Inverter**


$$t = f(I_C)$$

$$R_{Goff} = 7.5 \Omega, R_{Gon} = 7.5 \Omega, V_{CC} = 300 \text{ V}, V_{GE} = -15 / 15 \text{ V}, T_{vj} = 150^\circ\text{C}$$

**Switching times (typical), IGBT, Inverter**


$$t = f(R_G)$$

$$I_C = 20 \text{ A}, V_{CC} = 300 \text{ V}, V_{GE} = -15 / 15 \text{ V}, T_{vj} = 150^\circ\text{C}$$


**Switching losses (typical), IGBT, Inverter**

$$E = f(I_C)$$


$$R_{Goff} = 7.5 \Omega, R_{Gon} = 7.5 \Omega, V_{CC} = 300 \text{ V}, V_{GE} = -15 / 15 \text{ V}$$



7 Characteristics diagrams



7 Characteristics diagrams




7 Characteristics diagrams

**Output characteristic field (typical), IGBT, 3-Level**

$$I_C = f(V_{CE})$$


$$T_{vj} = 150^\circ\text{C}$$



**Transfer characteristic (typical), IGBT, 3-Level**

$$I_C = f(V_{GE})$$


$$V_{CE} = 20\text{ V}$$



**Gate charge characteristic (typical), IGBT, 3-Level**

$$V_{GE} = f(Q_G)$$


$$I_C = 20\text{ A}, T_{vj} = 25^\circ\text{C}$$







**Capacity characteristic (typical), IGBT, 3-Level**

$$C = f(V_{CE})$$

$$f = 100\text{ kHz}, V_{GE} = 0\text{ V}, T_{vj} = 25^\circ\text{C}$$




**Switching times (typical), IGBT, 3-Level** $t = f(I_C)$ 
 $R_{Goff} = 3.9 \Omega$ ,  $R_{Gon} = 3.9 \Omega$ ,  $V_{CC} = 300 \text{ V}$ ,  $V_{GE} = -15 / 15 \text{ V}$ ,  $T_{vj} = 150^\circ\text{C}$ 
**Switching losses (typical), IGBT, 3-Level** $E = f(I_C)$ 
 $R_{Goff} = 3.9 \Omega$ ,  $R_{Gon} = 3.9 \Omega$ ,  $V_{CC} = 300 \text{ V}$ ,  $V_{GE} = -15 / 15 \text{ V}$ 
**Switching times (typical), IGBT, 3-Level** $t = f(R_G)$ 
 $I_C = 20 \text{ A}$ ,  $V_{CC} = 300 \text{ V}$ ,  $V_{GE} = -15 / 15 \text{ V}$ ,  $T_{vj} = 150^\circ\text{C}$ 
**Switching losses (typical), IGBT, 3-Level** $E = f(R_G)$ 
 $I_C = 20 \text{ A}$ ,  $V_{CC} = 300 \text{ V}$ ,  $V_{GE} = -15 / 15 \text{ V}$ 


7 Characteristics diagrams

**Reverse bias safe operating area (RBSOA), IGBT, 3-Level**


$$I_C = f(V_{CE})$$

$$R_{Goff} = 3.9 \Omega, V_{GE} = \pm 15 \text{ V}, T_{vj} = 150^\circ\text{C}$$




**Transient thermal impedance, IGBT, 3-Level**

$$Z_{th} = f(t)$$



**Forward characteristic (typical), Diode, 3-Level**


$$I_F = f(V_F)$$




**Switching losses (typical), Diode, 3-Level**

$$E_{rec} = f(I_F)$$


$$R_{Gon} = 3.9 \Omega, V_{CE} = 300 \text{ V}$$



7 Characteristics diagrams




## 8 Circuit diagram



**Figure 1**

## 9 Package outlines



**Figure 2**

## 10 Module label code


<b>Module label code</b>			
Code format	Data Matrix		Barcode Code128
Encoding	ASCII text		Code Set A
Symbol size	16x16		23 digits
Standard	IEC24720 and IEC16022		IEC8859-1
Code content	<p><i>Content</i></p> <p>Module serial number Module material number Production order number Date code (production year) Date code (production week)</p>	<p><i>Digit</i></p> <p>1 – 5 6 - 11 12 - 19 20 – 21 22 – 23</p>	<p><i>Example</i></p> <p>71549 142846 55054991 15 30</p>
Example			71549142846550549911530

Figure 3

## Revision history

<b>Document revision</b>	<b>Date of release</b>	<b>Description of changes</b>
0.10	2023-10-04	Initial version
1.00	2024-04-09	Final datasheet

## **Trademarks**

All referenced product or service names and trademarks are the property of their respective owners.

**Edition 2024-04-09**

**Published by**

**Infineon Technologies AG  
81726 Munich, Germany**

**© 2024 Infineon Technologies AG  
All Rights Reserved.**

**Do you have a question about any aspect of this document?**

**Email: [erratum@infineon.com](mailto:erratum@infineon.com)**

**Document reference  
IFX-ABH459-002**

## **Important notice**

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenheitsgarantie").

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

## **Warnings**

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.

# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for IGBT Modules category:***

***Click to view products by Infineon manufacturer:***

Other Similar products are found below :

[F3L400R07ME4\\_B22](#) [F3L400R12PT4\\_B26](#) [FB20R06W1E3\\_B11](#) [FD300R12KE3](#) [FD300R12KS4\\_B5](#) [FD400R12KE3](#) [FF100R12KS4](#)  
[FF150R12KE3G](#) [FF200R06KE3](#) [FF200R06YE3](#) [FF300R06KE3\\_B2](#) [FF600R12IP4V](#) [FF800R17KP4\\_B2](#) [FF900R12IE4V](#)  
[FP06R12W1T4\\_B3](#) [FP100R07N3E4](#) [FP100R07N3E4\\_B11](#) [FP10R06W1E3\\_B11](#) [FP10R12W1T4\\_B11](#) [FP10R12YT3](#) [FP15R12W2T4](#)  
[FP15R12YT3](#) [FP20R06W1E3](#) [FP30R06W1E3](#) [FP40R12KT3G](#) [FP75R06KE3](#) [FS10R12YE3](#) [FS150R07PE4](#) [FS150R12PT4](#)  
[FS150R17N3E4\\_B11](#) [FS20R06W1E3\\_B11](#) [FS30R06W1E3\\_B11](#) [FS75R12KE3G](#) [FS75R12W2T4\\_B11](#) [FZ1600R17HP4\\_B2](#)  
[FZ300R12KE3G](#) [FZ400R17KE3](#) [FZ400R17KE4](#) [FZ600R65KE3](#) [DF1000R17IE4D\\_B2](#) [APTGT75DA60T1G](#) [DZ800S17K3](#) [F12-](#)  
[25R12KT4G](#) [F3L200R12W2H3\\_B11](#) [F3L300R12ME4\\_B22](#) [F3L75R07W2E3\\_B11](#) [F4-150R12KS4](#) [F475R07W1H3B11ABOMA1](#)  
[FD1400R12IP4D](#) [FD400R12KE3\\_B5](#)