

Automotive MOSFET

OptiMOS™ 6 Power-Transistor



Features



- OptiMOS™ power MOSFET for automotive applications
- N-channel – Enhancement mode – Normal Level
- Extended qualification beyond AEC-Q101
- Enhanced electrical testing
- Robust design
- MSL1 up to 260°C peak reflow
- 175°C operating temperature
- RoHS compliant
- 100% Avalanche tested
- Top Side Cooling

Potential applications

General automotive applications.

Product validation

Qualified for automotive applications. Product validation according to AEC-Q101.



Product Summary

| | | |
|----------------------|------|----|
| V_{DS} | 40 | V |
| $R_{DS(on)}$ | 0.75 | mΩ |
| I_D (chip limited) | 390 | A |

| Type | Package | Marking |
|----------------|---------------|---------|
| IAUCN04S6N007T | PG-LHDSO-10-3 | 6A4 |

Table of Contents

| | |
|---|----|
| Description | 1 |
| Maximum ratings | 3 |
| Thermal characteristics | 4 |
| Electrical characteristics | 4 |
| Electrical characteristics diagrams | 6 |
| Package outline & footprint | 10 |
| Revision history | 11 |
| Disclaimer | 12 |

Maximum ratings

at $T_j=25\text{ °C}$, unless otherwise specified

| Parameter | Symbol | Conditions | Value | Unit |
|--|----------------|--|--------------|------|
| Continuous drain current | I_D | $V_{GS}=10\text{ V}$, Chip limitation ^{1,2)} | 390 | A |
| | | $V_{GS}=10\text{V}$, DC current | 120 | |
| | | $T_a=85\text{ °C}$, $V_{GS}=10\text{ V}$, R_{thJH} on $2s2p$ ^{2,4)} | 95 | |
| Pulsed drain current ²⁾ | $I_{D,pulse}$ | $T_C=25\text{ °C}$, $t_p=100\text{ }\mu\text{s}$ | 1300 | |
| Avalanche energy, single pulse ²⁾ | E_{AS} | $I_D=60\text{ A}$ | 624 | mJ |
| Avalanche current, single pulse | I_{AS} | – | 115 | A |
| Gate source voltage | V_{GS} | – | ± 20 | V |
| Power dissipation | P_{tot} | $T_C=25\text{ °C}$ | 206 | W |
| Operating and storage temperature | T_j, T_{stg} | – | -55 ... +175 | °C |

Thermal characteristics²⁾

| Parameter | Symbol | Conditions | Values | | | Unit |
|--|-----------------|------------|--------|------|------|------|
| | | | min. | typ. | max. | |
| Thermal resistance, junction - case | R_{thJC} | – | – | 0.36 | 0.73 | K/W |
| Thermal characterization parameter, source pin ⁵⁾ | Ψ_{source} | | – | 5.3 | – | |
| Thermal characterization parameter, drain pin ⁶⁾ | Ψ_{drain} | | – | 5.4 | – | |
| Thermal resistance, junction - heatsink ⁴⁾ | R_{thJH} | | – | 6.8 | – | |
| Thermal resistance, junction - ambient ³⁾ | R_{thJA} | – | – | 45 | – | |

Electrical characteristics

at $T_j=25\text{ °C}$, unless otherwise specified

| Parameter | Symbol | Conditions | Values | | | Unit |
|-----------|--------|------------|--------|------|------|------|
| | | | min. | typ. | max. | |

Static characteristics

| | | | | | | |
|----------------------------------|---------------|--|-----|------|------|---------------|
| Drain-source breakdown voltage | $V_{(Br)DSS}$ | $V_{GS}=0\text{ V}$, $I_D=1\text{ mA}$ | 40 | – | – | V |
| Gate threshold voltage | $V_{GS(th)}$ | $V_{DS}=V_{GS}$, $I_D=120\text{ }\mu\text{A}$ | 2.2 | 2.6 | 3.0 | |
| Zero gate voltage drain current | I_{DSS} | $V_{DS}=40\text{ V}$, $V_{GS}=0\text{ V}$, $T_j=25\text{ °C}$ | – | – | 1 | μA |
| | | $V_{DS}=40\text{ V}$, $V_{GS}=0\text{ V}$, $T_j=125\text{ °C}^{2)}$ | – | – | 30 | |
| Gate-source leakage current | I_{GSS} | $V_{GS}=20\text{ V}$, $V_{DS}=0\text{ V}$ | – | – | 100 | nA |
| Drain-source on-state resistance | $R_{DS(on)}$ | $V_{GS}=7\text{ V}$, $I_D=60\text{ A}$ | – | 0.81 | 0.95 | m Ω |
| | | $V_{GS}=10\text{ V}$, $I_D=60\text{ A}$ | – | 0.68 | 0.75 | |
| Gate resistance ²⁾ | R_G | – | – | 0.97 | – | Ω |

| Parameter | Symbol | Conditions | Values | | | Unit |
|---|--------------|--|--------|------|------|------|
| | | | min. | typ. | max. | |
| Dynamic characteristics²⁾ | | | | | | |
| Input capacitance | C_{iss} | $V_{GS}=0\text{ V}, V_{DS}=25\text{ V}, f=1\text{ MHz}$ | - | 6950 | 9035 | pF |
| Output capacitance | C_{oss} | | - | 2100 | 2730 | |
| Reverse transfer capacitance | C_{rss} | | - | 98 | 147 | |
| Turn-on delay time | $t_{d(on)}$ | $V_{DD}=20\text{ V}, V_{GS}=10\text{ V},$ $I_D=120\text{ A}, R_G=3.5\ \Omega$ | - | 12 | - | ns |
| Rise time | t_r | | - | 7 | - | |
| Turn-off delay time | $t_{d(off)}$ | | - | 33 | - | |
| Fall time | t_f | | - | 15 | - | |

Gate Charge Characteristics²⁾

| | | | | | | |
|-----------------------|---------------|---|---|-----|-----|----|
| Gate to source charge | Q_{gs} | $V_{DD}=32\text{ V}, I_D=120\text{ A},$ $V_{GS}=0\text{ to }10\text{ V}$ | - | 26 | 34 | nC |
| Gate to drain charge | Q_{gd} | | - | 19 | 29 | |
| Gate charge total | Q_g | | - | 100 | 130 | |
| Gate plateau voltage | $V_{plateau}$ | | - | 3.9 | - | V |

Reverse Diode

| | | | | | | |
|--|---------------|---|---|-----|------|----|
| Diode continuous forward current ²⁾ | I_S | $T_C=25\text{ }^\circ\text{C}$ | - | - | 120 | A |
| Diode pulse current ²⁾ | $I_{S,pulse}$ | $T_C=25\text{ }^\circ\text{C}, t_p=100\ \mu\text{s}$ | - | - | 1300 | |
| Diode forward voltage | V_{SD} | $V_{GS}=0\text{ V}, I_F=60\text{ A}, T_j=25\text{ }^\circ\text{C}$ | - | 0.8 | 1.1 | V |
| Reverse recovery time ²⁾ | t_{rr} | $V_R=20\text{ V}, I_F=50\text{ A},$ $di_F/dt=100\text{ A}/\mu\text{s}$ | - | 46 | - | ns |
| Reverse recovery charge ²⁾ | Q_{rr} | | - | 42 | - | nC |

¹⁾ Practically the current is limited by the overall system design including the customer-specific PCB.

²⁾ The parameter is not subject to production testing – specified by design.

³⁾ Device on 2s2p FR4 PCB defined in accordance with JEDEC standards (JESD51-5, -7) without thermal vias. PCB is vertical in still air.


⁴⁾ Device on 2s2p FR4 PCB defined in accordance with JEDEC standards (JESD51-5, -7) without thermal vias, heatsink of 71x110x2 mm is attached through TIM with 3.3 W/(m*K) and 400µm thickness to top side pad. Heatsink fixed to 85°C ambient temperature.

⁵⁾ Thermal characterization parameter, calculated as $\psi_{source} = (T_{source} - T_{ambient})/P_{dis}$ in condition of 4). Used to determine PCB temperature at source pins for given power.


⁶⁾ Thermal characterization parameter, calculated as $\psi_{drain} = (T_{drain} - T_{ambient})/P_{dis}$ in condition of 4). Used to determine PCB temperature at drain pins for given power.

Electrical characteristics diagrams


1 Power dissipation




2 Drain current




3 Safe operating area




4 Max. transient thermal impedance




5 Typ. output characteristics




6 Typ. drain-source on-state resistance




7 Typ. transfer characteristics




8 Typ. drain-source on-state resistance




9 Typ. gate threshold voltage




10 Typ. capacitances




11 Typical forward diode characteristics




12 Typ. avalanche characteristics




13 Typical avalanche energy




14 Drain-source breakdown voltage




15 Typ. gate charge



16 Gate charge waveforms




Package Outline




<https://www.infineon.com/cms/en/product/packages/PG-LHDSO/PG-LHDSO-10-3>

Footprint



Packaging



all dimensions in mm



Revision History

| Revision | Date | Changes |
|-----------------|-------------|------------------|
| Revision 1.1 | 10.08.2023 | Final data sheet |

Trademarks

All referenced product or service names and trademarks are the property of their respective owners.

Edition 2023-08-10

Published by

Infineon Technologies AG

81726 Munich, Germany

© 2023 Infineon Technologies AG

All Rights Reserved.

Do you have any questions about any aspect of this document?

Email: erratum@infineon.com

Document reference

IAUCN04S6N007T-Data-Sheet-11-Infineon

IMPORTANT NOTICE

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenheitsgarantie").

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications. The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (www.infineon.com).

WARNINGS

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact the nearest Infineon Technologies Office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Infineon manufacturer](#):

Other Similar products are found below :

[0209085P001](#) [10TQ045](#) [111-4189PBF](#) [111-4190PBF](#) [16-1870-01](#) [16RIA80](#) [1EBN1001AEXUMA1](#) [1ED020I12-B2](#) [1ED020I12B2XUMA1](#)
[1ED020I12-BT](#) [1ED020I12BTXUMA1](#) [1ED020I12-F](#) [1ED020I12-F2](#) [1ED020I12F2XUMA1](#) [1ED020I12FA2](#) [1ED020I12FA2XUMA2](#)
[1ED020I12-FT](#) [1ED020I12FTA](#) [1ED020I12FTAXUMA2](#) [1ED3120MU12HXUMA1](#) [1ED3121MU12HXUMA1](#) [1ED3122MC12HXUMA1](#)
[1ED3122MU12HXUMA1](#) [1ED3123MC12HXUMA1](#) [1ED3123MU12HXUMA1](#) [1ED3124MC12HXUMA1](#) [1ED3124MU12HXUMA1](#)
[1ED3131MU12HXUMA1](#) [1ED3140MU12FXUMA1](#) [1ED3141MU12FXUMA1](#) [1ED3142MU12FXUMA1](#) [1ED3241MC12HXUMA1](#)
[1ED3321MC12NXUMA1](#) [1ED3323MC12NXUMA1](#) [1ED3431MU12MXUMA1](#) [1ED3461MU12MXUMA1](#) [1ED3491MC12MXUMA1](#)
[1ED3491MU12MXUMA1](#) [1ED3860MU12MXUMA1](#) [1ED3890MU12MXUMA1](#) [1ED44173N01BXTSA1](#) [1ED44175N01BXTSA1](#)
[1ED44176N01FXUMA1](#) [1EDB7275F](#) [1EDB7275FXUMA1](#) [1EDB8275FXUMA1](#) [1EDB9275FXUMA1](#) [1EDC05I12AHXUMA1](#)
[1EDC10I12MHXUMA1](#) [1EDC20H12AH](#)