


3rd Generation thinQ!TM SiC Schottky Diode

Features

- Revolutionary semiconductor material - Silicon Carbide
- Switching behavior benchmark
- No reverse recovery / No forward recovery
- Temperature independent switching behavior
- High surge current capability
- Pb-free lead plating; RoHS compliant
- Qualified according to JEDEC¹⁾ for target applications
- Breakdown voltage tested at 20mA²⁾
- Optimized for high temperature operation
- Lowest Figure of Merit Q_C/I_F

Product Summary

| | | |
|----------------------------|-----|----|
| V_{DC} | 600 | V |
| Q_C | 16 | nC |
| $I_F; T_C < 130\text{ °C}$ | 10 | A |

PG-TO220-2


thinQ! 3G Diode designed for fast switching applications like:

- SMPS e.g.; CCM PFC
- Motor Drives; Solar Applications; UPS

| Type | Package | Marking | Pin 1 | Pin 2 |
|------------|------------|---------|-------|-------|
| IDH10SG60C | PG-TO220-2 | D10G60C | C | A |

Maximum ratings

| Parameter | Symbol | Conditions | Value | Unit |
|--|----------------|---|-------------|------------------|
| Continuous forward current | I_F | $T_C < 130\text{ °C}$ | 10 | A |
| Surge non-repetitive forward current, sine halfwave | $I_{F,SM}$ | $T_C = 25\text{ °C}, t_p = 10\text{ ms}$ | 51 | |
| | | $T_C = 150\text{ °C}, t_p = 10\text{ ms}$ | 44 | |
| Non-repetitive peak forward current | $I_{F,max}$ | $T_C = 25\text{ °C}, t_p = 10\text{ }\mu\text{s}$ | 410 | |
| i^2t value | $\int i^2 dt$ | $T_C = 25\text{ °C}, t_p = 10\text{ ms}$ | 13 | A ² s |
| | | $T_C = 150\text{ °C}, t_p = 10\text{ ms}$ | 10 | |
| Repetitive peak reverse voltage | V_{RRM} | $T_j = 25\text{ °C}$ | 600 | V |
| Diode dv/dt ruggedness | dv/dt | $V_R = 0 \dots 480\text{ V}$ | 50 | V/ns |
| Power dissipation | P_{tot} | $T_C = 25\text{ °C}$ | 120 | W |
| Operating and storage temperature | T_j, T_{stg} | | -55 ... 175 | °C |
| Soldering temperature, wavesoldering only allowed at leads | T_{sold} | 1.6mm (0.063 in.) from case for 10s | 260 | |
| Mounting torque | | M3 and M3.5 screws | 60 | Ncm |

| Parameter | Symbol | Conditions | Values | | | Unit |
|-----------|--------|------------|--------|------|------|------|
| | | | min. | typ. | max. | |

Thermal characteristics

| | | | | | | |
|--|------------|---|---|---|------|-----|
| Thermal resistance, junction - case | R_{thJC} | | - | - | 1.25 | K/W |
| Thermal resistance, junction - ambient | R_{thJA} | Thermal resistance, junction- ambient, leaded | - | - | 62 | |

Electrical characteristics, at $T_j=25\text{ °C}$, unless otherwise specified
Static characteristics

| | | | | | | |
|-----------------------|----------|---|-----|-----|-----|---------------|
| DC blocking voltage | V_{DC} | $I_R=0.05\text{ mA}$, $T_j=25\text{ °C}$ | 600 | - | - | V |
| Diode forward voltage | V_F | $I_F=10\text{ A}$, $T_j=25\text{ °C}$ | - | 1.8 | 2.1 | |
| | | $I_F=10\text{ A}$, $T_j=150\text{ °C}$ | - | 2.2 | - | |
| Reverse current | I_R | $V_R=600\text{ V}$, $T_j=25\text{ °C}$ | - | 0.8 | 90 | μA |
| | | $V_R=600\text{ V}$, $T_j=150\text{ °C}$ | - | 3.3 | 860 | |

AC characteristics

| | | | | | | |
|------------------------------|-------|---|---|-----|-----|---------------|
| Total capacitive charge | Q_c | $V_R=400\text{ V}$, $I_F \leq I_{F,max}$, $di_F/dt=200\text{ A}/\mu\text{s}$, | - | 16 | - | nC |
| Switching time ³⁾ | t_c | $T_j=150\text{ °C}$ | - | - | <10 | |
| Total capacitance | C | $V_R=1\text{ V}$, $f=1\text{ MHz}$ | - | 290 | - | μF |
| | | $V_R=300\text{ V}$, $f=1\text{ MHz}$ | - | 40 | - | |
| | | $V_R=600\text{ V}$, $f=1\text{ MHz}$ | - | 40 | - | |

¹⁾ J-STD20 and JESD22

²⁾ All devices tested under avalanche conditions, for a time periode of 10ms, at 20mA.


³⁾ t_c is the time constant for the capacitive displacement current waveform (independent from T_j , I_{LOAD} and di/dt), different from t_{rr} which is dependent on T_j , I_{LOAD} and di/dt . No reverse recovery time constant t_{rr} due to absence of minority carrier injection.

⁴⁾ Under worst case Z_{th} conditions.

⁵⁾ Only capacitive charge occuring, guaranteed by design.


1 Power dissipation

$P_{tot}=f(T_C)$; parameter: $R_{thJC(max)}$




2 Diode forward current

$I_F=f(T_C)^4$; $T_j \leq 175\text{ °C}$; parameter: $D = t_p/T$




3 Typ. forward characteristic

$I_F=f(V_F)$; $t_p=400\text{ }\mu\text{s}$; parameter: T_j




4 Typ. forward characteristic in surge current mode

$I_F=f(V_F)$; $t_p=400\text{ }\mu\text{s}$; parameter: T_j




5 Typ. capacitance charge vs. current slope

$$Q_C = f(di_F/dt)^5; I_F \leq I_{F,max}$$




6 Typ. reverse current vs. reverse voltage

$$I_R = f(V_R); \text{ parameter: } T_j$$




7 Typ. transient thermal impedance

$$Z_{thJC} = f(t_p); \text{ parameter: } D = t_p/T$$




8 Typ. capacitance vs. reverse voltage

$$C = f(V_R); T_C = 25 \text{ °C}, f = 1 \text{ MHz}$$




9 Typ. C stored energy

$$E_C=f(V_R)$$



PG-T0220-2: Outline



Dimensions in mm/inches

Published by
Infineon Technologies AG
81726 Munich, Germany
© 2012 Infineon Technologies AG
All Rights Reserved.

Legal Disclaimer

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information

For further information on technology, delivery terms and conditions and prices, please [contact the nearest Infineon Technologies Office \(www.infineon.com\)](http://www.infineon.com).

Warnings

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office. Infineon Technologies components may be used in life-support devices or systems and/or automotive, aviation and aerospace applications or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support, automotive, aviation and aerospace device or system or to affect the safety or effectiveness of that device or system. Life support systems are intended to be implanted in the human body and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Schottky Diodes & Rectifiers](#) category:

Click to view products by [Infineon](#) manufacturer:

Other Similar products are found below :

[CUS06\(TE85L,Q,M\)](#) [MA4E2039](#) [D1FH3-5063](#) [MBR0530L-TP](#) [MBR10100CT-BP](#) [MBR30H100MFST1G](#) [MMBD301M3T5G](#) [PMAD1103-LF](#) [RB160M-50TR](#) [RB520S-30](#) [RB551V-30](#) [DD350N18K](#) [DZ435N40K](#) [DZ600N16K](#) [BAS16E6433HTMA1](#) [BAS 3010S-02LRH E6327](#) [BAT 54-02LRH E6327](#) [IDL02G65C5XUMA1](#) [NSR05F40QNXT5G](#) [JANS1N6640](#) [SB07-03C-TB-H](#) [SB1003M3-TL-W](#) [SBAT54CWT1G](#) [SBM30-03-TR-E](#) [SBS818-TL-E](#) [SK32A-LTP](#) [SK33A-TP](#) [SK34A-TP](#) [SK34B-TP](#) [SMD1200PL-TP](#) [ACDBN160-HF](#) [SS3003CH-TL-E](#) [STPS30S45CW](#) [PDS3100Q-7](#) [GA01SHT18](#) [CRS10I30A\(TE85L,QM\)](#) [MA4E2501L-1290](#) [MBR1240MFST1G](#) [MBRB30H30CT-1G](#) [BAS28E6433HTMA1](#) [BAS 70-02L E6327](#) [HSB123JTR-E](#) [VS-STPS40L45CW-N3](#) [DD350N12K](#) [SB007-03C-TB-E](#) [SB10015M-TL-E](#) [SB1003M3-TL-E](#) [SK110-LTP](#) [SK154-TP](#) [SK32A-TP](#)