

IR2125(S) & (PbF)

CURRENT LIMITING SINGLE CHANNEL DRIVER


Features

- Floating channel designed for bootstrap operation
Fully operational to +500V
Tolerant to negative transient voltage
dV/dt immune
- Gate drive supply range from 12 to 18V
- Undervoltage lockout
- Current detection and limiting loop to limit driven power transistor current
- Error lead indicates fault conditions and programs shutdown time
- Output in phase with input
- 2.5V, 5V and 15V input logic compatible
- Also available LEAD-Free


Product Summary

V_{OFFSET}	500V max.
I_O+/-	1A / 2A
V_{OUT}	12 - 18V
V_{CSt}	230 mV
t_{on/off} (typ.)	150 & 150 ns

Packages



8-Lead PDIP




16-Lead SOIC
(Wide Body)

Description

The IR2125(S) is a high voltage, high speed power MOSFET and IGBT driver with over-current limiting protection circuitry. Proprietary HVIC and latch immune CMOS technologies enable ruggedized monolithic construction. Logic inputs are compatible with standard CMOS or LSTTL outputs, down to 2.5V logic. The output driver features a high pulse current buffer stage designed for minimum driver cross-conduction. The protection circuitry detects over-current in the driven power transistor and limits the gate drive voltage. Cycle by cycle shutdown is programmed by an external capacitor which directly controls the time interval between detection of the over-current limiting conditions and latched shutdown. The floating channel can be used to drive an N-channel power MOSFET or IGBT in the high or low side configuration which operates up to 500 volts.

Typical Connection



IR2125(S) & (PbF)

International
IR Rectifier

Absolute Maximum Ratings

Absolute Maximum Ratings indicate sustained limits beyond which damage to the device may occur. All voltage parameters are absolute voltages referenced to COM. The Thermal Resistance and Power Dissipation ratings are measured under board mounted and still air conditions.

Symbol	Definition	Min.	Max.	Units
V_B	High Side Floating Supply Voltage	-0.3	525	V
V_S	High Side Floating Offset Voltage	$V_B - 25$	$V_B + 0.3$	
V_{HO}	High Side Floating Output Voltage	$V_S - 0.3$	$V_B + 0.3$	
V_{CC}	Logic Supply Voltage	-0.3	25	
V_{IN}	Logic Input Voltage	-0.3	$V_{CC} + 0.3$	
V_{ERR}	Error Signal Voltage	-0.3	$V_{CC} + 0.3$	
V_{CS}	Current Sense Voltage	$V_S - 0.3$	$V_B + 0.3$	
dV_S/dt	Allowable Offset Supply Voltage Transient	—	50	V/ns
P_D	Package Power Dissipation @ $T_A \leq +25^\circ\text{C}$ (8 lead PDIP)	—	1.0	W
	(16 lead SOIC)	—	1.25	
R_{thJA}	Thermal Resistance, Junction to Ambient (8 lead PDIP)	—	125	$^\circ\text{C}/\text{W}$
	(16 Lead SOIC)	—	100	
T_J	Junction Temperature	—	150	$^\circ\text{C}$
T_S	Storage Temperature	-55	150	
T_L	Lead Temperature (Soldering, 10 seconds)	—	300	

Recommended Operating Conditions

The Input/Output logic timing diagram is shown in Figure 1. For proper operation the device should be used within the recommended conditions. The V_S offset rating is tested with all supplies biased at 15V differential.

Symbol	Definition	Min.	Max.	Units
V_B	High Side Floating Supply Voltage	$V_S + 12$	$V_S + 18$	V
V_S	High Side Floating Offset Voltage	Note 1	500	
V_{HO}	High Side Floating Output Voltage	V_S	V_B	
V_{CC}	Logic Supply Voltage	0	18	
V_{IN}	Logic Input Voltage	0	V_{CC}	
V_{ERR}	Error Signal Voltage	0	V_{CC}	
V_{CS}	Current Sense Signal Voltage	V_S	V_B	
T_A	Ambient Temperature	-40	125	$^\circ\text{C}$

Note 1: Logic operational for V_S of -5 to +500V. Logic state held for V_S of -5V to $-V_{BS}$. (Please refer to the Design Tip DT97-3 for more details).

Dynamic Electrical Characteristics

V_{BIAS} (V_{CC} , V_{BS}) = 15V, C_L = 3300 pF and T_A = 25°C unless otherwise specified. The dynamic electrical characteristics are measured using the test circuit shown in Figures 3 through 6.

Symbol	Definition	Figure	Min.	Typ.	Max.	Units	Test Conditions
t_{on}	Turn-On Propagation Delay	7	—	170	240	ns	$V_{IN} = 0 \& 5V$ $V_S = 0$ to 600V
t_{off}	Turn-Off Propagation Delay	8	—	200	270		
t_{sd}	ERR Shutdown Propagation Delay	9	—	1.7	2.2	μs	
t_r	Turn-On Rise Time	10	—	43	60		
t_f	Turn-Off Fall Time	11	—	26	35	μs	
t_{cs}	CS Shutdown Propagation Delay	12	—	0.7	1.2		
t_{err}	CS to ERR Pull-Up Propagation Delay	13	—	9.0	12		$C_{ERR} = 270$ pF

Static Electrical Characteristics


V_{BIAS} (V_{CC} , V_{BS}) = 15V and T_A = 25°C unless otherwise specified. The V_{IN} , V_{TH} and I_{IN} parameters are referenced to COM. The V_O and I_O parameters are referenced to V_S .

Symbol	Definition	Figure	Min.	Typ.	Max.	Units	Test Conditions
V_{IH}	Logic "1" Input Voltage	14	2.2	—	—	V	
V_{IL}	Logic "0" Input Voltage	15	—	—	0.8		
V_{CSTH+}	CS Input Positive Going Threshold	16	150	230	320	mV	
V_{CSTH-}	CS Input Negative Going Threshold	17	130	210	300		
V_{OH}	High Level Output Voltage, $V_{BIAS} - V_O$	18	—	—	100		$I_O = 0A$
V_{OL}	Low Level Output Voltage, V_O	19	—	—	100		$I_O = 0A$
I_{LK}	Offset Supply Leakage Current	20	—	—	50		$V_B = V_S = 500V$
I_{QBS}	Quiescent V_{BS} Supply Current	21	—	400	1000		$V_{IN} = V_{CS} = 0V$ or 5V
I_{QCC}	Quiescent V_{CC} Supply Current	22	—	700	1200		$V_{IN} = V_{CS} = 0V$ or 5V
I_{IN+}	Logic "1" Input Bias Current	23	—	4.5	10		$V_{IN} = 5V$
I_{IN-}	Logic "0" Input Bias Current	24	—	—	1.0		$V_{IN} = 0V$
I_{CS+}	"High" CS Bias Current	25	—	4.5	10		$V_{CS} = 3V$
I_{CS-}	"Low" CS Bias Current	26	—	—	1.0		$V_{CS} = 0V$
V_{BSUV+}	V_{BS} Supply Undervoltage Positive Going Threshold	27	8.5	9.2	10.0		
V_{BSUV-}	V_{BS} Supply Undervoltage Negative Going Threshold	28	7.7	8.3	9.0		
V_{CCUV+}	V_{CC} Supply Undervoltage Positive Going Threshold	29	8.3	8.9	9.6		
V_{CCUV-}	V_{CC} Supply Undervoltage Negative Going Threshold	30	7.3	8.0	8.7		
I_{ERR}	ERR Timing Charge Current	31	65	100	130	μA	$V_{IN} = 5V$, $V_{CS} = 3V$ $ERR < V_{ERR+}$
I_{ERR+}	ERR Pull-Up Current	32	8.0	15	—		$V_{IN} = 5V$, $V_{CS} = 3V$ $ERR > V_{ERR+}$
I_{ERR-}	ERR Pull-Down Current	33	16	30	—		$V_{IN} = 0V$
I_{O+}	Output High Short Circuit Pulsed Current	34	1.0	1.6	—		$V_O = 0V$, $V_{IN} = 5V$ $PW \leq 10 \mu s$
I_{O-}	Output Low Short Circuit Pulsed Current	35	2.0	3.3	—	A	$V_O = 15V$, $V_{IN} = 0V$ $PW \leq 10 \mu s$

IR2125(S) & (PbF)

International
Rectifier

Functional Block Diagram



Lead Definitions

Symbol	Description
V _{CC}	Logic and gate drive supply
IN	Logic input for gate driver output (HO), in phase with HO
ERR	Serves multiple functions; status reporting, linear mode timing and cycle by cycle logic shutdown
COM	Logic ground
V _B	High side floating supply
HO	High side gate drive output
V _S	High side floating supply return
CS	Current sense input to current sense comparator

Lead Assignments

<p>8 Lead PDIP</p>	<p>16 Lead SOIC (Wide Body)</p>
IR2125	Part Number IR2125S




Figure 1. Input/Output Timing Diagram

IR2125(S) & (PbF)




Figure 2. Floating Supply Voltage Transient Test Circuit




Figure 3. Switching Time Waveform Definitions




Figure 4. ERR Shutdown Waveform Definitions




Figure 5. CS Shutdown Waveform Definitions




Figure 6. CS to ERR Waveform Definitions

IR2125(S) & (PbF)

International
IR Rectifier




Figure 7A. Turn-On Time vs. Temperature




Figure 7B. Turn-On Time vs. Voltage




Figure 8A. Turn-Off Time vs. Temperature




Figure 8B. Turn-Off Time vs. Voltage




Figure 9A. ERR to Output Shutdown vs. Temperature




Figure 9B. ERR to Output Shutdown vs. Voltage




Figure 10A. Turn-On Rise Time vs. Temperature




Figure 10B. Turn-On Rise Time vs. Voltage




Figure 11A. Turn-Off Fall Time vs. Temperature




Figure 11B. Turn-Off Fall Time vs. Voltage




Figure 12A. CS to Output Shutdown vs. Temperature




Figure 12B. CS to Output Shutdown vs. Voltage

IR2125(S) & (PbF)

International
IR Rectifier




Figure 13A. CS to ERR Pull-Up vs. Temperature




Figure 13B. CS to ERR Pull-Up vs. Voltage




Figure 14A. Logic "1" Input Threshold vs. Temperature




Figure 14B. Logic "1" Input Threshold vs. Voltage




Figure 15A. Logic "0" Input Threshold vs. Temperature




Figure 15B. Logic "0" Input Threshold vs. Voltage




Figure 16A. CS Input Threshold (+) vs. Temperature




Figure 16B. CS Input Threshold (+) vs. Voltage




Figure 17A. CS Input Threshold (-) vs. Temperature




Figure 17B. CS Input Threshold (-) vs. Voltage




Figure 18A. High Level Output vs. Temperature




Figure 18B. High Level Output vs. Voltage

IR2125(S) & (PbF)

International
IR Rectifier




Figure 19A. Low Level Output vs. Temperature




Figure 19B. Low Level Output vs. Voltage




Figure 20A. Offset Supply Current vs. Temperature




Figure 20B. Offset Supply Current vs. Voltage




Figure 21A. V_{BS} Supply Current vs. Temperature




Figure 21B. V_{BS} Supply Current vs. Voltage




Figure 22A. V_{CC} Supply Current vs. Temperature




Figure 22B. V_{CC} Supply Current vs. Voltage




Figure 23A. Logic "1" Input Current vs. Temperature




Figure 23B. Logic "1" Input Current vs. Voltage




Figure 24A. Logic "0" Input Current vs. Temperature




Figure 24B. Logic "0" Input Current vs. Voltage

IR2125(S) & (PbF)

International
IR Rectifier




Figure 25A. "High" CS Bias Current vs. Temperature




Figure 25B. "High" CS Bias Current vs. Voltage




Figure 26A. "Low" CS Bias Current vs. Temperature




Figure 26B. "Low" CS Bias Current vs. Voltage




Figure 27. V_{BS} Undervoltage (+) vs. Temperature




Figure 28. V_{BS} Undervoltage Lockout - (V) vs. Temperature




Figure 29. V_{CC} Undervoltage (+) vs. Temperature




Figure 30. V_{CC} Undervoltage (-) vs. Temperature




Figure 31A. ERR Timing Charge Current vs. Temperature




Figure 31B. ERR Timing Charge Current vs. Voltage




Figure 32A. ERR Pull-Up Current vs. Temperature




Figure 32B. ERR Pull-Up Current vs. Voltage

IR2125(S) & (PbF)

International
IR Rectifier




Figure 33A. ERR Pull-Down Current vs. Temperature




Figure 33B. ERR Pull-Down Current vs. Voltage




Figure 34A. Output Source Current vs. Temperature




Figure 34B. Output Source Current vs. Voltage




Figure 35A. Output Sink Current vs. Temperature




Figure 35B. Output Sink Current vs. Voltage




Figure 36A. Turn-On Time vs. Input Voltage




Figure 36B. Turn-Off Time vs. Input Voltage






Figure 37. Maximum V_S Negative Offset vs. Supply Voltage


IR2125(S) & (PbF)

International
IR Rectifier

Case outlines



LEADFREE PART MARKING INFORMATION



ORDER INFORMATION

Basic Part (Non-Lead Free)

8-Lead PDIP IR2125 order IR2125
16-Lead SOIC IR2125S order IR2125S

Leadfree Part

8-Lead PDIP IR2125 order IR2125PbF
16-Lead SOIC IR2125S order IR2125SPbF

International
IR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245 Tel: (310) 252-7105
This product has been qualified per industrial level
Data and specifications subject to change without notice. 9/12/2004

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Gate Drivers category:

Click to view products by Infineon manufacturer:

Other Similar products are found below :

[89076GBEST](#) [00053P0231](#) [56956](#) [57.404.7355.5](#) [LT4936](#) [57.904.0755.0](#) [5882900001](#) [00600P0005](#) [00-9050-LRPP](#) [00-9090-RDPP](#)
[5951900000](#) [01-1003W-10/32-15](#) [0131700000](#) [00-2240](#) [LTP70N06](#) [LVP640](#) [5J0-1000LG-SIL](#) [LY1D-2-5S-AC120](#) [LY2-US-AC240](#) [LY3-UA-DC24](#) [00576P0020](#) [00600P0010](#) [LZN4-UA-DC12](#) [LZNQ2M-US-DC5](#) [LZNQ2-US-DC12](#) [LZP40N10](#) [00-8196-RDPP](#) [00-8274-RDPP](#)
[00-8275-RDNP](#) [00-8722-RDPP](#) [00-8728-WHPP](#) [00-8869-RDPP](#) [00-9051-RDPP](#) [00-9091-LRPP](#) [00-9291-RDPP](#) [0207100000](#) [0207400000](#)
[01312](#) [0134220000](#) [60713816](#) [M15730061](#) [61161-90](#) [61278-0020](#) [6131-204-23149P](#) [6131-205-17149P](#) [6131-209-15149P](#) [6131-218-17149P](#)
[6131-220-21149P](#) [6131-260-2358P](#) [6131-265-11149P](#)