

## **High and Low Side Driver**

### **Features**

- Floating channel designed for bootstrap operation
- Fully operational to +600V
- Tolerant to negative transient voltage
- dV/dt immune
- Gate drive supply range from 10 to 20V
- Undervoltage lockout for both channels
- 3.3V, 5V and 15V input logic compatible
- Matched propagation delay for both channels
- Logic and power ground +/-5V offset
- Lower di/dt gate driver for better noise immunity
- Outputs in phase with inputs


### **Product Summary**

V <sub>OFFSET</sub>	600V max.
I <sub>O+/-</sub>	200 mA / 350 mA
V <sub>OUT</sub>	10 – 20V
Ton/off (typ.)	220 & 200 ns

### **Description**


The IR25604 is a high voltage, high speed power MOSFET and IGBT driver with independent high and low side referenced output channels. Proprietary HVIC and latch immune CMOS technologies enable ruggedized monolithic construction. The logic input is compatible with standard CMOS or LSTTL output, down to 3.3V logic. The output drivers feature a high pulse current buffer stage designed for minimum driver cross-conduction. The floating channel can be used to drive an N-channel power MOSFET or IGBT in the high side configuration which operates up to 600 V.

### **Package Options**



### **Ordering Information**

Base Part Number	Package Type	Standard Pack		Orderable Part Number
		Form	Quantity	
IR25604SPBF	SO8N	Tube	95	IR25604SPBF
IR25604SPBF	SO8N	Tape and Reel	2500	IR25604STRPBF

**Typical Connection Diagram**

## Absolute Maximum Ratings

Absolute maximum ratings indicate sustained limits beyond which damage to the device may occur. All voltage parameters are absolute voltages referenced to COM. The thermal resistance and power dissipation ratings are measured under board mounted and still air conditions.

Symbol	Definition	Min.	Max.	Units
$V_B$	High side floating absolute voltage	-0.3	625	V
$V_S$	High side floating supply offset voltage	$V_B - 25$	$V_B + 0.3$	
$V_{HO}$	High side floating output voltage	$V_S - 0.3$	$V_B + 0.3$	
$V_{CC}$	Low side and logic fixed supply voltage	-0.3	25	
$V_{LO}$	Low side output voltage	-0.3	$V_{CC} + 0.3$	
$V_{IN}$	Logic input voltage	-0.3	$V_{CC} + 0.3$	
$dV_s/dt$	Allowable offset supply voltage transient	—	50	V/ns
$P_D$	Package power dissipation @ $TA \leq +25^\circ C$	—	0.625	W
$R_{thJA}$	Thermal resistance, junction to ambient	—	200	$^\circ C/W$
$T_J$	Junction temperature	—	150	$^\circ C$
$T_S$	Storage temperature	-55	150	
$T_L$	Lead temperature (soldering, 10 seconds)	—	300	

## Recommended Operating Conditions

For proper operation the device should be used within the recommended conditions. The  $V_S$  offset rating is tested with all supplies biased at 15V differential.

Symbol	Definition	Min.	Max.	Units
$V_B$	High side floating supply absolute voltage	$V_S + 10$	$V_S + 20$	V
$V_S$	High side floating supply offset voltage	†	600	
$V_{HO}$	High side floating output voltage	$V_S$	$V_B$	
$V_{CC}$	Low side and logic fixed supply voltage	10	20	
$V_{LO}$	Low side output voltage	0	$V_{CC}$	
$V_{IN}$	Logic input voltage	0	$V_{CC}$	
$T_A$	Ambient temperature	-40	125	$^\circ C$

† Logic operational for  $V_S$  of -5 to +600V. Logic state held for  $V_S$  of -5V to - $V_{BS}$ . (Please refer to Design Tip DT97-3 for more details).

## Dynamic Electrical Characteristics

$V_{BIAS}$  ( $V_{CC}$ ,  $V_{BS}$ ) = 15V,  $CL$  = 1000 pF and  $T_A$  = 25°C unless otherwise specified.


Symbol	Definition	Min.	Typ.	Max.	Units	Test Conditions
$t_{on}$	Turn-on propagation delay	—	220	300	ns	$V_S$ = 0V
$t_{off}$	Turn-off propagation delay	—	200	280		$V_S$ = 0V or 600V
$t_r$	Turn-on rise time	—	150	220		$V_S$ = 0V
$t_f$	Turn-off fall time	—	50	80		$V_S$ = 0V
MT	Delay matching, HS & LS turn-on/off	—	0	30		

## Static Electrical Characteristics

$V_{BIAS}$  ( $V_{CC}$ ,  $V_{BS}$ ) = 15V and  $T_A$  = 25°C unless otherwise specified. The  $V_{IN}$ ,  $V_{TH}$  and  $I_{IN}$  parameters are referenced to COM. The  $V_O$  and  $I_O$  parameters are referenced to COM and are applicable to the respective output leads: HO and LO.

Symbol	Definition	Min.	Typ.	Max.	Units	Test Conditions
$V_{IH}$	Logic “1” input voltage	2.9	—	—	V	$V_{CC}$ = 10V to 20V
$V_{IL}$	Logic “0” input voltage	—	—	0.8		$V_{CC}$ = 10V to 20V
$V_{OH}$	High level output voltage, $V_{BIAS} - V_O$	—	0.8	1.4		$I_O$ = 20 mA
$V_{OL}$	Low level output voltage, $V_O$	—	0.3	0.6		$I_O$ = 20 mA
$I_{LK}$	Offset supply leakage current	—	—	50		$V_B = V_S$ = 600V
$I_{QBS}$	Quiescent $V_{BS}$ supply current	20	75	130	$\mu A$	$V_{IN}$ = 0V or 5V
$I_{QCC}$	Quiescent $V_{CC}$ supply current	60	120	180		$V_{IN}$ = 0V or 5V
$I_{IN+}$	Logic “1” input bias current	—	5	20		$V_{IN}$ = 5V
$I_{IN-}$	Logic “0” input bias current	—	—	2		$V_{IN}$ = 0V
$V_{CCUV+}$ $V_{BSUV+}$	$V_{CC}$ and $V_{BS}$ supply undervoltage positive going threshold	8	8.9	9.8	V	
$V_{CCUV-}$ $V_{BSUV-}$	$V_{CC}$ and $V_{BS}$ supply undervoltage negative going threshold	7.4	8.2	9		
$V_{CCUVH}$ $V_{BSUVH}$	Hysteresis	0.3	0.7	---		
$I_{O+}$	Output high short circuit pulsed current	120	200	—	mA	$V_O$ = 0V $PW \leq 10 \mu s$
$I_{O-}$	Output low short circuit pulsed current	250	350	—		$V_O$ = 15V $PW \leq 10 \mu s$


## Functional Block Diagram



## Lead Definitions

Symbol	Description
HIN	Logic input for high side gate driver outputs (HO), in phase
LIN	Logic input for high side gate driver outputs (LO), in phase
V <sub>B</sub>	High side floating supply
HO	High side gate drive output
V <sub>S</sub>	High side floating supply return
V <sub>CC</sub>	Low side and logic fixed supply
LO	Low side gate drive output
COM	Low side return

## Lead Assignments



## Application Information and Additional Details




Figure 1. Input/Output Timing Diagram




Figure 2. Switching Time Waveform Definitions




Figure 3. Delay Matching Waveform Definitions




Figure 4A. Turn-on Propagation Delay  
vs. Temperature




Figure 4B. Turn-on Propagation Delay  
vs. Supply Voltage




Figure 5A. Turn-off Propagation Delay  
vs. Temperature




Figure 5B. Turn-off Propagation Delay  
vs. Supply Voltage




Figure 6A. Turn-on Rise Time  
vs. Temperature




Figure 6B. Turn-on Rise Time  
vs. Supply Voltage




Figure 7A. Turn-off Fall Time  
vs. Temperature




Figure 7B. Turn-off Fall Time  
vs. Supply Voltage




Figure 8A. Logic "1" Input Voltage  
vs. Temperature




Figure 8B. Logic "1" Input Voltage  
vs. Supply Voltage




Figure 9A. Logic "0" Input Voltage  
vs. Temperature




Figure 9B. Logic "0" Input Voltage  
vs. Supply Voltage




Figure 10A. High Level Output Voltage vs. Temperature




Figure 10B. High Level Output Voltage vs. Supply Voltage




Figure 11A. Low Level Output Voltage vs. Temperature




Figure 11B. Low Level Output Voltage vs. Supply Voltage




Figure 12A. Offset Supply Leakage Current vs. Temperature




Figure 12B. Offset Supply Leakage Current vs. Supply Voltage




Figure 13A. V<sub>BS</sub> Supply Current vs. Temperature




Figure 13B. V<sub>BS</sub> Supply Current vs. Supply Voltage




Figure 14A. Quiescent V<sub>CC</sub> Supply Current vs. Temperature




Figure 14B. Quiescent V<sub>CC</sub> Supply Current vs. V<sub>CC</sub> Supply Voltage




Figure 15A. Logic "1" Input Current vs. Temperature




Figure 15B. Logic "1" Bias Current vs. Supply Voltage




Figure 16A. Logic "0" Input Current  
vs. Temperature




Figure 16B. Logic "0" Input Current  
vs. Supply Voltage




Figure 17.  $V_{CC}$  Undervoltage Threshold (+)  
vs. Temperature




Figure 18.  $V_{CC}$  Undervoltage Threshold (-)  
vs. Temperature




Figure 19.  $V_{BS}$  Undervoltage Threshold (+)  
vs. Temperature




Figure 20.  $V_{BS}$  Undervoltage Threshold (-)  
vs. Temperature




Figure 21A. Output Source Current  
vs. Temperature




Figure 21B. Output Source Current  
vs. Supply Voltage




Figure 22A. Output Sink Current vs. Temperature




Figure 22B. Output Sink Current vs. Supply Voltage






Figure 23. Maximum  $V_s$  Negative Offset vs. Supply Voltage

## Package Details




## Tape and Reel Details




CARRIER TAPE DIMENSION FOR 8SOICN

Code	Metric		Imperial	
	Min	Max	Min	Max
A	7.90	8.10	0.311	0.318
B	3.90	4.10	0.153	0.161
C	11.70	12.30	0.46	0.484
D	5.45	5.55	0.214	0.218
E	6.30	6.50	0.248	0.255
F	5.10	5.30	0.200	0.208
G	1.50	n/a	0.059	n/a
H	1.50	1.60	0.059	0.062



REEL DIMENSIONS FOR 8SOICN

Code	Metric		Imperial	
	Min	Max	Min	Max
A	329.60	330.25	12.976	13.001
B	20.95	21.45	0.824	0.844
C	12.80	13.20	0.503	0.519
D	1.95	2.45	0.767	0.096
E	98.00	102.00	3.858	4.015
F	n/a	18.40	n/a	0.724
G	14.50	17.10	0.570	0.673
H	12.40	14.40	0.488	0.566

**Part Marking Information**

**Qualification Information<sup>†</sup>**

<b>Qualification Level</b>	Industrial <sup>††</sup> (per JEDEC JESD 47) Comments: This family of ICs has passed JEDEC's Industrial qualification. IR's Consumer qualification level is granted by extension of the higher Industrial level.
<b>Moisture Sensitivity Level</b>	MSL2 <sup>†††</sup> (per IPC/JEDEC J-STD-020)
<b>RoHS Compliant</b>	Yes

<sup>†</sup> Qualification standards can be found at International Rectifier's web site <http://www.irf.com/>

<sup>††</sup> Higher qualification ratings may be available should the user have such requirements. Please contact your International Rectifier sales representative for further information.

<sup>†††</sup> Higher MSL ratings may be available for the specific package types listed here. Please contact your International Rectifier sales representative for further information.

The information provided in this document is believed to be accurate and reliable. However, International Rectifier assumes no responsibility for the consequences of the use of this information. International Rectifier assumes no responsibility for any infringement of patents or of other rights of third parties which may result from the use of this information. No license is granted by implication or otherwise under any patent or patent rights of International Rectifier. The specifications mentioned in this document are subject to change without notice. This document supersedes and replaces all information previously supplied.

For technical support, please contact IR's Technical Assistance Center  
<http://www.irf.com/technical-info/>

**WORLD HEADQUARTERS:**  
233 Kansas St., El Segundo, California 90245  
Tel: (310) 252-7105

# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for Gate Drivers category:***

***Click to view products by Infineon manufacturer:***

Other Similar products are found below :

[00053P0231](#) [56956](#) [57.404.7355.5](#) [LT4936](#) [57.904.0755.0](#) [5882900001](#) [00600P0005](#) [00-9050-LRPP](#) [00-9090-RDPP](#) [5951900000](#) [01-1003W-10/32-15](#) [0131700000](#) [00-2240](#) [LTP70N06](#) [LVP640](#) [5J0-1000LG-SIL](#) [LY1D-2-5S-AC120](#) [LY2-US-AC240](#) [LY3-UA-DC24](#)  
[00576P0020](#) [00600P0010](#) [LZN4-UA-DC12](#) [LZNQ2M-US-DC5](#) [LZNQ2-US-DC12](#) [LZP40N10](#) [00-8196-RDPP](#) [00-8274-RDPP](#) [00-8275-RDNP](#) [00-8722-RDPP](#) [00-8728-WHPP](#) [00-8869-RDPP](#) [00-9051-RDPP](#) [00-9091-LRPP](#) [00-9291-RDPP](#) [0207100000](#) [0207400000](#) [013120134220000](#) [60713816](#) [M15730061](#) [61161-90](#) [61278-0020](#) [6131-204-23149P](#) [6131-205-17149P](#) [6131-209-15149P](#) [6131-218-17149P](#) [6131-220-21149P](#) [6131-260-2358P](#) [6131-265-11149P](#) [CS1HCPU63](#)