

## SIPMOS® Power-Transistor

### Feature

- P-channel
- Enhancement mode
- Logic Level
- 175°C operating temperature
- Avalanche rated
- dv/dt rated
- Pb-free lead plating; RoHS compliant
- Qualified according to AEC Q101





Type	Package	Lead free
SPD09P06PL G	PG-T0252-3	Yes

### Product Summary

$V_{DS}$	-60	V
$R_{DS(on)}$	0.25	$\Omega$
$I_D$	-9.7	A

PG-T0252-3



**Maximum Ratings**, at  $T_j = 25^\circ\text{C}$ , unless otherwise specified

Parameter	Symbol	Value	Unit
Continuous drain current $T_C=25^\circ\text{C}$	$I_D$	-9.7	A
$T_C=100^\circ\text{C}$		-6.8	
Pulsed drain current $T_C=25^\circ\text{C}$	$I_{D \text{ puls}}$	-38.8	
Avalanche energy, single pulse $I_D=-9.7 \text{ A}, V_{DD}=-25\text{V}, R_{GS}=25\Omega$	$E_{AS}$	70	mJ
Avalanche energy, periodic limited by $T_{j\text{max}}$	$E_{AR}$	4.2	
Reverse diode dv/dt $I_S=-9.7\text{A}, V_{DS}=-48\text{V}, dI/dt=200\text{A}/\mu\text{s}, T_{j\text{max}}=175^\circ\text{C}$	$dv/dt$	6	kV/ $\mu\text{s}$
Gate source voltage $T_C=25^\circ\text{C}$	$V_{GS}$	$\pm 20$	V
Power dissipation $T_C=25^\circ\text{C}$	$P_{\text{tot}}$	42	W
Operating and storage temperature	$T_j, T_{\text{stg}}$	-55... +175	°C
IEC climatic category; DIN IEC 68-1		55/175/56	

**Thermal Characteristics**

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
<b>Characteristics</b>					
Thermal resistance, junction - case	$R_{thJC}$	-	-	3.6	K/W
Thermal resistance, junction - ambient, leaded	$R_{thJA}$	-	-	100	
SMD version, device on PCB: @ min. footprint @ 6 cm <sup>2</sup> cooling area <sup>1)</sup>	$R_{thJA}$	-	-	75	
		-	-	50	

**Electrical Characteristics**, at  $T_j = 25^\circ\text{C}$ , unless otherwise specified

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
<b>Static Characteristics</b>					
Drain-source breakdown voltage $V_{GS}=0\text{V}, I_D=-250\mu\text{A}$	$V_{(BR)DSS}$	-60	-	-	V
Gate threshold voltage, $V_{GS} = V_{DS}$ $I_D=-250\mu\text{A}$	$V_{GS(\text{th})}$	-1	-1.5	-2	
Zero gate voltage drain current $V_{DS}=-60\text{V}, V_{GS}=0\text{V}, T_j=25^\circ\text{C}$ $V_{DS}=-60\text{V}, V_{GS}=0\text{V}, T_j=150^\circ\text{C}$	$I_{DSS}$	-	-0.1	-1	$\mu\text{A}$
-	-	-	-10	-100	
Gate-source leakage current $V_{GS}=-20\text{V}, V_{DS}=0\text{V}$	$I_{GSS}$	-	-10	-100	nA
Drain-source on-state resistance $V_{GS}=-4.5\text{V}, I_D=-5.4\text{A}$	$R_{DS(\text{on})}$	-	0.3	0.4	$\Omega$
Drain-source on-state resistance $V_{GS}=-10\text{V}, I_D=-6.8\text{A}$	$R_{DS(\text{on})}$	-	0.2	0.25	

<sup>1)</sup>Device on 40mm\*40mm\*1.5mm epoxy PCB FR4 with 6cm<sup>2</sup> (one layer, 70 µm thick) copper area for drain connection. PCB is vertical without blown air.

**Electrical Characteristics**, at  $T_j = 25^\circ\text{C}$ , unless otherwise specified

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	

### Dynamic Characteristics

Transconductance	$g_{fs}$	$V_{DS} \geq 2 * I_D * R_{DS(on)max}$ , $I_D = -5.4$	1.8	3.5	-	S
Input capacitance	$C_{iss}$	$V_{GS} = 0V$ , $V_{DS} = -25V$ , $f = 1\text{MHz}$	-	360	450	pF
Output capacitance	$C_{oss}$		-	103	130	
Reverse transfer capacitance	$C_{rss}$		-	40	50	
Turn-on delay time	$t_{d(on)}$	$V_{DD} = -30V$ , $V_{GS} = -4.5V$ , $I_D = -5.4$ , $R_G = 6\Omega$	-	11	17	ns
Rise time	$t_r$		-	168	252	
Turn-off delay time	$t_{d(off)}$		-	49	74	
Fall time	$t_f$		-	89	134	

### Gate Charge Characteristics


Gate to source charge	$Q_{gs}$	$V_{DD} = -48V$ , $I_D = -9.7A$	-	1.3	2	nC
Gate to drain charge	$Q_{gd}$		-	5.1	7.5	
Gate charge total	$Q_g$	$V_{DD} = -48V$ , $I_D = -9.7A$ , $V_{GS} = 0$ to $-10V$	-	14	21	
Gate plateau voltage	$V_{(plateau)}$	$V_{DD} = -48V$ , $I_D = -9.7A$	-	-4.1	-	V

### Reverse Diode

Inverse diode continuous forward current	$I_S$	$T_C = 25^\circ\text{C}$	-	-	-9.7	A
Inverse diode direct current, pulsed	$I_{SM}$		-	-	-38.8	
Inverse diode forward voltage	$V_{SD}$	$V_{GS} = 0V$ , $I_F = -9.7A$	-	-1.1	-1.4	V
Reverse recovery time	$t_{rr}$	$V_R = -30V$ , $I_F = I_S$ , $dI_F/dt = 100A/\mu\text{s}$	-	52	76	ns
Reverse recovery charge	$Q_{rr}$		-	64	96	nC

## 1 Power dissipation


$$P_{\text{tot}} = f(T_C)$$



## 2 Drain current

$$I_D = f(T_C)$$


parameter:  $V_{GS} \geq 10$  V



## 3 Safe operating area

$$I_D = f(V_{DS})$$


parameter :  $D = 0$  ,  $T_C = 25$  °C



## 4 Transient thermal impedance

$$Z_{\text{thJC}} = f(t_p)$$


parameter :  $D = t_p/T$



### 5 Typ. output characteristic

$$I_D = f(V_{DS}); \quad T_j=25^\circ\text{C}$$


parameter:  $t_p = 80 \mu\text{s}$



### 6 Typ. drain-source on resistance

$$R_{DS(on)} = f(I_D)$$


parameter:  $V_{GS}$



### 7 Typ. transfer characteristics

$$I_D = f(V_{GS}); \quad V_{DS} \geq 2 \times I_D \times R_{DS(on)\max}$$


parameter:  $t_p = 80 \mu\text{s}$



### 8 Typ. forward transconductance

$$g_{fs} = f(I_D); \quad T_j=25^\circ\text{C}$$


parameter:  $g_{fs}$



### 9 Drain-source on-state resistance

$$R_{DS(on)} = f(T_j)$$


parameter :  $I_D = -6.8 \text{ A}$ ,  $V_{GS} = -10 \text{ V}$



### 10 Gate threshold voltage

$$V_{GS(th)} = f(T_j)$$


parameter:  $V_{GS} = V_{DS}$ ,  $I_D = -250 \mu\text{A}$



### 11 Typ. capacitances

$$C = f(V_{DS})$$


parameter:  $V_{GS}=0\text{V}$ ,  $f=1 \text{ MHz}$



### 12 Forward character. of reverse diode

$$I_F = f(V_{SD})$$


parameter:  $T_j$ ,  $t_p = 80 \mu\text{s}$



### 13 Typ. avalanche energy

$$E_{AS} = f(T_j)$$


par.:  $I_D = -9.7 \text{ A}$ ,  $V_{DD} = -25 \text{ V}$ ,  $R_{GS} = 25 \Omega$



### 14 Typ. gate charge


$$V_{GS} = f(Q_{Gate})$$


parameter:  $I_D = -9.7 \text{ A}$  pulsed




### 15 Drain-source breakdown voltage

$$V_{(BR)DSS} = f(T_j)$$





DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	2.16	2.41	0.085	0.095
A1	0.00	0.15	0.000	0.006
b	0.64	0.89	0.025	0.035
b2	0.65	1.15	0.026	0.045
b3	5.00	5.50	0.197	0.217
c	0.46	0.60	0.018	0.024
c2	0.46	0.98	0.018	0.039
D	5.97	6.22	0.235	0.245
D1	5.02	5.84	0.198	0.230
E	6.40	6.73	0.252	0.265
E1	4.70	5.21	0.185	0.205
e	2.29		0.090	
e1	4.57		0.180	
N	3		3	
H	9.40	10.48	0.370	0.413
L	1.18	1.70	0.046	0.067
L3	0.90	1.25	0.035	0.049
L4	0.51	1.00	0.020	0.039
F1	10.50	10.70	0.413	0.421
F2	6.30	6.50	0.248	0.256
F3	2.10	2.30	0.083	0.091
F4	5.70	5.90	0.224	0.232
F5	5.66	5.86	0.223	0.231
F6	1.10	1.30	0.043	0.051

DOCUMENT NO.	Z8B00003328
SCALE	0 2.0 0 2.0 4mm
EUROPEAN PROJECTION	
	
ISSUE DATE	19-10-2007
REVISION	03

---

**Published by**  
**Infineon Technologies AG**  
**81726 Munich, Germany**  
**© 2008 Infineon Technologies AG**  
**All Rights Reserved.**

**Legal Disclaimer**

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

**Information**

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office ([www.infineon.com](http://www.infineon.com)).

**Warnings**

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office. Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for MOSFET category:***

***Click to view products by Infineon manufacturer:***

Other Similar products are found below :

[614233C](#) [648584F](#) [IRFD120](#) [JANTX2N5237](#) [FCA20N60\\_F109](#) [FDZ595PZ](#) [2SK2545\(Q,T\)](#) [405094E](#) [423220D](#) [TPCC8103,L1Q\(CM](#)  
[MIC4420CM-TR](#) [VN1206L](#) [614234A](#) [715780A](#) [NTNS3166NZT5G](#) [SSM6J414TU,LF\(T](#) [751625C](#) [BUK954R8-60E](#) [GROUP A 5962-](#)  
[8877003PA](#) [NTE6400](#) [SQJ402EP-T1-GE3](#) [2SK2614\(TE16L1,Q\)](#) [2N7002KW-FAI](#) [DMN1017UCP3-7](#) [EFC2J004NUZTDG](#) [ECH8691-TL-W](#)  
[FCAB21350L1](#) [P85W28HP2F-7071](#) [DMN1053UCP4-7](#) [NTE221](#) [NTE222](#) [NTE2384](#) [NTE2903](#) [NTE2941](#) [NTE2945](#) [NTE2946](#) [NTE2960](#)  
[NTE2967](#) [NTE2969](#) [NTE2976](#) [NTE6400A](#) [NTE2910](#) [NTE2916](#) [NTE2956](#) [NTE2911](#) [DMN2080UCB4-7](#) [TK10A80W,S4X\(S](#)  
[SSM6P69NU,LF](#) [DMP22D4UFO-7B](#) [DMN1006UCA6-7](#)