

PRODUCT BRIEF

Intel® Dual Band Wireless-N 7260

802.11agn, 2x2, Dual Band Wi-Fi + Bluetooth 4.0*



Intel® Dual Band Wireless-N 7260





Premium Wi-Fi. Exceptional Features. Great Connected Experience

The Intel® Dual Band Wireless-N 7260 802.11agn, dual band, 2x2 Wi-Fi + Bluetooth 4.0* adapter delivers faster speeds (up to 300 Mbps¹), greater range and more reliability. Combined 4th Gen Intel® Core™ processors and exceptional Intel wireless innovations, the Intel® Dual Band Wireless-N 7260 reshapes your connected experience at work, home or on the go.

reference to their location, locate the nearest resource (printer, conference, room, elevator, etc.),

Premium 802.11agn Wireless	
Speed Coverage Capacity 802.11agn, 2x2, Dual Band	Delivers up to 300 Mbps speed with dual streams (2x2) for better performance and connectivity in more places, through more walls, doors and floors. Use the power of dual band 5GHz to boost speeds and reduce congestion compared to older 2.4 GHz networks and devices.
Bluetooth 4.0* Smart Ready (Low Energy)	Dual mode Bluetooth 4.0 connects to the newest low energy Bluetooth products as well as your familiar devices, such as headsets, keyboard, mice and more.
Intel® Power Optimizer²	Optimized power modes during periods of activity and inactivity to improve platform battery life for greater mobility and convenience. Dramatically lower power consumption than previous generation products.
HMC and M.2 Form Factors	Single sided HMC and M.2 modules support multiple connectors for flexible system configuration and platform usages. The new M.2 form factor delivers a smaller, lower profile, more flexible form factor for thin-and-light Ultrabook™, notebook and tablet designs.
Experience the Intel Difference	
Always Ready to Go Intel® Smart Connect Technology ³	Stay current with automatic, no-wait updates to your email and social networks, even when your device is asleep. Combine it with Intel® WiFi HotSpot Assistant and automatically connect to millions of free and paid hotspots to refresh your content in more locations worldwide.
Instant Internet Worldwide Intel® WiFi Hotspot Assistant ⁴	Delivers instant Internet connectivity at millions of free and paid hotspot worldwide. After accepting a one-time only terms and conditions (T&C) login, your Internet connections are on auto-pilot as you roam the Wi-Fi hotspot universe—even as your Ultrabook™ sleeps. Combine it with Intel® Smart Connect Technology and your favorite cloud content (email, social networks, news, etc.) is automatically refreshed as you roam.
Business-Class Wireless	
Intel raide Intel vPro™ Technology 5	Supports Intel's hardware-based security and management features built into Intel® Core™ vPro™ processors and chipsets that enables IT to manage PCs virtually anywhere, anytime while reducing deployment costs, improving security and ROI.
Intel ² Active Management Technology ⁶	Using integrated platform capabilities and popular third-party management and security applications, Intel® AMT allows IT or managed service providers to better discover, repair, and protect their networked computing assets. Intel AMT is a feature of 3rd generation Intel® Core™ processors with Intel® vPro™ technology.
Intel® PROSet/Wireless Software7	Combines simplified user interface design with advanced IT tools to improve security, reduce complexity and save IT time and money. Streamlines client deployments and allows remote management of wireless settings and profiles by IT managers.
Intel Location Based Service ⁸	Enables seamless Wi-Fi indoor location service capability for employees to see campus maps with reference to their location, locate the nearest resource (printer, conference, room, elevator, etc.).

or for asset tracking.

Intel® Dual Band Wireless-N 7260 Technical Specifications

General

Weight

Dimensions (H x W x D) HMC: 26.80 mm x 30.00 mm x 2.4 mm Max (Top Side) / 1.35 mm Max (Bottom Side) Single Sided

M.2: 22 mm x 30.00 mm x 2.4 mm [1.5mm Max (Top Side)/ 0.1mm Max (Bottom Side)]

Diversity Supported

Radio ON/OFF Control Supported in both hardware and software Connector interface HMC: PCIe. USB

M.2: PCIe, USB **LED Output** On/Off

Operating Temperature (Adapter Shield) 0º to +80° C

Humidity Non-Operating 50% to 90% RH non-condensing (at temperatures of 25°C to 35°C) Operating Systems

Microsoft Windows 7*, Microsoft Windows 8*, Linux* (most features not available on Linux) Wi-Fi Alliance Wi-Fi CERTIFIED* a/b/g, Wi-Fi CERTIFIED* n, WMM*, WPA*, WPA2*, and WPS, WPS 2.0, Protected

Management Frames.

Wi-Fi Direct* for peer to peer device connections

IEEE 802.11abgn, 802.11d, 802.11e, 802.11i, 802.11h, 802.11w

Infrastructure and SoftAP; Supports simultaneous Client and SoftAP modes Architecture Roaming9 Supports seamless roaming between respective access points

(802.11b, 802.11g, 802.11a/b/g, 802.11a/b/g/n)

Bluetooth* Dual Mode Bluetooth* 2.1, 2.1+EDR, 3.0, 3.0+HS, 4.0 (BLE)

Security¹⁰

IEEE WLAN Standard

WPA and WPA2, 802.1X (EAP-TLS, TTLS, PEAP, LEAP, EAP-FAST), EAP-SIM, EAP-AKA Authentication

Authentication Protocols PAP, CHAP, TLS, GTC, MS-CHAP*, MS-CHAPv2 Encryption 64-bit and 128-bit WEP, AES-CCMP, TKIP

Wi-Fi Direct* Encryption and Authentication WPA2, AES-CCMP UL, C-UL, CB (IEC 60950-1)

Product Safety

802.11w (WFA- Protected Management Frames) Management Frame Protection

Compliance

FIPS¹¹, FISMA Government PCI, CISP Retail (Credit Card Processing)

Product Name Model Number Version Intel® Dual Band Wireless-N 7260 7260HMW AN 802.11agn, 2x2, Bluetooth 4.0, PCIe, USB, HMC 7260NGW AN 802.11agn, 2x2, Bluetooth 4.0, PCIe, USB, M.2

For more information on Intel® Wireless products, visit intel.com/wireless

¹ Based on the theoretical maximum bandwidth enabled by 2x2 802.11n implementations. Actual wireless throughput and/or range will vary depending on your specific operating system, hardware and software configurations. Check with your PC manufacturer for details

Actual platform battery life savings will vary depending on your specific operating system, hardware and software configurations. Check with your PC manufacturer for details.

³ Intel® Smart Connect Technology requires a select Intel® processor, Intel® software and BIOS update, Intel® Wireless adaptor, and Internet connectivity. Solid state memory or drive equivalent may

be required. Depending on system configuration, your results may vary. Contact your system manufacturer for more information.

Intel WiFi Hotspot Assistant requires an Intel wireless adapter, Intel® PROSet/Wireless WiFi Software v15.6 or later, and an Internet connection for initial setup with the Easy WiFi network.

5 Intel® vPro™ Technology is sophisticated and requires setup and activation. Availability of features and results will depend upon the setup and configuration of your hardware, software and IT environment.

To learn more visit: http://www.intel.com/technology/vpro
⁶ Requires activation and a system with a corporate network connection, an Intel[®] AMT-enabled chipset, network hardware and software. For notebooks, Intel[®] AMT may be unavailable or limited over a host OS-based VPN, when connecting wirelessly, on battery power, sleeping, hibernating or powered off. Results dependent upon hardware, setup & configuration. For more information, visit http://www.intel.com/technology/platform-technology/intel-amt

Intel® PROSet/Wireless Software may not be supported by your PC manufacturer. Check with your PC manufacturer for details on availability.

⁸ Intel Location Based Service requires selected Intel wireless adapters and Intel[®] PROSet/Wireless WiFi Software v15.6 or later on Intel[®] 4th Gen Core processor-based PCs only.

9 Roaming is supported only within each respective band and mode of access points.

¹⁰ Some security solutions may not be supported by your PC's operating system and/or by your PC manufacturer. Check with your PC manufacturer for details on availability.

¹¹ Microsoft Windows 7 and Microsoft Windows 8.

Software and workloads used in performance tests may have been optimized for performance only on Intel microprocessors. Performance tests, such as SYSmark and MobileMark, are measured using specific computer systems, components, software, operations and functions. Any change to any of those factors may cause the results to vary. You should consult other information and performance tests to assist you in fully evaluating your contemplated purchases, including the performance of that product when combined with other products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Intel's Terms and Conditions of Sale for such products, Intel assumes no liability whatsoever, and Intel disclaims any express or implied warranty, relating to sale and/or use of Intel products including without limitation, liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright or other intellectual property right. Intel products are not intended for use in medical, lifesaving, or life sustaining applications. Intel may make changes to specifications and product descriptions at any time, without notice. For the most current product information, please visit: http://www.intel.com/wireless Intel, the Intel logo, Intel, and Intel Centrino are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

*Other names and brands may be claimed as the property of others

Copyright © 2013 Intel Corporation. All rights reserved.



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for WiFi Modules - 802.11 category:

Click to view products by Intel manufacturer:

Other Similar products are found below:

KBPC10/15/2506WP WIFI-RT5392-SB-R10 SX-PCEAN2C-SP 849WM520100E WIFI-AT2350 7265.NGWG.SW HDG204-DN-3 FXX-3061-MIX EMIO-1533-00A2 7265.NGWWB.W PPC-WL-KIT02-R11 RC-CC2640-B HLK-7688A WH-NB73-BA NF-02-PA LSD4BT-E92ASTD001 EAR00364 3168.NGWG MY-WF003U AX210.NGWG.NV ESP-15F32Mbit ESP32-S32Mb TG-01M ESP-13 ESP-01F-2M ESP-01E-2M ESP-20 ESP32-SL ESP-12K-PSRAM ESP-12K-PSRAM-IPEX ESP-12H BW18 BW12-16Mb BW14 BW15 BW16 TG-12F SIM7600CE-L1S CB3S(tjrl) CB3S(hvk9) CB3S(qh6) WB2S(csyd) WB3S(ppty) WB3S(h238) WB3S(uvmz) 1005869 1012 QCA4004X-BL3B 32-2006-BU WT51822-S4AT