PRODUCT BRIEF

Intel® Wireless-AC 9260 5th Generation Intel 802.11ac, Dual Band, 2x2 Wi-Fi + Bluetooth® 5.1



Intel® Wireless-AC 9260

Ultra Wi-Fi. Ultra Features. Ultra Connected Experience





The Intel® Wireless-AC 9260 adapter supports Bluetooth® 5.1 and 2x2 802.11ac Wi-Fi including wave 2 features such as 160MHz channels, delivering up to 1.73Gbps¹ and downlink MU-MIMO. These new features deliver a significant increase in user speeds in dense deployments, supporting fast downloads and long battery life compared to legacy 802.11ac devices. Combined with Intel® Core™ processors and exceptional Intel wireless innovations, the Intel® Wireless-AC 9260 can provide Gigabit download speed¹ and dramatically improve your connected experience at home, work, or on the go.

5 [™] GENERATION INTEL 802.11AC WIRELESS		
Faster Speed Better Coverage Larger Capacity	Intel® Wireless-AC 9260 enables smoother streaming of higher resolution videos, fewer dropped connections, less congestion, and faster speeds farther away from the router, enabling DL MU-MIMO and 160MHz channel use.	
802.11ac, 2x2, Dual Band, 160MHz, MU-MIMO	When using 160MHz channels, Intel® Wireless-AC 9260 can deliver over 5x faster Wi-Fi speeds (up to 1.73Gbps) than 802.11n and double the speed of legacy 802.11ac².	
	Downlink MU-MIMO allows an Access Point to simultaneously transmit data to multiple clients and potentially improve overall downlink network capacity by over $3x^3$.	
Bluetooth® 5.1	Bluetooth* 5.1 provides 4x4 range over Bluetooth* 4.2 with the same power, enabling coverage throughout the home. Bluetooth* 5.1 also doubles the transmit speed for faster transmissions thereby reducing the overall power4. Additionally, Bluetooth* 5.1 adds new enhanced data broadcasting enabling seamless services such as location-based services and simpler pairing for Bluetooth* devices.	
Microsoft Windows 10* Ready	Full support for latest Microsoft Windows 10* OS.	
Form Factors (M.2 2230 and 1216)	M.2 2230 modules enable system configuration and platform usages flexibility with the use of a standard Key A or E socket for attaching the module.	
	M.2 1216 modules enable platform design providing savings on motherboard space and BOM.	

Worldwide Regulatory Support	Enables worldwide regulatory compliance on a single adapter SKU. The Intel® Wireless-AC 9260 detects i	
Intel® Dynamic Regulatory Solution	location and automatically optimizes the Wi-Fi settings to local regulatory requirements, maximizing performance in each geography, simplifying travel experience and global enterprise procurement. Future regulatory changes are easily managed during the product life cycle.	
Wireless Functionality in Pre-boot Environment	Support for Wi-Fi network and Bluetooth® Low Energy Human Interface Device (HID) connectivity in the platform's UEFI (Unified Extensible Firmware Interface) environment during its boot stage. This capability enables use cases like OS recovery over Wi-Fi and Bluetooth® Low Energy-based keyboard and mouse connectivity in this pre-boot environment.	
Wirelessly Project to the Big Screen	Watch your 2-in-1 or laptop content instantly without wires on the big HD screen with stunning image clarity and sound using Wi-Fi Miracast*. Stream movies, videos, games, photos, connect with friends, and more—experience it all, bigger and better than ever before.	

BUSINESS-CLASS WIRELESS		
Intel® vPro™ Technology⁵	Supports Intel's hardware-based security and management features built into Intel® Core™ vPro™ processors and chipsets that enables IT to manage PCs virtually anywhere, anytime while reducing deployment costs, improving security and ROI.	
Intel® Active Management Technology ⁶	Using integrated platform capabilities and popular third-party management and security applications, Intel® AMT allows IT or managed service providers to better discover, repair, and help protect their networked computing assets. Intel® AMT is a feature of Intel® Core™ processors with Intel® vPro™ technology.	

INTEL® WIRELESS-AC 9260 TECHNICAL SPECIFICATIONS

GENERAL

Dimensions (H x W x D)	M.2 2230: 22mm x 30mm x 2.4mm [1.5mm Max (Top Side)/ 0.1mm Max (Bottom Side)]	
	M.2 1216: 12mm x 16mm x 1.67 (+-0.08)mm	
Weight	M.2 2230: 2.9 +/- 0.3 g M.2 1216: 0.61 +/- 0.1 g	
Antenna Diversity	Supported	
Radio ON/OFF Control	Supported	
Connector Interface	M.2: PCle*, USB	
Operating Temperature (Adapter Shield)	0°C to +80°C	
Humidity Non-Operating	50% to 90% RH non-condensing (at temperatures of 25°C to 35°C)	
Operating Systems	Microsoft Windows 10*, Linux* (limited feature support), Chrome OS*	
Wi-Fi Alliance	Wi-Fi CERTIFIED* a/b/g/n/ac with wave 2 features, WMM*, WMM-PS*, WPA2*, WPA3*, WPS2*, Protected Management Frames, Wi-Fi Miracast* as Source, and Wi-Fi Direct (For Microsoft Windows* only)	
IEEE WLAN Standard	IEEE 802.11a/b/g/n/ac, 802.11d, 802.11e, 802.11h, 802.11i, 802.11w; 802.11r, 802.11k, 802.11v pending OS support; Fine Timing Measurement based on 802.11REVmc	
Roaming ⁷	Supports seamless roaming between access points	
Bluetooth®	Bluetooth® 5.1	

SECURITY⁸

Authentication	WPA2* and WPA3*, 802.1X (EAP-TLS, TTLS, PEAP,EAP-SIM, EAP-AKA, EAP-AKA')	
Authentication Protocols	PAP, CHAP, TLS, MS-CHAP*, MS-CHAPv2	
Encryption 64-bit and 128-bit WEP, TKIP, 128-bit AES-CCMP, 128-bit and 256-bit AES-GCMP		
Wi-Fi Direct* Encryption and Authentication WPA2-PSK, AES-CCMP		

COMPLIANCE

Regulatory	For a list of country approvals, please contact your local Intel representatives.	
US Government	FIPS ⁹ , FISMA	
Product Safety	UL, C-UL, CB (IEC 60950-1)	

PRODUCT NAME	MODEL NUMBER	VERSION
Intel® Wireless-AC 9260	9260NGW	802.11ac wave 2, 2x2, Bluetooth® 5.1, PCIe*, USB, M.2 2230
Intel® Wireless-AC 9260	9260D2WL	802.11ac wave 2, 2x2, Bluetooth® 5.1, PCIe*, USB, M.2 1216 LTE Coex





For more information on Intel® Wireless products, visit intel.com/wireless

- ¹ Based on the theoretical maximum bandwidth enabled by 2x2 802.11ac 160Mhz implementations. Actual wireless throughput and/or range will vary depending on your specific operating system, hardware and software configurations. Check with your device manufacturer for details.
- ² 802.11ac 160MHz provides 1.73Gbps maximum throughput, 2x more than 802.11ac 80MHz (867Mbps) and 5x more than 802.11n 40MHz (300Mbps) based on industry standards.
- ³ 802.11ac downlink MU-MIMO technology allows concurrently serving multiple devices simultaneously, in turn increasing network capacity potentially by over 3x while improving per-user throughput based on industry standards.
- 4 Bluetooth® 5.1 Feature Overview, https://3pl46c46ctx02p7rzdsvsg21-wpengine.netdna-ssl.com/wp-content/uploads/2019/03/1901 Feature Overview Brief FINAL.pdf
- ⁵ Intel® vPro™ Technology is sophisticated and requires setup and activation. Availability of features and results will depend upon the setup and configuration of your hardware, software and IT environment. To learn more visit: http://www.intel.com/technology/vpro
- ⁶ Requires activation and a system with a corporate network connection, an Intel® AMT-enabled chipset, network hardware and software. For notebooks, Intel® AMT may be unavailable or limited over a host OS-based VPN, when connecting wirelessly, on battery power, sleeping, hibernating or powered off. Results dependent upon hardware, setup and configuration. For more information, visit http://www.intel.com.
- ⁷ Roaming is supported only within each respective band and mode of access points.
- ⁸ Some security solutions may not be supported by your device operating system and/or by your device manufacturer. Check with your device manufacturer for details on availability.
- ⁹ Microsoft Windows 7*, Microsoft Windows 8.1* and Microsoft Windows 10*.

The Bluetooth® word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. and any use of such marks by Intel Corporation is under license.

Software and workloads used in performance tests may have been optimized for performance only on Intel microprocessors. Performance tests, such as SYSmark and MobileMark, are measured using specific computer systems, components, software, operations and functions. Any change to any of those factors may cause the results to vary. You should consult other information and performance tests to assist you in fully evaluating your contemplated purchases, including the performance of that product when combined with other products. For more complete information visit http://www.intel.com/benchmarks.

No license (express or implied, by estoppel or otherwise) to any intellectual property rights is granted by this document. Except as provided in Intel's Terms and Conditions of Sale for such products, Intel assumes no liability whatsoever, and Intel disclaims any express or implied warranty, relating to sale and/or use of Intel products including without limitation, liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright or other intellectual property right. Intel products are not intended for use in medical, lifesaving, or life sustaining applications. Intel may make changes to specifications and product descriptions at any time, without notice. For the most current product information, please visit http://www.intel.com/wireless.

Cost reduction scenarios described are intended as examples of how a given Intel-based product, in the specified circumstances and configurations, may affect future costs and provide cost savings. Circumstances will vary. Intel does not guarantee any costs or cost reduction. This device has not been authorized as required by the rules of the Federal Communications Commission. This device is not, and may not be, offered for sale or lease, or sold or leased, until authorization is obtained.

Intel, the Intel logo, and Intel are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and/ or other countries.

*Other names and brands may be claimed as the property of others.

Copyright © Intel Corporation. All rights reserved.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for WiFi Modules (802.11) category:

Click to view products by Intel manufacturer:

Other Similar products are found below:

WISE-1520ITB-TDA1E SX-PCEAN2C-SP BCM43602KMLG 7265.NGWG.W ENW-49801A1JF WH-M2SD50NBT SX-680-2700-SP RN171-IRM481 FXX-3061-MIX 9668C52W10E EMIO-1533-00A2 ISM43340-L77-TR BCM4352KMLG BCM43520KMLG BCM43520KMLG BCM43217KMLG 7265.NGWWB.W PPC-WL-KIT02-R11 E19-433MS1W RC-CC2640-A M113DH3200PS3Q0 M113DH3200US3Q0 SX-PCEAN2c WT-01S WT8266-S3 ESP-07S WT8266-S6 ESP-12S WT-01F WT8266-S5 ESP-12F WT32-S1 ESP-WROOM-02UC ESP-WROOM-02DC WT-01N ESP32-WROOM-32UC ESP32-WROOM-32DC ESP-01 ESP-01S ESP32-WROOM-32(16MB) ESP32-WROVER-E(8MB) ESP32-WROVER-IB(16MB) ESP32-WROVER-E(16MB) ESP32-WROOM-32U(8MB) ESP32-WROOM-32U(16MB) ESP32-WROOM-02(4MB) ESP32-WROOM-02D(4MB) ESP32-WROVER-E(4MB) ESP32-WROVER-B(16MB) ESP32-WROVER-B(16MB) ESP32-WROVER-B(16MB) ESP32-WROVER-E(4MB) ESP32-WROVER-B(16MB) ESP32-WROVER-B(