intel

Intel[®] PRO/1000 GT Desktop Adapter

Lead-Free Gigabit Performance to the Desktop

Now you can maximize system performance and increase end-user productivity for mainstream PCs with the new Intel® PRO/1000 GT Desktop Adapter. Today's desktops are weighed down with high-bandwidth applications including voice, data, streaming video, video conferencing, and long-distance storage area networks. The environmentally friendly Intel PRO/1000 GT Desktop Adapter's Gigabit bandwidth makes quick work of these network applications with power to spare.

The Intelligent Way to Connect

Built on Intel lead-free technology, the Intel PRO/ 1000 GT Desktop Adapter is the environmentally friendly way to bring Gigabit performance to your desktop at no extra cost! The GT Desktop Adapter contains no lead and conforms to the European Union's Restrictions on the use of Hazardous Substances and Japan's White Goods Recycling Act.

■ Simplify installation and maintenance with Intel[®] SingleDriver[™] technology: Intel offers a single driver across all Intel PRO/1000 Desktop and Server Adapters making it easier to administer



and upgrade to the latest generation of Intel adapters, simplifying network management and reducing maintenance costs.

High-performing, auto-negotiating 10/100/ 1000 connection: Systems that are currently running at 10 Mbps or 100 Mbps can be upgraded with the Intel PRO/1000 GT Desktop Adapter now, whether Gigabit switching is currently available or not. By integrating an Intel® PRO Gigabit Network Connection now, information technology (IT) managers will save time, money and downtime when the network is upgraded later because the Intel PRO/1000 GT Desktop Adapter will automatically detect and run at the higher speed when it becomes available.

Features	Benefits
Intel® 82541PI Gigabit Controller	Enhances high performance and reliability
Compatible with Fast Ethernet and Ethernet	Reduces deployment and training costs and enables easy, quick migration to Gigabit Ethernet
Peripheral Component Interconnect (PCI) 2.3 32-bit 33/66 MHz	Designed for high performance on desktop bus architecture
10/100/1000 Mbps	Allows easy migration to faster networks as current 10/100 Mbps networks move to Gigabit, without requiring reconfiguration by IT staff—saving time, money and downtime
Category-5 Cabling	Uses pre-existing 4-pair cabling and saves re-wiring cost
Interrupt Moderation	Significantly reduces CPU utilization and increases throughput
Advanced Configuration and Power Interface (ACPI), Wake on LAN* (WoL), Preboot Execution Environment (PXE)	Allows lower power consumption, remote wake and remote booting
Simple Network Management Protocol (SNMP)/Desktop Management Interface (DMI), Wired for Management (WfM)	Lowers Total Cost of Ownership (TCO) through improved manageability
Meets IEEE 802.3ab* Technology	Supports standards interoperability
Advanced Cable Diagnostics	Dynamically tests and reports network problems (interrupts, error rate, cable length) and automatically compensates for cable issues such as crossover cable, wrong pin-out and polarity
Support for Many Network Operating Systems (NOSs)	Enables widespread deployment



Specifications: Intel[®] PRO/1000 GT Desktop Adapter

General

uciiciai	
Product Codes Connectors	PWLA8391GT, PWLA8391GTBLK, PWLA8391GTLBLK RJ-45
IEEE Standard/Network Topology Wiring	10BASE-T, 100BASE-TX, 1000BASE-T Cat-5, 4-pair
Adapter Product Features	
Intel [®] Lead-free Technology	
Intel [®] SingleDriver [™] Technology	
Plug and Play Specification Support Easy Installation, Intel [®] PROSet Utility	Standard
Auto-negotiation, Full-duplex Capable	-
PCI 2.3	•
Bus Speed	32-bit 33/66 MHz
Network Management	
WfM Baseline v2.0	
DMI 2.0 Support, Windows	
Management Instrumentation	
(WMI) & SNMP-manageable Offline Diagnostics	
Intel [®] Boot Agent	
ACPI Power Management	
Wake on LAN	
NOS Software Support	
Microsoft Windows* 2000, XP	=
Microsoft Windows NT* 4.0	1
Microsoft Windows 98 SE, Me Disk Operating System (DOS) and	
Disk Operating System (DOO) and Disk Operating System Optical	_
Digital Image (DOSODI)	
Linux* 2.2.5 or Later	-
Novell Netware* 4.2, 5.1, 6.0	-
Advanced Software Features	
IEEE 802.1Q Virtual Local Area	
Network (VLANs) IEEE 802.3x Flow Control	
Transmission Control Protocol (TCP)	-
Checksum Offload	
IEEE 802.1p, Intel® Priority Packet II	
Technical Features	
Data Rate(s) Supported Per Port	10/100/1000 Mbps
Integrated Memory	64 KB
Interrupt Levels IEEE Support	INTA 802.2 and 802.3ab
Data Path Width	32-bit PCI
Hardware Certifications	FCC B, CE, BSMI B, VCCI B
Data Transfer Mode	Bus-master DMA
Controller—Processor	Intel® 82541PI
Typical Power Consumption Operating Temperature	800 mA @+5 VDC 0-55°C
Operating Humidity	85% at +55°C
Intel Backing	
Limited Lifetime Warranty	
90-day Money-back Guarantee	
(U.S. and Canada)	

Order Codes

- PWLA8391GT (Single Packs)
- PWLA8391GTBLK (20 Packs)
- PWLA8391GTLBLK (Low-Profile 20 Packs)

Companion Products

Consider these Intel products in your server and network planning:

- Intel® PRO/1000 MT Server Adapter
- Intel® PRO/1000 MF Server Adapter
- Intel[®] PRO/1000 MF Server Adapter (LX)
- Intel® PRO/1000 MF Dual Port Server Adapter
- Intel[®] PRO/1000 MT Dual Port Server Adapter
- Intel® PRO/1000 MT Quad Port Server Adapter
- Intel[®] Desktop Boards
- Intel® Pentium® 4 Processor with Hyper-Threading Technology

Network-Ready PCs

Top PC and server manufacturers offer Intel adapters in their new products. Specify or ask for Intel® PRO Network Connections with your next PC, server, or mobile PC purchase. For a list of preferred suppliers, visit us at www.intel.com/buy/wtb/ wtb1019.htm.

Customer Support

Intel[®] Customer Support Services offers a broad selection of programs including phone support and warranty service. For more information, contact us at **support.intel.com/support/ network.** Service and availability may vary by country.

Product Information

To speak to a customer service representative regarding Intel products, please call 1-800-538-3373 (U.S. and Canada) or visit www.intel.com/support/9089.htm for the telephone number in your area. For additional product information on the Intel® Networking and Communication products, visit www.intel.com/network/connectivity.

Online Documents

For the latest product information, visit us at www.intel.com/ network/connectivity.

Information in this document is provided in connection with Intel® products. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Intel's Terms and Conditions of Sale for such products, Intel assumes no liability whatsoever, and Intel disclaims any express or implied warranty, relating to sale and/or use of Intel products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright or other intellectual property right. Intel products are not intended for use in medical, life-saving, or life-sustaining applications. Intel may make changes to specifications and product descriptions at any time, without notice. For the most current product information, please visit www.intel.com/network/connectivity.

*Other names and brands may be claimed as the property of others. Copyright © 2004 Intel Corporation. All rights reserved.

Intel, the Intel logo, SingleDriver, and Pentium are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

Printed in USA

0804/PAL/0CG/XX/PDF

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Ethernet Modules category:

Click to view products by Intel manufacturer:

Other Similar products are found below :

TDKEZW3
V23993-USB1029A
100-POE4
I210T1BLK
X520QDA1
BCM84794A1KFSBG
X520DA2OCP
808-38157
7506GX2
TC

EXTENDER 2001
ETH-2S
105FX-SC-MDR
110FX2-SC
BCM54291B0IQLEG
7000-P3201-P050150
750-1415
750-494
750-495
750-612

750-613
750-627
750-643
750-940
753-540
753-650/003-000
852-1322
852-1812
852-1813
852-1816
LANTICK PE

0-16
LANTICK PE-16-0
RBMTXLITE-L4X2.X.X.X.X.
USR-TCP232-T2
2017008
EKI-7708E-4FP-AE
EKI-7708G

4FP-AE
2352903-2
753-620
EGU-0702-SFP-T
SW-525
SW-725
1005957
1006191
304TX-N
WIZ107SR_TTL
ES-320

TDKEZW5
S
S
S
S
S
S
S
S
S
S
S
S
S
S
S
S
S
S
S
S
S
S
S
S
S
S
S
S
S
S
S
S
S
S
S
S
S
S
S