

#### IB090102 INDUCTIVE SENSORS • NORM SWITCHING DISTANCE

sensor inductive, 40x8x8mm, Flush, Sn: 1.5, 10-30V DC, PNP NO, Cable 10m PVC, IP67, Brass Nickel-plated



### MECHANICAL FEATURES


| Active area material of sensor           | PA 6.1 GF15           |
|--|-----------------------|
| Ambient temperature                      | -25 °C 70 °C          |
| Cable infeed                             | Axial                 |
| Cable length                             | 10 m                  |
| Degree of protection (IP)                | IP67                  |
| Design                                   | Cuboid                |
| Housing coating                          | Nickel-plated         |
| Housing material                         | Brass                 |
| Material of cable sheath                 | PVC                   |
| Max. tightening torque                   | 1 Nm                  |
| Mechanical mounting condition for sensor | Flush                 |
| Number of cores                          | 3                     |
| Pressure-proof                           | ·                     |
| Sensor height                            | 40 mm                 |
| Sensor length                            | 8 mm                  |
| Sensor width                             | 8 mm                  |
| ELECTRICAL FEATURES                      |                       |
| Cascadable                               |                       |
| Hysteresis                               | -<br>5 %              |
| No-load current                          | 10 mA                 |
| Rated switching current                  | 200 mA                |
| Reverse polarity protection              |                       |
| Short-circuit protection                 | +                     |
| Suitable for safety functions            | •                     |
|  | -<br>10 V 30 V        |
| Supply voltage                           | 1.5 mm                |
| Switching distance                       | 1.5 mm<br>1000 Hz     |
| Switching frequency                      | Cable                 |
| Type of electrical connection            |                       |
| Type of switching function               | Normally open contact |
| Type of switching output                 | PNP                   |
| Voltage drop                             | 2 V<br>DC             |
| Voltage type                             |                       |

# **IPF** ELECTRONIC


| ELECTRICAL FEATURES                            |                         |
|--|-------------------------|
| With LED display                               | +                       |
| With monitoring function of downstream devices | -                       |
| Other  |                         |
| Packaging dimensions                           | 76.0mm x 50mm x 121.0mm |
| Shipping weight                                |                         |
| Tariff code                                    | 85365019                |
|  |                         |
| Classification                                 |                         |
| ipf product group                              | 215                     |
|  | 27270101                |


| ipf product group | 215      |
|-------------------|----------|
| eClass 8.0        | 27270101 |
| eClass 9.0        | 27270101 |
| eClass 9.1        | 27270101 |
| ETIM-5.0          | EC002714 |
| ETIM-6.0          | EC002714 |
| ETIM-7.0          | EC002714 |

#### Connection



#### **Dimensional drawing**





#### Installation



carried out by a qualified electrician!

Mounting / installation may only be



Disposal

#### Safety warnings

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information. Never use these devices in applications where the safety of a person depends on their functionality. LED lighting systems can generate intensive UV radiation, which can damage your eyes in case of improper use. The manufacturer cannot be held responsible for damages that result from improper use or connection.

# **IPF** ELECTRONIC

### **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Proximity Sensors category:

Click to view products by IPF ELECTRONIC manufacturer:

Other Similar products are found below :

01.001.5653.1 70.340.1028.0 70.360.2428.0 70.364.4828.0 70.810.1053.0 72.360.1628.0 73.363.6428.0 8027AL20NL2CPXX FYCC8E1-2 9221350022 922AA2W-A9P-L PLS2 GL-12F-C2.5X10(LOT3) 972AB2XM-A3N-L 972AB3XM-A3P-L PS3251 980659-1 QT-12 E2E2-X5M41-M4 E2E-X14MD1-G E2E-X2D1-G E2EX2ME2N E2EX3D1SM1N E2E-X4MD1-G E2E-X5E1-5M-N E2E-X5Y2-N E2E-X7D1-M1J-T-0.3M-N E2K-F10MC1 5M EH-302 EI3010TBOP EI5515NPAP MS605AU EP175-32000 IFRM04N35B1/L IFRM04P1513/S35L IFRM06P1703/S35L IFRM08P1501/S35L IFRM12N17G3/L IFRM12P17G3/L IFRM12P3502/L IFRM12P37G1/S14L ILFK12E9189/I02 ILFK12E9193/I02 IMM2582C OISN-013 25.161.3253.0 25.332.0653.1 25.352.0653.0 25.352.0753.0 25.523.3253.0