

#### IB307004

# **INDUCTIVE SENSORS • NORM SWITCHING DISTANCE**

sensor inductive, M30x1.5 35long, Flush, Sn: 10, 7.7-10V DC, NA-MUR Anschluss an Verstärker, Cable 2m PVC, IP67, Brass Nickel-plated



# **MECHANICAL FEATURES**

Active area material of sensor	Polytetrafluorethylene (PTFE)
Alignment of cable entry	Axial
Ambient temperature	-25 °C 70 °C
Cable infeed	Axial
Cable length	2 m
Degree of protection (IP)	IP67
Design	Cylinder, screw-thread
Housing coating	Nickel-plated
Housing material	Brass
Material of cable sheath	PVC
Mechanical mounting condition for sensor	Flush
Pressure-proof	-
Sensor length	35 mm
Thread pitch	1.5 mm
Thread size, metric	30

# **ELECTRICAL FEATURES**

ELECTRICAL FEATORES	
ATEX approval	+
Cascadable	-
Connection to amplifier	+
Norm measuring plate	30x30x1
Rated switching current	2.1 mA
Relative repeat accuracy	0.1 %
Suitable for safety functions	-
Supply voltage	7.7 V 10 V
Switching distance	10 mm
Switching frequency	500 Hz
Type of electrical connection	Cable
Type of switching function	Amplifier
Type of switching output	NAMUR
Voltage type	DC
With monitoring function of downstream devices	-



#### **OTHER FEATURES**

ATEX product marking, gas	Ex II 1G Ex ia Ex IIC T1 – T6 Ga
Other	
Packaging dimensions	124.0mm x 35.0mm x 149.0mm
Shipping weight	0.27kg
Tariff code	85365019
Classification	
ipf product group	203
eClass 8.0	27270101
eClass 9.0	27270101
eClass 9.1	27270101
ETIM-5.0	EC002714


EC002714

EC002714

#### Connection

ETIM-6.0

ETIM-7.0



# **Dimensional drawing**

### Installation



Mounting / installation may only be carried out by a qualified electrician!

### Disposal



# Safety warnings

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.

Never use these devices in applications where the safety of a person depends on their functionality.

LED lighting systems can generate intensive UV radiation, which can damage your eyes in case of improper use. The manufacturer

LED lighting systems can generate intensive UV radiation, which can damage your eyes in case of improper use. The manufacturer cannot be held responsible for damages that result from improper use or connection.

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Proximity Sensors category:

Click to view products by IPF ELECTRONIC manufacturer:

Other Similar products are found below:

01.001.5653.1 70.340.1028.0 70.360.2428.0 70.364.4828.0 70.810.1053.0 72.360.1628.0 73.363.6428.0 8027AL20NL2CPXX FYCC8E1-2 9221350022 922AA2W-A9P-L PLS2 GL-12F-C2.5X10(LOT3) 972AB2XM-A3N-L 972AB3XM-A3P-L PS3251 980659-1 QT-12 E2E2-X5M41-M4 E2E-X14MD1-G E2E-X2D1-G E2EX2ME2N E2EX3D1SM1N E2E-X4MD1-G E2E-X5E1-5M-N E2E-X5Y2-N E2E-X7D1-M1J-T-0.3M-N E2FMX1R5D12M E2K-F10MC1 5M EH-302 EI3010TBOP EI5515NPAP MS605AU EP175-32000 IFRM04N35B1/L IFRM04P1513/S35L IFRM06P1703/S35L IFRM08P1501/S35L IFRM12N17G3/L IFRM12P17G3/L IFRM12P3502/L IFRM12P37G1/S14L ILFK12E9189/I02 ILFK12E9193/I02 IMM2582C OISN-013 25.161.3253.0 25.332.0653.1 25.352.0653.0 25.352.0753.0