

KBQC0100

Capacitive sensor

I for positioning of objects

I for filling level detction of liquids and bulk materials

/ plastic housing

l easy mounting

I short-circuit and reverse polarity protected

/ protection class IP68

I cable connection



switching distance adjustable via teach-in












Technical data


dimensions	34 x 34 x 8mm
switching distance	0 10mm
operating voltage	10 30V DC
current consumption	<15mA
switching frequency	≤ 2Hz
output circuit	NO
output current max.	200mA
voltage drop (max. load)	≤ 2.0V
LED-display	+
short-circuit protection	+
reverse polarity protection	+
ambient temperature	-25 +70°C
protection class (EN 60529)	IP68
material (housing)	PA
connection	2m cable, PVC, 4x0.14mm ²

Connection



colors: BN = brown, WH = white, BU = blue, BK = black functions: BN = L+, WH = teach-in, BU = L-, BK = PNP, NO

Dimensional drawing





LED-display teach function



Note: After teaching, please make sure that the teach-wire remains unconnected.

SAFETY WARNINGS

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!

Never use these articles in applications where the safety of a person depends on their functionality.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Proximity Sensors category:

Click to view products by IPF ELECTRONIC manufacturer:

Other Similar products are found below:

01.001.5653.1 70.340.1028.0 70.360.2428.0 70.364.4828.0 70.810.1053.0 72.360.1628.0 73.363.6428.0 8027AL20NL2CPXX FYCC8E1-2 9221350022 922AA2W-A9P-L PLS2 GL-12F-C2.5X10(LOT3) 972AB2XM-A3N-L 972AB3XM-A3P-L PS3251 980659-1 QT-12 E2E2-X5M41-M4 E2E-X14MD1-G E2E-X2D1-G E2EX2ME2N E2EX3D1SM1N E2E-X4MD1-G E2E-X5E1-5M-N E2E-X5Y2-N E2E-X7D1-M1J-T-0.3M-N E2FMX1R5D12M E2K-F10MC1 5M EH-302 EI3010TBOP EI5515NPAP MS605AU EP175-32000 IFRM04N35B1/L IFRM04P1513/S35L IFRM06P1703/S35L IFRM08P1501/S35L IFRM12N17G3/L IFRM12P17G3/L IFRM12P3502/L IFRM12P37G1/S14L ILFK12E9189/I02 ILFK12E9193/I02 IMM2582C OISN-013 25.161.3253.0 25.332.0653.1 25.352.0653.0 25.352.0753.0