

#### KN126051

# **CAPACITIVE SENSORS • INCREASED AMBIENT TEMPERATURE**

sensor capacitive, M12x1 25long, Non-flush, Sn: 1-25, 250°C, Amplifier, Cable 2m FEP, IP67, V2A



# **MECHANICAL FEATURES**

Ambient temperature (MAX)	250 °C
Ambient temperatures < -25°C	+
Cable length	2 m
Degree of protection (IP)	IP67
Design	Cylinder, screw-thread
Housing material	Stainless steel (V2A)
Increased ambient temperatures > 80°C	+
Material of cable sheath	FEP
Mechanical mounting condition for sensor	Non-flush
Pressure-proof	-
Sensor length	25 mm
Thread pitch	1 mm
Thread size, metric	12

### **ELECTRICAL FEATURES**

Cascadable	r
Reverse polarity protection	+
Short-circuit protection	+
Suitable for safety functions	-
Switching distance	25 mm
Switching distance	1 mm 25 mm
Type of electrical connection	Cable
Type of switching function	Amplifier
With monitoring function of downstream devices	-

# **OTHER FEATURES**

Level detection +

## Other


Packaging dimensions	77.0mm x 25.0mm x 123.0mm
Shipping weight	0.17kg
Tariff code	85365019




#### Classification

ipf product group	242
eClass 8.0	27270102
eClass 9.0	27270102
eClass 9.1	27270102
ETIM-5.0	EC002715
ETIM-6.0	EC002715
ETIM-7.0	EC002715

#### Connection



# **Dimensional drawing**



#### Installation



Mounting / installation may only be carried out by a qualified electrician!

#### Disposal



# Safety warnings

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information. Never use these devices in applications where the safety of a person depends on their functionality.

LED lighting systems can generate intensive UV radiation, which can damage your eyes in case of improper use. The manufacturer cannot be held responsible for damages that result from improper use or connection.

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Proximity Sensors category:

Click to view products by IPF ELECTRONIC manufacturer:

Other Similar products are found below:

01.001.5653.1 70.340.1028.0 70.360.2428.0 70.364.4828.0 70.810.1053.0 72.360.1628.0 73.363.6428.0 8027AL20NL2CPXX FYCC8E1-2 9221350022 922AA2W-A9P-L PLS2 GL-12F-C2.5X10(LOT3) 972AB2XM-A3N-L 972AB3XM-A3P-L PS3251 980659-1 QT-12 E2E2-X5M41-M4 E2E-X14MD1-G E2E-X2D1-G E2EX2ME2N E2EX3D1SM1N E2E-X4MD1-G E2E-X5E1-5M-N E2E-X5Y2-N E2E-X7D1-M1J-T-0.3M-N E2FMX1R5D12M E2K-F10MC1 5M EH-302 EI3010TBOP EI5515NPAP MS605AU EP175-32000 IFRM04N35B1/L IFRM04P1513/S35L IFRM06P1703/S35L IFRM08P1501/S35L IFRM12N17G3/L IFRM12P17G3/L IFRM12P3502/L IFRM12P37G1/S14L ILFK12E9189/I02 ILFK12E9193/I02 IMM2582C OISN-013 25.161.3253.0 25.332.0653.1 25.352.0653.0 25.352.0753.0