

KN304107

CAPACITIVE SENSORS • NORM SWITCHING DISTANCE

sensor capacitive, M30x1.5 81long, Non-flush, Sn: 5-20, 20-250V AC, Two-wire NO, Cable 2m PVC, IP67, PBT, LED, Manual adjustment



MECHANICAL FEATURES

| | |
|--|------------------------|
| Active area material of sensor | PA 6.6 (synthetic) |
| Ambient temperature | -25 °C ... 70 °C |
| Cable length | 2 m |
| Degree of protection (IP) | IP67 |
| Design | Cylinder, screw-thread |
| Housing material | PBT |
| Material of cable sheath | PVC |
| Mechanical mounting condition for sensor | Non-flush |
| Number of cores | 2 |
| Pressure-proof | - |
| Sensor length | 81 mm |
| Thread length | 40 mm |
| Thread pitch | 1.5 mm |
| Thread size, metric | 30 |

ELECTRICAL FEATURES

| | |
|---|-------------------|
| Cascadable | - |
| Correction factor (glass) | 0.6 |
| Correction factor (oil) | 0.5 |
| Correction factor (PVC) | 0.5 |
| Correction factor (wood) | 0.6 |
| Hysteresis | 15 % |
| Min. output current | 5 mA |
| No-load current | 15 mA |
| Rated control supply voltage U_s at AC 50HZ | 20 V ... 250 V |
| Rated switching current | 300 mA |
| Setting procedure | Manual adjustment |
| Suitable for safety functions | - |
| Supply voltage | 20 V ... 250 V |
| Switching distance | 20 mm |
| Switching distance | 5 mm ... 20 mm |
| Switching frequency | 15 Hz |
| Type of electrical connection | Cable |

ELECTRICAL FEATURES

| | |
|--|-----------------------|
| Type of switching function | Normally open contact |
| Type of switching output | Two-wire |
| Voltage drop | 10 V |
| Voltage type | AC |
| With LED display | + |
| With monitoring function of downstream devices | - |

OTHER FEATURES

| | |
|-----------------|---|
| Level detection | + |
|-----------------|---|

Other

| | |
|----------------------|-------------------------|
| Packaging dimensions | 76.0mm x 50mm x 121.0mm |
| Shipping weight | 0.18kg |
| Tariff code | 85365080 |


Classification

| | |
|-------------------|----------|
| ipf product group | 243 |
| eClass 8.0 | 27270102 |
| eClass 9.0 | 27270102 |
| eClass 9.1 | 27270102 |
| ETIM-5.0 | EC002715 |
| ETIM-6.0 | EC002715 |
| ETIM-7.0 | EC002715 |

Connection



Dimensional drawing



Installation



Mounting / installation may only be carried out by a qualified electrician!

Disposal



Safety warnings

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.

Never use these devices in applications where the safety of a person depends on their functionality.

LED lighting systems can generate intensive UV radiation, which can damage your eyes in case of improper use. The manufacturer cannot be held responsible for damages that result from improper use or connection.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Proximity Sensors](#) category:

Click to view products by [IPF ELECTRONIC](#) manufacturer:

Other Similar products are found below :

[01.001.5653.1](#) [70.340.1028.0](#) [70.360.2428.0](#) [70.364.4828.0](#) [70.810.1053.0](#) [72.360.1628.0](#) [73.363.6428.0](#) [8027AL20NL2CPXX](#) [FYCC8E1-2](#)
[9221350022](#) [922AA2W-A9P-L](#) [PLS2](#) [GL-12F-C2.5X10\(LOT3\)](#) [972AB2XM-A3N-L](#) [972AB3XM-A3P-L](#) [PS3251](#) [980659-1](#) [QT-12](#) [E2E2-](#)
[X5M41-M4](#) [E2E-X14MD1-G](#) [E2E-X2D1-G](#) [E2EX2ME2N](#) [E2EX3D1SM1N](#) [E2E-X4MD1-G](#) [E2E-X5E1-5M-N](#) [E2E-X5Y2-N](#) [E2E-X7D1-](#)
[M1J-T-0.3M-N](#) [E2K-F10MC1](#) [5M](#) [EH-302](#) [EI3010TBOP](#) [EI5515NPAP](#) [MS605AU](#) [EP175-32000](#) [IFRM04N35B1/L](#) [IFRM04P1513/S35L](#)
[IFRM06P1703/S35L](#) [IFRM08P1501/S35L](#) [IFRM12N17G3/L](#) [IFRM12P17G3/L](#) [IFRM12P3502/L](#) [IFRM12P37G1/S14L](#) [ILFK12E9189/I02](#)
[ILFK12E9193/I02](#) [IMM2582C](#) [OISN-013](#) [25.161.3253.0](#) [25.332.0653.1](#) [25.352.0653.0](#) [25.352.0753.0](#) [25.523.3253.0](#)