

KN306050

CAPACITIVE SENSORS • INCREASED AMBIENT TEMPERATURE

sensor capacitive, M30x1.5 70long, Non-flush, Sn: 5-100, 250°C, Amplifier Amplifier, Cable 2m FEP, IP67, V2A



MECHANICAL FEATURES

| Ambient temperature (MAX) | 250 °C |
|--|------------------------|
| Ambient temperatures < -25°C | + |
| Cable length | 2 m |
| Degree of protection (IP) | IP67 |
| Design | Cylinder, screw-thread |
| Housing material | Stainless steel (V2A) |
| Increased ambient temperatures > 80°C | + |
| Material of cable sheath | FEP |
| Mechanical mounting condition for sensor | Non-flush |
| Pressure-proof | - |
| Sensor length | 70 mm |
| Thread pitch | 1.5 mm |
| Thread size, metric | 30 |

ELECTRICAL FEATURES

| Cascadable | - |
|--|-------------|
| Reverse polarity protection | + |
| Short-circuit protection | + |
| Suitable for safety functions | - |
| Switching distance | 60 mm |
| Switching distance | 5 mm 100 mm |
| Type of electrical connection | Cable |
| Type of switching function | Amplifier |
| Type of switching output | Amplifier |
| With monitoring function of downstream devices | - |

OTHER FEATURES

| Level detection | + |
|-----------------|---|

Other


| Packaging dimensions | 76.0mm x 50mm x 121.0mm |
|----------------------|-------------------------|
| Shipping weight | 0.29kg |
| Tariff code | 85365019 |




Classification

| ipf product group | 242 |
|-------------------|----------|
| eClass 8.0 | 27270102 |
| eClass 9.0 | 27270102 |
| eClass 9.1 | 27270102 |
| ETIM-5.0 | EC002715 |
| ETIM-6.0 | EC002715 |
| ETIM-7.0 | EC002715 |

Connection



Dimensional drawing



Installation



Mounting / installation may only be carried out by a qualified electrician!

Disposal



Safety warnings

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information. Never use these devices in applications where the safety of a person depends on their functionality.

LED lighting systems can generate intensive UV radiation, which can damage your eyes in case of improper use. The manufacturer cannot be held responsible for damages that result from improper use or connection.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Proximity Sensors category:

Click to view products by IPF ELECTRONIC manufacturer:

Other Similar products are found below:

01.001.5653.1 70.340.1028.0 70.360.2428.0 70.364.4828.0 70.810.1053.0 72.360.1628.0 73.363.6428.0 8027AL20NL2CPXX FYCC8E1-2 9221350022 922AA2W-A9P-L PLS2 GL-12F-C2.5X10(LOT3) 972AB2XM-A3N-L 972AB3XM-A3P-L PS3251 980659-1 QT-12 E2E2-X5M41-M4 E2E-X14MD1-G E2E-X2D1-G E2EX2ME2N E2EX3D1SM1N E2E-X4MD1-G E2E-X5E1-5M-N E2E-X5Y2-N E2E-X7D1-M1J-T-0.3M-N E2FMX1R5D12M E2K-F10MC1 5M EH-302 EI3010TBOP EI5515NPAP MS605AU EP175-32000 IFRM04N35B1/L IFRM04P1513/S35L IFRM06P1703/S35L IFRM08P1501/S35L IFRM12N17G3/L IFRM12P17G3/L IFRM12P3502/L IFRM12P37G1/S14L ILFK12E9189/I02 ILFK12E9193/I02 IMM2582C OISN-013 25.161.3253.0 25.332.0653.1 25.352.0653.0 25.352.0753.0