


## OG020373

### OPTICAL SENSORS • FORKED LIGHT BARRIERS

sensor optical, fork, 34x14x60mm, fork width 2mm, 10-35V DC, 1x PNP NC/NO, Connector M8 3pin, IP67, Zinc die-cast+Plastic, Infrared light, 3kHz pulsed, Teach-In



#### MECHANICAL FEATURES

|                             |                  |
|-----------------------------|------------------|
| Ambient temperature         | -10 °C ... 60 °C |
| Degree of protection (IP)   | IP67             |
| Design                      | Cuboid           |
| Diameter detection          | -                |
| Fork depth                  | 40 mm            |
| Fork light barrier design   | Furcate          |
| Fork width                  | 2 mm             |
| Housing material            | Zinc die-cast    |
| Installation bracket        | -                |
| Material of optical surface | Plastic          |
| Sensor height               | 34.5 mm          |
| Sensor length               | 14 mm            |
| Sensor width                | 60 mm            |

#### ELECTRICAL FEATURES

|                              |                     |
|------------------------------|---------------------|
| Analog output 0 V ... 10 V   | -                   |
| Analog output 4 mA ... 20 mA | -                   |
| Connection to amplifier      | -                   |
| Decay time                   | 0.17 ms             |
| Dynamic switching output     | -                   |
| Equipment protection class   | Protection class 3  |
| Hysteresis                   | 0.1 mm              |
| No-load current              | 35 mA               |
| Number of pins               | 3                   |
| Number of switching outputs  | 1                   |
| Operating voltage            | 10 V ... 35 V       |
| Rated switching current      | 200 mA              |
| Relative repeat accuracy     | 0.03 mm             |
| Repeatability +/-            | 30 µm               |
| Response time                | 0.17 ms             |
| Reverse polarity protection  | +                   |
| Scanning function            | Light-/dark-on mode |
| Setting procedure            | Teach-In            |

**ELECTRICAL FEATURES**

|                                      |   |
|--------------------------------------|---|
| Short-circuit protection             | +   |
| Switching frequency                  | 3000 Hz                                       |
| Type of electrical connection        | Connector M8                                  |
| Type of switching function           | Normally closed contact/normally open contact |
| Type of switching output             | PNP   |
| Type of the forked light barrier     | Standard                                      |
| Voltage drop                         | 2 V   |
| Voltage type                         | DC  |
| With communication interface, analog | -   |
| With communication interface, RS-232 | -   |
| With other analog output             | -   |
| With time function                   | -   |

**OPTICAL FEATURES**

|                     |        |
|---------------------|--------|
| Min. object size    | 0.5 mm |
| Resolution          | 500 µm |
| Light beam form     | Point  |
| Pulsed light source | +      |

**Other**


|                      |                           |
|----------------------|---------------------------|
| Packaging dimensions | 77.0mm x 25.0mm x 123.0mm |
| Shipping weight      | 0.1kg                     |
| Tariff code          | 85365019                  |

**Classification**

|                   |          |
|-------------------|----------|
| ipf product group | 110      |
| eClass 8.0        | 27270909 |
| eClass 9.0        | 27270909 |
| eClass 9.1        | 27270909 |
| ETIM-5.0          | EC002720 |
| ETIM-6.0          | EC002720 |
| ETIM-7.0          | EC002720 |

**Connection**

## Dimensional drawing



## Installation



Mounting / installation may only be carried out by a qualified electrician!

## Disposal



## Safety warnings

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information. Never use these devices in applications where the safety of a person depends on their functionality. LED lighting systems can generate intensive UV radiation, which can damage your eyes in case of improper use. The manufacturer cannot be held responsible for damages that result from improper use or connection.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Photoelectric Sensors](#) category:*

*Click to view products by [IPF ELECTRONIC](#) manufacturer:*

Other Similar products are found below :

[7442AD2X5FRX](#) [EX-19B-LP](#) [EX-19SB-PN](#) [7443AR0X5FRX](#) [7452AD4D4NNX](#) [7694ADE04DS2X](#) [FE7C-FRC6S-M](#) [FX-305](#) [PM-R24-R](#)  
[Q45VR2FPQ](#) [13104RQD07](#) [E3JUXM4MN](#) [E3L2DC4](#) [E3S3LE21](#) [E3SCT11M1J03M](#) [E3SDS20E21](#) [E3VDS70C43S](#) [E3XNM16](#) [BR23P](#)  
[HOA6563-001](#) [OJ-3307-30N8](#) [OS-311A-30](#) [P32013](#) [P34036](#) [P43004](#) [P60001](#) [PB10CNT15PO](#) [S14132](#) [935286-000](#) [S52101](#) [S56258](#) [FD-](#)  
[SN500](#) [FE7B-FDRB6-M](#) [SU-79](#) [T36342](#) [T40300](#) [T60001](#) [PD60CNX20BP](#) [FX-302-HY](#) [FZS](#) [PM-T64W](#) [PZ2-51P](#) [CX-491-P-J](#) [CYNUTX10](#)  
[UZB802](#) [UZB803](#) [UZFRG1](#) [UZFRG4](#) [UZFRT4](#) [UZFTT8](#)